Coded Caching over Realistic and Scalable Wireless Networks

vorgelegt von
Mozhgan Bayat, M.Sc.
ORCID: 0000-0002-8784-1157

an der Fakultät IV - Elektrotechnik und Informatik
der Technischen Universität Berlin
zur Erlangung des akademischen Grades

Doktorin der Ingenieurwissenschaften
- Dr.-Ing. -

genehmigte Dissertation

Promotionsausschuss:

Vorsitzender: Prof. Dr. Rafael Schaefer

Gutachter: Prof. Dr. Giuseppe Caire

Gutachter: Prof. Dr. Olav Tirkkonen

Gutachterin: Prof. Dr. Mari Kobayashi

Tag der wissenschaftlichen Aussprache: 6. November, 2020

Berlin 2020

To my parents, Akram and Jafar
and
to Elnaz Nabiyyi, one of the victims of the flight PS752

Abstract

The coded caching scheme proposed by Maddah-Ali and Niesen (MAN) is designed to reduce peak hours traffic by partially prefetching the files in end users' cache memory in low traffic hours and sending the requested files through multicast messages. This scheme was proved to be optimal under the constraint of uncoded prefetching and was originally proposed for a so-called single bottleneck link network. This dissertation goes beyond the unrealistic bottleneck network and extends the MAN scheme to a class of two-hop wireless networks consisting of one server connected via fronthaul links to a layer of H helper nodes, which in turn communicate via a wireless access network to K users. The proposed schemes in this work achieve full spatial scalability with an arbitrary number of users and the multicast rate does not vanish as the number of users in the network increase. This dissertation primarily focuses on interference management techniques. This work includes several network models with the first model in Chapters 2 and 3 embracing the path loss and channel gain, while in Chapter 4 orthogonal links (topological model) and interference collision model (protocol model) were considered. In the first model, users are able to use their multiple antennas to receive their requested multicast message through a fixed number of helpers with a non vanishing rate. Furthermore, a scalable video streaming service with two different qualities was implemented using the proposed delivery scheme, allowing users with better channel quality to decode a high quality version of the requested video file, which results in lower distortion levels. The routing scheme proposed in the final chapter delivers the multicast messages through the helpers with orthogonal channels to the receivers by formalizing a Linear Program (LP) which can be solved optimally in linear time in terms of the number of users in very large networks. Furthermore, a novel scheme that serves users as they become interference-free is proposed, which has a practical appeal since it could be implemented via the CSMA protocol. These approaches simultaneously solve many of the open practical problems identified as stumbling blocks for the application of coded caching in practical scenarios, namely: asynchronous streaming sessions, finite file size, subpacketization and high complexity of the MAN scheme, scalability of the scheme to large and spatially distributed networks, user mobility, and random activity (users joining and leaving the system at arbitrary times), decentralized prefetching of the cache contents.

Zusammenfassung

Das von Maddah-Ali und Niesen (MAN) vorgeschlagene Coded Caching Schema zielt darauf ab, den Datenverkehr zu Spitzenzeiten zu reduzieren, indem die Dateien im Cache-Speicher der Endbenutzer zu verkehrsarmen Zeiten teilweise vorgeladen werden und die angeforderten Dateien über Multicast-Nachrichten gesendet werden. Dieses Schema erwies sich unter der Einschränkung des uncodierten Prefetchings als optimal und wurde ursprünglich für eine so genannte Single-Bottleneck-Link Netzwerk entworfen. Diese Dissertation geht über das unrealistische Bottleneck Netzwerk hinaus und erweitert das MAN-Schema auf eine Klasse von drahtlosen Two-Hop Netzwerken mit einem Server, der über Fronthaul-Verbindungen zu einer Schicht von H -Hilfsknoten verfügt, die ihrerseits über ein drahtloses Netzwerk mit K -Benutzern kommunizieren.

Diese Dissertation befasst sich in erster Linie mit Interferenzmanagement-Techniken. Diese Arbeit umfasst mehrere Netzwerkmodelle, wobei das erste Modell in Kapitel 2 und 3 den Pfadverlust und die Kanalverstärkung umfasst, während Kapitel 4 orthogonale Verbindungen (topologisches Modell) und das Interferenz-Kollisionsmodell (Protokollmodell) berücksichtigt. Im ersten Modell sind die Benutzer in der Lage, mehrere Antennen zu verwenden, um ihre angeforderte Multicast-Nachricht über eine feste Anzahl von Helfern zu empfangen. Darüber hinaus wurde ein skalierbarer Video-Streaming-Dienst mit zwei verschiedenen Qualitäten unter Verwendung des vorgeschlagenen Bereitstellungsschemas implementiert, der es Benutzern mit besserer Kanalqualität ermöglicht, eine qualitativ hochwertige Version der angeforderten Videodatei zu dekodieren, was zu einer geringeren Verzerrung führt. Das im letzten Kapitel vorgeschlagene Routing-Schema liefert die Multicast-Nachrichten über die Helfer mit orthogonalen Kanälen an die Empfänger, indem es ein *Lineares Programm* (LP) formalisiert, das in linearer Zeit in Bezug auf die Anzahl der Benutzer optimal gelöst werden kann. Darüber hinaus wird ein neuartiges Schema vorgeschlagen, das den Nutzern hilft, wenn sie störungsfrei werden. Das wäre auch von praktischer Bedeutung, da es über das CSMA-Protokoll implementiert werden könnte. Diese Ansätze lösen gleichzeitig viele der offenen praktischen Probleme, die als Stolpersteine für die Anwendung von Coded Caching in praktischen Szenarien identifiziert wurden, nämlich: asynchrone Streaming-Sitzungen, endliche Dateigröße, die hohe Komplexität des MAN-Schemas, die Skalierbarkeit des Schemas auf große und räumlich verteilte Netzwerke,

Benutzermobilität und Zufallsaktivität (Benutzer treten dem System zu beliebigen Zeiten bei und verlassen es wieder), dezentrales Prefetching der Cache-Inhalte.

Acknowledgements

I would like to express my sincere thanks and appreciation to my supervisor Prof. Giuseppe Caire for offering me the opportunity to work with him. His insightful comments from the very beginning, and his continued support and patience guided me through this gratifying journey. I gratefully acknowledge the funding scholarship that made my Ph.D. possible. I was funded by the Alexander von Humboldt Professorship for my first four years and by European Research Council for the last six months.

I would like to thank the members of the guidance committee Prof. Olav Tirkkonen and Prof. Mari Kobayashi for devoting their time to be referees of this thesis. I am also fortunate to have had incredibly talented collaborators, each of which has impacted me in some way. I am forever grateful to my co-authors Dr. Ratheesh K. Mungara who believed in me early in my research career and provided me with an opportunity to collaborate with him and I would like to express my gratitude to Dr. Kai Wan for the time and patience that he donated towards our joint work and for always reviewing them and instantly providing the most useful feedbacks. I also would thank all my friends and colleagues at the Technische Universität Berlin Xiaoshen, Elham, Jana, Muah, Hamdi, Mahdi, Saied, Thomas, Cakan, Alex, Eleftherios, Xinpeng, Andreas, Rafael and all the new colleagues, I really appreciate their supports and enjoyed our conversations.

A special thank you to all my friends Elnaz, Sima, Saba, Alireza, Parisa, Sheyda, Esmat, and many more for making this journey enjoyable. Finally, I am forever indebted to my parents, Akram and Jafar, and my brothers, Ramin and Ali, and sister in law, Zahra, and my niece, Sana for their unwavering support, countless sacrifices and boundless love during my studies and throughout my life. My parents always strongly motivated me from very beginning when I was a student. Last but not least, I am thankful to Kiril for encouraging me in every step of the way, and endless support throughout my Ph.D. journey.

*Mozhgan Bayat,
Berlin, Nov 2020*

Contents

1. Introduction	1
1.1. Background and Motivation	1
1.1.1. Motivation for Caching	1
1.1.2. Fundamentals of the Coded Caching Scheme (MAN)	2
1.1.3. Coded Caching beyond Error-Free Shared Link	5
1.1.4. Tackling the Complexity of Coded Caching	7
1.2. Outline and Contributions	7
1.3. Notation, Abbreviations and Definitions	9
1.4. Publications	11
2. Broadcast Wireless Network with Zero Forcing Receiver	13
2.1. Background and Motivation	13
2.2. System Model	15
2.3. Main Results	17
2.3.1. Partial Zero-Forcing Detection	18
2.3.2. PZF with Successive Interference Cancellation	26
2.4. Numerical Results	30
2.5. Summary and Conclusion	32
3. Lossy Cache Aided Broadcast Channel	35
3.1. Background and Motivation	35
3.2. System Model and Definition	36
3.3. System Analysis	37
3.3.1. Time-Division Multiple Access (TDMA)	37
3.3.2. Superposition Coding	41
3.3.3. Multidimensional Decoding Error Probability	43
3.4. Suboptimal Rate and Cache Allocation	46
3.5. Results and Discussions	47
3.6. Conclusion	47

4. Multicast Routing Scheme in Practical Wireless Networks	51
4.1. Background and Motivation	51
4.1.1. Contributions	53
4.2. Topological Networks of Non-Interfering Links	54
4.2.1. System Model	55
4.2.2. Coded Caching Scheme	57
4.2.3. Centralized Coded Caching and Routing Optimization	58
4.2.4. Divide and Conquer Greedy Optimization	60
4.2.5. Decentralized Coded Caching with Cache Replication	61
4.3. Networks with Broadcast Constraints and Collision Interference	65
4.3.1. System Model	65
4.3.2. Reuse with per Cell Multiround Delivery	67
4.3.3. Avalanche Scheduling Scheme	70
4.4. Results and Discussions	74
4.5. Conclusion	77
5. Conclusion and Future work	79
5.1. Future Work	80
A. Stochastic Geometry	83
A.1. Proof of (2.19), (2.20)	83
A.2. Proof of (A.15) and (A.18)	84
A.3. Proof of (2.28) and (2.29)	86
A.4. Proof of Theorem 1	88
B. Linear Programming	91
B.1. Proposed Scheme by Independent Sets of Interference Graph	91
Publication List	95
References	95
Bibliography	97

1. Introduction

1.1. Background and Motivation

1.1.1. Motivation for Caching

Given the ever growing amount of traffic generated within the internet being transmitted via wireless networks with limited bandwidth, wireless networks should exploit the phenomenal progress made both in the pricing and capacity of data storage devices, the drastic increase in computational power, while also taking the users' consumption patterns into account and alleviate the burden of increased traffic during busy hours. Nowhere is this more apparent than the growing consumption of on-demand video and audio streaming services with prominent platforms like Youtube, Netflix and Spotify garnering billions of users on a daily basis. This calls for a clever usage of the low cost storage to cache data in network design. Due to the complexity of the transmission of traffic to the end user, a large variety of solutions were proposed to optimize every step of the process. In LTE, the *evolved Multimedia Broadcast Multicast Service* (eMBMS) standard was designed to simultaneously multicast popular common content (e.g., live TV channels) to a large number of users in a wide area via the simultaneous transmission from multiple base stations (multipoint multicasting). While addressing vital issues it has left much to be desired as the by-far favorite media user consumption pattern over internet consists of on-demand content delivery like in the streaming services previously mentioned. Caching addresses this issue by duplicating parts of the content in the end user's storage during off-peak hours and using these copies to recreate the content during peak hours, where the user's demands are known.

The caching strategy can further be adapted to be better suited to wireless networks which exploits the inherent *asynchronous content reuse* of on-demand content delivery and has been widely advocated in several contexts (e.g., see [16, 35, 50, 51, 56, 59]). The authors in [16] introduced femto caching in heterogeneous wireless networks, where edge nodes possess high storage, are placed in a fixed position within the cell and cache popular files requested by mobile users. The aforementioned work is based on uncoded caching, where the demanded files are both stored and transmitted in their original form. That is to say that the server and the base stations directly transmit the uncached bits of each demanded

file through the network. The gain achieved by uncoded schemes is referred to as the *local caching gain*. An alternative approach would be to consider *coded caching* strategies, where the users' cache content is exploited as side information so that coded messages are multicast and are simultaneously useful to multiple users; in other words, coded caching creates multicast opportunities and provides *global caching gain* defined later. Maddah-Ali and Niesen [36, 37] (for brevity referred to as MAN henceforth) proposed a novel coded caching scheme that creates multicast opportunities to ensure a global caching gain is achieved. This scheme operates in two phases: a placement phase which takes place during off-peak times, and a delivery phase which takes place during peak times. We explain main idea of coded caching through a toy example.

Example 1. Consider the server has access to a library of two files $\{A, B\}$ each of which has length F bits and two users equipped with cache memory to save F bits. File A and B are divided into two equal length subfiles, $\{A_1, A_2\}$ and $\{B_1, B_2\}$ where $|A_1| = |A_2| = F/2$ and $|B_1| = |B_2| = F/2$. First, user 1 saves the subfiles A_1 and B_1 in its cache memory and user 2 saves the subfiles A_2 and B_2 in its cache memory. Then consider user 1 requests file A and user 2 requests file B . In MAN scheme, server transmits the multicast message $X = A_2 \oplus B_1$ of length $F/2$ to both users. User 1 has B_1 in its cache memory, after receiving X it can extract A_2 by doing $X \oplus B_1$. In a similar manner, user 2 can decode B_1 from the message X by using its own cache content. In this scheme, the server in total need to have a transmission of rate $R = F/2$ bits. On the other hand, in traditional uncoded caching, the server needs to transmit subfile A_2 to user 1 and in another transmission send subfile B_1 to user 2. In this scheme the server in total has transmission of rate $R = F$ bits.

As we have seen in above example, the coded caching scheme has a gain of $1/2$ in rate compared to the uncoded caching scheme, which we will refer to this gain as *global caching gain*. The coded caching scheme enables users to benefit from the cache memories across the network and provides global caching gain. The main distinction between these two gains is that local caching gain scales with the individual cache size, while global caching gain scales with the accumulative cache size.

1.1.2. Fundamentals of the Coded Caching Scheme (MAN)

The information theoretic formulation of the coded caching scheme was proposed in [36]. The problem, originally, was to study the fundamental limits of caching in an error-free broadcast channel. This section serves as an in-depth exploration of the aforementioned scheme. In this scenario the server has access to a library of N files $\mathcal{F} = \{W_1, W_2, \dots, W_N\}$

Figure 1.1.: MAN setting

each of which has a length of F bits. The server is connected to K users through an error-free shared link, which is referred to as the *bottleneck channel*. Each user k is equipped with cache memory Z_k of size MF bits, i.e. it is equal in length to M files. The normalized cache size is denoted as $\mu = \frac{M}{N}$ and is also referred to as the normalized/fractional cache memory. The setting of MAN scheme is illustrated in Fig. 1.1. The key idea is to treat the cache content as receiver side information and design the caches during the placement phase such that, during the delivery phase, the server can send coded multicast messages to satisfy multiple users' requests simultaneously.

The caching scheme consists of two phases, which are referred to as the placement and delivery phase. Coded caching is a way in which these two phases can be optimized. Please note that in certain works these phases are referred to as pre-fetching (or cache placement) and multicast transmission. During the placement phase, which is performed prior to the network's run time(i.e. peak hours), the users store segments of the files either in a specified manner (centralized scheme [36]) or at random (decentralized scheme [37]). Then, during the network runtime, users make requests from a file from library, to which the server responds with the transmission of coded multicast messages, computed such that each user can retrieve its requested subfile from the multicast codeword and its own cache content. The objective of the MAN scheme is to design a two-phase scheme so that the worst-case load over all possible demand configurations is minimized. For brevity, we denote the quantity MK/N by t . Note that t can be understood as the normalized aggregate (i.e. global) size of cache memories. For ease of exposition, we proceed while

assuming that t takes integer values.¹ In the centralized MAN scheme, each file W_i is partitioned into segments $\{W_{i,T} : T \subseteq [K], |T| = t\}$ and each user $k \in [K]$ caches all and only the segments $W_{i,T}$ for all the subsets T such that $T \ni k$. It is easy to check that the cache of each user must have size

$$N \frac{F}{\binom{K}{t}} \binom{K-1}{t-1} = MF. \quad (1.1)$$

In the delivery phase, given a uniform demand vector $\mathbf{d} \in [N]^K$, the server computes the codeword X obtained from the concatenation of blocks X_S for all $S \subseteq [K], |S| = t+1$. Each such block is given by

$$X_S = \bigoplus_{k \in S} W_{d_k, S \setminus \{k\}}, \quad (1.2)$$

where we observe that for any S of size $t+1$ and $k \in S$, the set $S \setminus \{k\}$ is a subset of size t , such that $W_{d_k, S \setminus \{k\}}$ are effectively segments of the file desired by user k and cached at all users $j \in S, j \neq k$. Assuming that $K < N$, the achievable rate in the centralized MAN scheme is given by

$$R = F \frac{K(1 - M/N)}{1 + KM/N}. \quad (1.3)$$

The rate here corresponds to the worst-case load, i.e. the number of bits that have to be communicated over the shared link to satisfy set of demands. Local caching gain from individual memory size is equal to $(1 - M/N)$ and global caching gain is equal to $(1/(1 + KM/N))$. The MAN scheme was then later extended to decentralized settings. In decentralized coded caching, during the placement phase each user k independently caches a subset of the μF bits of each file in a uniform manner. Such random symmetric independent decentralized placement was shown to be optimal (under uncoded prefetching) in the limit of infinite file size in [71]. During the delivery phase for any nonempty set, the server transmits a coded multicast message for any $\mathcal{S} \subset [K]$ and $|\mathcal{S}| = s$ ($s \in \{1, \dots, K\}$) as given in (1.2). The placement procedure of the decentralized scheme partitions each file W_i into 2^K subfiles, $W_i = \{W_{i,\mathcal{S}} | \mathcal{S} \subseteq [K], |\mathcal{S}| = \{0, 1, 2, \dots, K\}\}$. $W_{i,\mathcal{S}}$ denotes the part of the file W_i that are cached by users in the set $\mathcal{S}$. By the law of large numbers it follows that

$$|W_{i,\mathcal{S}}| = F \left(\prod_{j \in \mathcal{S}} \mu_j \right) \left(\prod_{k \notin \mathcal{S}} (1 - \mu_k) \right). \quad (1.4)$$

¹if not, a memory-sharing argument is used to multiplex between points for which this parameter is an integer [36].

For large enough F the rate can be approximated by

$$R_d = \frac{N(1 - M/N)}{M} (1 - (1 - M/N)^K). \quad (1.5)$$

When $N \geq K$ the MAN scheme was proved to be optimal under the constraint of uncoded placement (i.e., each user directly stores a collection of segments of the library files in its cache) [29]. However for the case with $K > N$, the authors in [71] observed that the algorithm proposed in [36] produces redundant transmissions. They improved the delivery phase of the original MAN scheme and finally demonstrated the optimality of the proposed scheme through a matching converse for all possible values of N and K under uncoded prefetching. The peak rate or worst case rate when $K > N$ is characterized as follows

$$R = \frac{\binom{K}{\mu+1} - \binom{K - \min\{K, N\}}{\mu+1}}{\binom{K}{\mu}}. \quad (1.6)$$

1.1.3. Coded Caching beyond Error-Free Shared Link

The coded caching scheme introduced by the MAN scheme was originally proposed for an idealized single bottleneck network, where a server is connected to K users through a shared error-free link of given capacity. Based on the coded caching idea, several other network topologies have been studied and explored beyond error free or orthogonal links. In practice, most communication systems possess a more complicated network topology, which consists of more than a single broadcast link. A particularly relevant topology for the present work is the so-called *combination network*, formed by the server, a layer of N_E helpers (alternatively referred to as edge nodes or access point in other works), and a second layer of end users. In the combination network there are exactly $K = \binom{N_E}{L}$ users, each of which is connected to a distinct unordered subset of L out of N_E helpers (from which the name “combination” network derives from). All links are error-free and orthogonal in [24, 25, 41, 65, 67, 72]. Fig. 1.2 illustrates a small combination network with 3 helpers and $L = 2$.

In [25] the authors applied the centralized MAN algorithm to create each coded multicast message, which is then encoded with a (N_E, L) *Maximum Distance Separable* (MDS) code and then transmitted to N_E helpers. The users receive messages from the connected helpers. Each user receiving L out of the N_E coded blocks will be able to decode the whole coded message. The server transmits a different MDS coded symbol for each MAN multicast message to each helper, which in turn broadcasts it to the connected users. Notice that while the MDS coded scheme of [25] applies to any network topology as long as each user can receive from at least L helpers, the scheme of [72] critically hinges on the

Figure 1.2.: Combination network setting

combination network topology and therefore does not generalize to networks with random topology, which is the main focus of this dissertation. In [65, 67] further improvements on combination networks were presented, and cache-aided multiple helper networks with random topology were considered in [41], where each user is randomly connected to L helpers. By observing that for each helper, there are some MAN multicast messages which are not desired by any of its connected users, the authors presented an improved delivery strategy with respect to [25] by avoiding transmitting MDS coded symbols to the helpers which are not connected to at least one user desiring these symbols.

In the MAN scheme framework the prefetching phase is an offline operation that costs no transmission resources.² This is meaningful when the prefetching phase is performed at a time-scale much larger than the one at which the users make their content requests. For example, in a video-server application (e.g., Netflix), it is reasonable to assume that a fixed number N of the most popular movies are maintained in the system, and this list is updated every week by adding some new movies and removing some obsolete ones, such that the prefetching phase can be performed $\sim$ once per week, using the home internet connection. In contrast, for a wireless mobile network, the network topology may change much faster. A typical video streaming session lasts between 10 and 100 minutes. Consider a vehicular network with cars moving in an urban areas. It is clear that in this case the network topology may change significantly even within a single streaming session. In the context of such rapidly changing network topology, designing the prefetching phase as a function of the network topology is *practically meaningless*. Hence, it is interesting to design systems according to a *separation principle* between caching and physical-layer (PHY) transmission, where the caching (i.e., the prefetching and the formation of MAN multicast message) is completely agnostic of the underlying network topology, while the

²In fact, the prefetching phase plays the same role as the “code generation” in a standard information theoretic setting [11].

delivery of MAN multicast message is implemented [18] which has shown that separation is indeed a good thing to do. Motivated by the separation approach, several works have considered the delivery of the multicast message(s) generated by the MAN scheme through some specific wireless PHY and network topology. In [60] the authors focused on applying the multi-server *linear network* setting of [61] to the scenario of a multiuser MIMO *downlink* (DL) with *Channel State Information at the Transmitter* (CSIT).

1.1.4. Tackling the Complexity of Coded Caching

The coded caching algorithm requires splitting the files into $\binom{K}{t}$ subfiles to achieve caching gain t . The drawback of this algorithm is that the number of subfiles is increasing exponentially with K . For example, consider that the number of users in the network is $K = 10, 100, 1000$ and $t = 3$; by a simple calculation we can verify that the number of subfiles will be order of $10^2, 10^5, 10^8$ respectively. Not only is the complexity of the algorithm increasing exponentially with number of users K , but it is also not possible for finite length files to be divided into an exponentially increasing number of segments. This subpacketization bottleneck becomes a big challenge in designing coded caching algorithms. The authors in [61] were one of the first to combine the coded caching gain with the spatial multiplexing gain. They considered L multiple servers connected to K users through a network. Their work can be considered as MISO BC with L antennas. The multiplexing gain of L users and an additional theoretical caching gain of t can be achieved through their work.

Work [43] explored a scenario with multiple transmitters equipped with cache. Both works [43, 61] explored networks with multiple transmitters and combined the coded caching and multiplexing gain but maintained a high exponential subpacketization order. The authors in the recent work [32] revealed that having multiple transmitting antennas dramatically reduces the subpacketization bottleneck of coded caching by reducing it to approximately its L -th root. Works [27, 48] proposed a new class of coded caching algorithm, the so-called coded caching with cache replication, which has a significantly lower subpacketization order. In this scheme, users are divided into groups with L members. Each group separately and sequentially serves an independent MAN scheme.

1.2. Outline and Contributions

This dissertation concerns itself with extending the MAN scheme to a two-hop broadcast network and mainly deals with the design of algorithms that optimize physical layer performance. The main aspects that are addressed at the physical layer are interference management, channel coding, subpacketization order as well as minimizing the outage

probability and delivery latency. Furthermore, a novel routing algorithm on the network layer is proposed.

In **Chapter 2** we develop a physical layer model that applies the preexisting coded caching scheme for a combination network to the aforementioned two-hop broadcast network. In order to apply the coded caching paradigm proposed by the MAN scheme to a spatially distributed wireless network, the chapter starts from a variant of the MAN scheme successively proposed for combination networks, where the multicast message is further encoded by a MDS code. The MDS-coded blocks are sent to multiple spatially distributed single-antenna helpers, which in turn transmit at a fixed rate with no channel state information. The users have multiple antennas and they obtain receiver channel state information from standard downlink pilots and can select to decode a desired number of helper transmissions, while either nulling the others or treating them as noise. The users are then able to decode their requested file if they successfully decode L transmissions of the helpers. This parameter is referred to as the macro diversity order. The fundamental underlying transmission mechanism is *multipoint multicasting*, where each user can independently (in a user-centric manner) decide which helper to decode, without any explicit association of users to helpers. The proposed scheme achieves full spatial scalability in the following sense: for an extended network with arbitrary constant ratio of users per helper and area $A = O(N_E)$, where N_E denotes the number of helpers, the system achieves a per-user delivery rate that does not vanish as $N_E \rightarrow \infty$.

Chapter 3 builds upon the same model as in the previous chapter and applies it to a multipoint multicasting video paradigm, where each video file in the library can be broadcast in varying degrees of quality. Each user can decide to decode any helper transmission by using a zero forcing receiver. Motivated by *Scalable Video Coding* (SVC), we consider successive refinement source coding in order to provide a “softer” tradeoff between the number of decoded helpers and the source distortion at each user receiver. Each level of quality is referred to as a layer. Unlike Chapter 2, the users are not restricted by a fixed macro diversity order, but are rather capable of obtaining a higher video quality by decoding more than L transmissions. The proposed system is *spatially scalable* in the sense that, for given users’ and helpers’ spatial density, the achieved distortion-delivery time performance is independent of the coverage area. We consider a scenario with two layers, referred to as the fundamental and enhancement layer respectively, with users being able to decode both layers only if they have a high enough channel coding rate. *Time-division multiple access* (TDMA) and superposition coding are used to transmit both layers in the same channel.

After exploring the pros and cons of MDS coding in our proposed physical layer, we then turn to addressing the issue of redundant parity blocks within our scheme. The scheme proposed in **Chapter 4** uses an alternative approach and extends the MAN caching scheme

to a class of two-hop helper networks including one server, and H helpers communicating with K users all of which are distributed according to a *Poisson Point Process* (PPP). The key strategy of our approach is routing the MAN multicast messages through the network and formulating the optimal routing scheme as a *Linear Program* (LP). The MAN scheme requires splitting the files into an exponentially large number of subfiles which renders it impractical in the case of a large number of users. By building upon the initial LP formulation we are then able to address this issue. In the last part of the chapter, we consider the “collision interference model” and achieve interference avoidance by routing packets through non-interfering helpers through a heuristic method. Through numerical simulations we show that our proposed model outperforms the existing frequency reuse scheme in terms of delivery latency. Our proposed scheme offers solutions to multiple challenges, namely asynchronous requests, finite file size, scalability of the scheme to large and spatially distributed networks, decentralized prefetching of the cache contents, reducing subpacktization order to linear.

1.3. Notation, Abbreviations and Definitions

We denote scalars, vectors, matrices and sets by lower case letters, lower case bold letters, upper case bold letters and calligraphic letters, i.e., x , $\mathbf{x}$, $\mathbf{X}$, $\mathcal{X}$, respectively. For two value a and b , we denote by $[a : b] = \{a, a + 1, \dots, b\}$, $[n] = [1 : n]$. We denote the probability mass function as $p(x) = \Pr(X = x)$, for x in (element of) $\mathcal{X}$ (discrete) and the probability density function as $f_X(x)$ (continuous). The symbol $|\cdot|$ indicates the number of elements of a set or the length of a sequence appearing as argument inside the bars. To specify a particular range of elements in a vector, we use the notation $\mathbf{a}_{[i:j]}$ to indicate that $\mathbf{a}$ is restricted to the elements i to j . If $i = 1$, it will be omitted $\mathbf{a}_{[i:j]}$, the same for $j = n$, $\mathbf{a}_{[i:]}$.

Notation

$\mathcal{N}(\mu, \sigma)$	Gaussian (normal) distribution with mean μ and variance σ
$\text{Unif}[a, b]$	Continuous uniform distribution between a and b
$\text{var}(X)$	Variance of the real-valued random variable X
$x \in \mathcal{X}$	x is an element of $\mathcal{X}$
$\mathcal{X} \times \mathcal{Y}$	Cartesian product of the sets $\mathcal{X}$ and $\mathcal{Y}$
$\mathcal{X}^n$	n -th Cartesian product of $\mathcal{X}$
$\mathbb{E}[X]$	The expected value of X : $\sum_{x \in \mathcal{X}} xp(x)$
$\min \mathcal{A},$ $\max \mathcal{A}$	The smallest and the largest number of the set
$(\cdot)^+$	$\max\{0, \cdot\}$
$ \cdot $	The absolute value or the cardinality, distinction is made clear in context
$\log(\cdot)$	The base 2 logarithm $\log_2(\cdot)$
$\oplus$	Binary addition (addition in $\mathbb{F}_2$)
$(a, b), [a, b]$	An open and a closed interval, respectively
$(a, b], [a, b)$	Half-open intervals, which do not contain a or b , respectively
iff	if and only if
$:=$	equal by definition

Abbreviations

SNR	signal to noise ratio
SINR	signal to sum of noise and interference ratio
MAN	Maddah Ali and Niesen
LP	linear programming
PHY	physical
ZF	zero forcing
PZF	partial zero forcing
MAC	medium access control
TIN	treating interference as noise
MDS	minimum distance separable
CSIT	channel state information at the transmitter
DL	downlink
PPP	poisson point process
SIC	successive interference cancellation
MSE	mean square error

1.4. Publications

Copyright Information

Parts of this thesis have already been published as journal articles and in conference proceedings as listed in the publication list in the following section. ©2018-2020 IEEE. The following lists are the papers produced during my Ph.D. candidature.

Published

1. Mozhgan Bayat, Ratheesh K. Mungara, and Giuseppe Caire. "Coded caching in a cell-free SIMO network." WSA 2018; 22nd International ITG Workshop on Smart Antennas. VDE, 2018.
2. Mozhgan Bayat, Ratheesh K. Mungara, and Giuseppe Caire. "Achieving Spatial Scalability for Coded Caching via Coded Multipoint Multicasting." IEEE Transactions on Wireless Communications 18.1 (2018): 227-240.
3. Mozhgan Bayat, Cagkan Yapar, and Giuseppe Caire. "Spatially scalable lossy coded caching." 2018 15th International Symposium on Wireless Communication Systems (ISWCS). IEEE, 2018.
4. Mozhgan Bayat, Kai Wan, and Giuseppe Caire. "Routing-Based Delivery in Combination-Type Networks with Random Topology." 2019 IEEE 20th International Workshop on Signal Processing Advances in Wireless Communications (SPAWC). IEEE, 2019.

Submitted

1. Mozhgan Bayat, Kai Wan, and Giuseppe Caire. "Coded Caching over Multicast Routing Networks." arXiv preprint arXiv:2008.08900 (2020).

2. Broadcast Wireless Network with Zero Forcing Receiver

2.1. Background and Motivation

In this chapter we focus on the efficient delivery of the coded multicast message generated by the MAN scheme over a wireless extended network formed by K users and N_E helpers, such that the ratio K/N_E is an arbitrary constant, and the area of the network grows as $A = O(N_E)$ when N_E becomes large. Both the single bottleneck link network and the combination network are deterministic error-free models. In order to apply such caching paradigms to an actual wireless network, it is important to ensure that the content delivery rate does not vanish as the number of users and/or the network size become large. This represents a challenge in the presence of small-scale fading and distance dependent pathloss. We call *scalable* a scheme that achieves a non-vanishing per-user delivery rate as $K \rightarrow \infty$. In particular, for extended networks as defined above $K \rightarrow \infty$ implies that the network coverage area (A) must grow linearly with K . In this case, a scalable scheme shall be referred to as *spatially scalable*, since the scheme can provide a fixed positive delivery rate for an arbitrarily large coverage area. In this chapter the content server is connected through high-capacity backhaul links to N_E wireless helpers (e.g., access points, or remote radio heads or edge nodes). In the presence of a given set of users' demands, the server computes the MAN coded message and further encodes with a (L, N_E) Minimum Distance Separable (MDS) code, such that the whole message can be retrieved from any L out of N_E MDS-coded blocks, and where $L \geq 1$ is an integer parameter referred to as *macro-diversity order* of the system. The MDS-coded blocks are sent to the N_E helpers, that transmit them simultaneously on the same channel at some fixed PHY rate R bit/s/Hz. Each user in the system can choose to receive data from its best L helpers in a completely autonomous user-centric way. As long as a user is able to decode at least L helper transmissions, it will retrieve the whole MAN coded message and therefore its own requested file.

The network topology induced by this PHY scenario is somehow reminiscent of the combination network, with the fundamental difference that, in general, the number of users K not necessarily equal to $\binom{N_E}{L}$ and the nice symmetry of the combination network

is lost, since there are possibly more than one user associated to the same combination of L strongest helpers, while some other combinations of L helpers that are physically far apart will not be chosen by any user. Nevertheless, we argue that the combination network forms a useful good paradigm. In fact, the fully separated scheme based on the concatenation of the MAN with MDS coding can be seamlessly applied for the more general topology induced by the PHY of the spatially extended wireless network at hand. Notice also that this is not the case for more advanced schemes successively proposed for the combination network, exploiting its special topology (e.g., see [41, 65, 67, 72]). In this chapter, users are affected by both small-scale fading (e.g., Rayleigh fading as in [15, 45]) and by large-scale distance-dependent pathloss. A single base station multi-antenna approach as in [15, 45] will not be effective against the pathloss since the worst-case user rate can be made arbitrarily small with a network whose area grows as $A = O(K)$, such that the distance from the worst-case user and the base station grows as $O(\sqrt{K})$.

While [60] focused on the small K regime, with the goal of achieving the optimal cache-aided degrees of freedom, other works such as [15, 45] have considered schemes to serve multicast messages to a very large number of users K , such that the delivery rate does not vanish as $K \rightarrow \infty$. In particular, [45] considers the transmission from a single base station with n_{tx} antennas to K users and focuses on the worst-case user instantaneous rate, i.e., the common rate that can be sustained by the system when coding on a single fading state (a single realization of the $K \times n_{\text{tx}}$ channel matrix). In this dissertation's scenarios, like those in [45], the transmitter has no *Channel State Information at the Transmitter* (CSIT). This assumption is fully justified in the large K regime by the fact that gathering the CSIT for all users and for each fading coherence block would incur an enormous pilot overhead and consume the transmission resource completely. In this case, the worst-case user instantaneous rate is shown to vanish as $K \rightarrow \infty$ if $n_{\text{tx}} = O(1)$ and be bounded away from zero if n_{tx} grows at least as $\log K$.

The proposed system is extremely simple, since no coordination among users and between the users and the helpers is required, no CSIT at the helpers is required, no joint signal space precoding across the helpers is used, and only standard *Channel State Information at the Receiver* (CSIR) at each user is required, which can be obtained via a completely standard DL pilot scheme, for which each helper broadcasts a pilot beacon signal as done in virtually any cellular system in operation today (including eMBMS). Summarizing, the contributions of this chapter are: We provide a novel stochastic geometry performance analysis for the proposed system, focusing on the distribution of the per-user ergodic rate as a function of the (random) network topology. The analytical tools focus on optimizing the system, in particular, the macro-diversity order L of the scheme and the PHY coding rate R of the helper transmissions, as a function of the MAN parameters.

2.2. System Model

We consider a wireless network with N_E single-antenna helpers and K users, each equipped with an n_r -antenna array.¹ A server is connected to the helpers via an error-free backhaul data network of very high capacity and has access to a content library formed by N files indicated as $\mathcal{F} = \{W_1, W_2, \dots, W_N\}$, each of which has a size of F bits. The helpers are simple remote antenna terminals that simply transmit what they receive from the server. For the sake of conceptual simplicity we consider here the centralized MAN scheme [36] but everything can also be applied to its decentralized version [37] as well as to improved versions thereof that take into account possible repeated requests [71] or other schemes based on uncoded pre-fetching and optimized for finite file size F (e.g., see [27, 28, 64, 68]).

In our scheme, coded words X computed by coded multicast message in (1.2) is divided into L blocks of equal size, for some integer $L \leq N_E$, and MDS coding is applied to append $N_E - L$ parity blocks. Each MDS-coded block is treated as a symbol over a large finite field. The resulting N_E MDS-coded blocks are sent to the N_E helpers, such that each helper is associated to a distinct MDS-coded block. Eventually, the blocks are transmitted through an appropriate physical-layer (PHY) coded modulation scheme and sent in parallel, on the same time-frequency slot, from the different helpers. The users use their antenna array to detect and decode the PHY codewords of L helpers. Thanks to MDS coding, whenever a user k is able to decode L helpers messages, then it can reconstruct the whole multicast codeword X .² At this point, user k can decode the desired file d_k from X and its cache content, as detailed in [36]. Fig. 2.1 shows an example with $N_E = 5$ and $L = 2$, where all users that can decode 2 data streams from two distinct helpers can retrieve their requested file. The delivery latency, i.e., the time necessary to deliver all requests, is given by

$$T = \frac{1}{LR} \times \frac{F}{w} \times \frac{K(1 - \mu)}{1 + K\mu}, \quad (2.1)$$

where w is the bandwidth of the wireless channel and R is the PHY coding rate, expressed in bit/s/Hz and μ is normalized cache size at each user. This scheme is spatial scalable which means T does not vanish as K grows. Notice that T in (2.1) is given by the product of three factors: F/w depends on the file size and the system bandwidth (baudrate), and is

¹Typical hand-held devices operating at conventional cellular and WiFi frequency bands cannot host a large number of antenna elements. Nevertheless, for a relevant scenario we may think of a vehicular network where users are cars, which can host relatively large arrays, or a mmWave network, where a large number of antenna elements can be accommodated in a small form factor even on hand-held devices.

²The basic property of an MDS code is that it satisfies the Singleton bound with equality. In our case, a (L, N_E) code has minimum Hamming distance (in symbols) equal to $N_E - L + 1$. This implies that any $(N_E - L) \times (N_E - L)$ submatrix of the parity-check matrix has full rank. In turn, this means that the transmitted codeword can be uniquely identified if at least L MDS-coded symbols are received.

Figure 2.1.: A conceptual example of the proposed system with $N_E = 5$ and $L = 2$. User nodes make use of their beamforming antenna array to decode two out of five helper transmissions, by treating the others as noise.

fixed by the system design. The term $\frac{K(1-\mu)}{1+K\mu}$ is the MAN codeword length normalized by the file size [36]. Finally, $1/(LR)$ is the combined effect of MDS “macro-diversity order” L and the PHY coding rate. *For this system, the main design goal consists of determining L such that the product LR is maximized (i.e., the delivery latency is minimized) for a given target per-user outage probability.* From the PHY viewpoint, the goal for each user is to successfully decode the L strongest helpers. Assuming that the PHY codewords span a sufficiently large number of small-scale fading states, we denote by $C_{k,\ell}(\Phi)$ the achievable ergodic rate that user k can successfully decode with high probability (w.h.p.) from helper ℓ for a given decoding strategy (to be detailed later) and a given geometry Φ , i.e., a given placement of the helpers relative to user k . Without loss of generality, we can sort these achievable rates such that $C_{k,1}(\Phi), \dots, C_{k,L}(\Phi)$ are the largest rates over all the helpers. It follows that user k can obtain its requested file if

$$C_k^{(L)}(\Phi) = \min_{\ell \in [L]} C_{k,\ell}(\Phi) > R. \quad (2.2)$$

For a random geometry Φ , we can define the user outage probability as

$$P_{\text{out},k}(R) = \mathbb{P}(C_k^{(L)}(\Phi) \leq R), \quad (2.3)$$

given by the Cumulative Distribution Function (CDF) of $C_k^{(L)}(\Phi)$.

Furthermore, the case of PHY coding over a single fading state is quite irrelevant in the context of modern broadband communication systems. The existing 4G LTE and the forthcoming 5G systems are designed such that a codeword can span a large number of fading states in the time-frequency domain. For example, in a channel with bandwidth 20

MHz, PHY-layer coding with frame length 10 ms,³ small-scale fading coherence time of 1 ms and coherence bandwidth of 200 kHz, a codeword spans ~ 1000 nearly independent states (channel realizations). It is well-known that when a codeword spans between 100 and 1000 independent fading states (indeed, much less when channel hardening due to multiple antennas occurs), the ergodic rate (averaging with respect to the small-scale fading) rather than the instantaneous rate per fading state becomes a much more meaningful performance metric. It follows that, under the ergodic rate metric, the symmetric system scenario of [45] becomes completely trivial since all users have exactly the same ergodic rate. Motivated by the above observations, in this chapter we focus on a spatially extended network with non-symmetric users due to the fact that the pathloss between each user and the helpers is different, and depends on the users and helpers locations. As extensively discussed in [14, 42], in this context it is meaningful to consider the per-user ergodic rate where averaging (ergodic behavior) is with respect to the small-scale fading and conditioning is with respect to the random realization of the pathloss, which in turn depends on the random placement of users and helpers on the plane. Since such conditional ergodic rate is a function of the random network geometry, it is a random variable itself. Using stochastic geometry, we are able to characterize the distribution of such random variable under different detection schemes at the users' receivers. In particular, the tail of such distribution yields the user outage probability, which can be interpreted as the fraction of users in the system that cannot retrieve their requested file, since they are not able to decode at least L helpers transmissions. Since this probability is a constant strictly less than 1 (in fact, it can be made sufficiently small for a good choice of the system parameters), this means that a linear fraction of users can be served at non-vanishing delivery rate. In turn, this shows that the proposed system is spatially scalable in the presence of both small-scale Rayleigh fading and distance dependent pathloss.

2.3. Main Results

We assume that helpers are randomly located on the two-dimensional plane and are distributed according to a two-dimensional homogeneous Poisson Point Process (PPP) of density λ . The ensemble of the locations of the helpers is denoted by Φ . The propagation is characterized by small-scale Rayleigh fading that remains constant on time-frequency coherence blocks of n symbols (block fading model) and evolves according to a station-

³Notice that the 1 ms latency requirement of 5G does not apply for content distribution and video streaming, which is generally a much more elastic traffic, since at the streaming client there is a playback buffer that averages the channel instantaneous delivery rate over a window of several seconds of video. Therefore, it is really the average rate and its long-term fluctuations due to pathloss that count here, not the small-scale fading instantaneous realizations.

any ergodic process from block to block. Each receiving user acquires the DL CSIR from its surrounding helpers (e.g., through common DL pilots periodically broadcasted by the helpers). For simplicity, we do not consider CSIR error and pilot overhead in the present analysis. However, broadcasting DL pilots, or “beacon” signals, from the base stations/access points is common practice of any current cellular system and Wi-Fi network, so that the same type of overhead and (small) performance degradation incurred by any standard technology is to be expected in our system.

Without loss of generality, we can consider the performance of the typical user indexed by k and located at the origin. We sort the helpers according to their distance from user k in non-decreasing order, and let $j \in [N_E]$ be the index of the j -th closest helper to user k . The space-time signal received by user k is given by

$$\mathbf{Y}_k = \sum_{j=1}^{N_E} \sqrt{\beta r_{k,j}^{-\eta}} \mathbf{h}_{k,j} \mathbf{x}_j + \mathbf{N}_k \quad (2.4)$$

where $\mathbf{Y}_k \in \mathbb{C}^{n_r \times n}$ with n being the size of the fading blocks in symbols, $\mathbf{h}_{k,j} \in \mathbb{C}^{n_r \times 1}$ is the channel vector containing the small-scale fading coefficients from helper j to the array of user k , $\mathbf{x}_j \in \mathbb{C}^{1 \times n}$ is the coded-modulation block of symbol sent by helper j , $r_{k,j}$ is the distance between helper j and user k , η is the pathloss exponent, and β is the path loss intercept. The helpers transmit at a constant average power $\frac{1}{n} \mathbb{E}[\mathbf{x}_j \mathbf{x}_j^H] = P$. The noise samples in the matrix $\mathbf{N}_k$ are independent and identically distributed (IID) $\sim \mathcal{CN}(0, N_0)$. According to the independent Rayleigh statistics, $\mathbf{h}_{k,j}$ are IID across users and helpers and have IID components $\sim \mathcal{CN}(0, 1)$.

2.3.1. Partial Zero-Forcing Detection

We introduce here the *Partial Zero-Forcing* (PZF) receiver strategy, proposed for our system. Let $\mathbf{H}_k = [\mathbf{h}_{k,1}, \dots, \mathbf{h}_{k,N_E}]$ denote the $n_r \times N_E$ matrix of the channel coefficients from the helper antennas to user k antenna array, and, for a subset $\mathcal{B} \subseteq [N_E]$, let $\mathbf{H}_{k,\mathcal{B}}$ denote the submatrix formed by the columns with indices $j \in \mathcal{B}$. PZF consists of applying linear zero-forcing only with respect to the signals of the L nearest helpers, whereas the signals of the remaining helpers with indices $j > L$ are treated as noise. Assuming $n_r \geq L$, the receive filtering matrix of user k is defined as the pseudo-inverse of the $n_r \times L$ matrix $\mathbf{H}_{k,1:L}$. This is given by

$$\mathbf{H}_{k,1:L}^\dagger = \mathbf{H}_{k,1:L} (\mathbf{H}_{k,1:L}^H \mathbf{H}_{k,1:L})^{-1}. \quad (2.5)$$

Denoting by $\mathbf{h}_{k,\ell}^\dagger$, $1 \leq \ell \leq L$, the ℓ -th column of $\mathbf{H}_{k,1:L}^\dagger$ and by $\mathbf{q}_{k,\ell} = \mathbf{h}_{k,\ell}^\dagger / \|\mathbf{h}_{k,\ell}^\dagger\|$ the normalized receive filtering vector corresponding to the ℓ -th stream, the filtered output

$\tilde{\mathbf{y}}_{k,\ell} = \mathbf{q}_{k,\ell}^H \mathbf{Y}_k$ is written as

$$\tilde{\mathbf{y}}_{k,\ell} = \frac{(\mathbf{h}_{k,\ell}^\dagger)^H}{\|\mathbf{h}_{k,\ell}^\dagger\|} \mathbf{h}_{k,\ell} \sqrt{\beta r_{k,\ell}^{-\eta}} \mathbf{x}_\ell + \sum_{j=L+1}^{N_E} \frac{(\mathbf{h}_{k,\ell}^\dagger)^H}{\|\mathbf{h}_{k,\ell}^\dagger\|} \mathbf{h}_{k,j} \sqrt{\beta r_{k,\ell}^{-\eta}} \mathbf{x}_j + \tilde{\mathbf{z}}_k \quad (2.6)$$

where $\tilde{\mathbf{z}}_k$ is the filtered noise vector with IID components $\sim \mathcal{CN}(0, N_0)$. In the rest of this chapter, for the sake of analytical tractability, we focus on the case of an infinitely extended network (i.e., $N_E \rightarrow \infty$) and high-SNR interference limited performance (i.e., $N_0 \rightarrow 0$). As a result, the system becomes “scale-free”, that is, the results of our analysis are invariant to any non-zero scaling factor of the physical distances $r_{k,\ell}$ appearing in (2.6). The Signal-to-Interference Ratio (SIR) at user k receiver is given by

$$\text{SIR}_{k,\ell} = \frac{r_{k,\ell}^{-\eta} \|\mathbf{h}_{k,\ell}^\dagger\|^{-2}}{\sum_{j=L+1}^{\infty} r_{k,j}^{-\eta} |\tilde{h}_{k,j}|^2}. \quad (2.7)$$

Since $\mathbf{q}_{k,\ell}$ is a unit vector that is independent of $\{\mathbf{h}_{k,j} : j = L+1, L+2, \dots\}$, it follows that $\tilde{h}_{k,j} = \mathbf{q}_{k,\ell}^H \mathbf{h}_{k,j} \sim \mathcal{CN}(0, 1), \forall j \geq L+1$. Furthermore, a well-known property of the ZF linear detector is that in the case of Gaussian IID channel vectors the useful signal coefficient $\|\mathbf{h}_{k,\ell}^\dagger\|^{-2} = \mathcal{X}_{2(n_r-L+1)}$ is Chi-squared distributed with $2(n_r - L + 1)$ degrees of freedom [39] and mean $\mathbb{E}[\mathcal{X}_{2(n_r-L+1)}] = n_r - L + 1$. The ergodic rate with Gaussian inputs and treating interference as noise for the transmission of the ℓ -th closest helper at user k is given by

$$C_{k,\ell}(\Phi) = \mathbb{E} \left[\log \left(1 + \frac{r_{k,\ell}^{-\eta} \mathcal{X}_{2(n_r-L+1)}}{\sum_{j=L+1}^{\infty} r_{k,j}^{-\eta} |\tilde{h}_{k,j}|^2} \right) \middle| \Phi \right], \quad (2.8)$$

where the random variables $\mathcal{X}_{2(n_r-L+1)}$ and $|\tilde{h}_{k,j}|^2 : j > L$ are mutually independent, and the conditioning with respect to the geometry Φ determines the distances $r_{k,\ell}$ and $r_{k,j} : j > L$. In order to obtain analytically tractable expressions, we consider the following lower bound:

Proposition 1. *The ergodic rate in (2.8) is lower-bounded as*

$$C_{k,\ell}(\Phi) \geq \mathbb{E} \left[\log \left(1 + \rho_{k,\ell} \mathcal{X}_{2(n_r-L+1)} \right) \middle| \Phi \right], \quad (2.9)$$

where we define the local-average SIR

$$\rho_{k,\ell} = \frac{r_{k,\ell}^{-\eta}}{\sum_{j=L+1}^{\infty} r_{k,j}^{-\eta}}, \quad 1 \leq \ell \leq L. \quad (2.10)$$

□

Proof. From the convexity of the function $f(x) = \log(1 + a/x)$ for $a > 0$ and $x > 0$, and using $\mathbb{E}[|\tilde{h}_{k,j}|^2] = 1$, the result follows by applying Jensen's inequality with respect to the interference fading coefficients $|\tilde{h}_{k,j}|^2$, $j \geq L + 1$ in (2.8). $\square$

Next, we would like to eliminate the dependency on the distances $r_{k,j}$ with $j \geq L + 1$. To this purpose, we replace the conditioning with respect to Φ by the conditioning with respect to only $r_{k,\ell}$ and $r_{k,L}$, i.e., the ℓ -th and the L -th shortest distances from the origin. Furthermore, letting $I = \sum_{j=L+1}^{\infty} r_{k,j}^{-\eta}$ and noticing that $r_{k,j}$ for $j \geq L + 1$ depends on PPP points outside the disk of radius $r_{k,L}$ around user k while $r_{k,\ell}$ depend on PPP points inside the disk, we have that [20]. By applying this approximation and Jensen's inequality in (2.9), we obtain

$$C_{k,\ell}(\Phi) \gtrsim \mathbb{E} \left[\log \left(1 + \frac{r_{k,\ell}^{-\eta} \mathcal{X}_{2(n_r-L+1)}}{\sum_{j=L+1}^{\infty} r_{k,j}^{-\eta}} \right) \middle| r_{k,L}, r_{k,\ell} \right] \quad (2.11a)$$

$$\geq \mathbb{E} \left[\log \left(1 + \frac{r_{k,\ell}^{-\eta} \mathcal{X}_{2(n_r-L+1)}}{\mathbb{E}[I|r_{k,L}]} \right) \middle| r_{k,L}, r_{k,\ell} \right]. \quad (2.11b)$$

In order to calculate the conditional average interference term in (2.11b), we apply Campbell theorem [20, Theorem 4.1] and, for $\eta > 2$, we obtain

$$\mathbb{E}[I|r_{k,L}] = \frac{2\pi\lambda}{\eta-2} r_{k,L}^{2-\eta}. \quad (2.12)$$

Plugging (2.12) in (2.11b), we obtain the quasi-lower bound⁴ on the ergodic rate.

Proposition 2. *The quasi-lower bound on the ergodic rate is given by*

$$C_{k,\ell}^{\text{qlb}}(\Phi) = \mathbb{E} \left[\log \left(1 + \tilde{\rho}_{k,\ell} \mathcal{X}_{2(n_r-L+1)} \right) \middle| \Phi \right], \quad (2.13)$$

where we define the approximated conditional local-average SIR as

$$\tilde{\rho}_{k,\ell} = \frac{r_{k,L}^{\eta-2}}{r_{k,\ell}^{\eta}} \frac{\eta-2}{2\pi\lambda}, \quad 1 \leq \ell \leq L. \quad (2.14)$$

$\square$

Notice that $\tilde{\rho}_{k,\ell}$ is related to $\rho_{k,\ell}$ defined in (2.10) by replacing the denominator I of (2.10) with its conditional expectation given in (2.12). This approach yields analytically tractable expressions and is expected to provide an accurate approximation of the actual achievable ergodic rate for fixed geometry Φ because the interference term I contains the cumulative

⁴This is referred to as quasi-lower bound because of the approximation in (2.11a).

Figure 2.2.: CDFs of the exact and approximate local-average SIRs $\rho_{k,\ell}$ and $\tilde{\rho}_{k,\ell}$ with $n_r = 8$.

effect of many “far” helpers, such that it is expected that a sort of self-averaging effect kicks in. Fig. 2.2 compares the CDF of the local average SIR $\tilde{\rho}_{k,\ell}$ obtained via approximation in (2.14) against its exact form $\rho_{k,\ell}$ in (2.10). All the curves are obtained via Monte-Carlo simulations by setting the helper density $\lambda = 8$ Relays/km² (which means on average there is one helper in a circular cell of radius 200 m), the pathloss exponent $\eta = 3.75$. We assumed that the PZF is applied to cancel the $L = 4$ nearest interferers at the receiving user equipped with antenna array size $n_r = 8$. As it can be seen from Fig. 2.2, the CDFs of $\tilde{\rho}_{k,\ell}$ and $\rho_{k,\ell}$ are very close for a wide range of SIR. Similar results have been observed for different system parameters L , n_r and η . Notice also that the quasi-lower bound in (2.13) and the actual lower bound in (2.9) differ only by the replacement of $\rho_{k,\ell}$ with $\tilde{\rho}_{k,\ell}$. Since these terms appear inside the logarithm, their very small difference (as evidenced by the CDFs of Fig. (2.2)) plays an even more negligible role with respect to the ergodic rates. In order to proceed further, we shall make use of the following results on distance distribution in PPPs taken from [19, 38].

Lemma 1. *Given a homogeneous PPP Φ of density of λ , let r_n denote the n -th shortest distance of points of Φ from the origin. Then, the Probability Density Function (PDF) of r_n is given by*

$$f_{r_n}(v) = \frac{2(\pi\lambda)^n}{(n-1)!} v^{2n-1} e^{-\pi\lambda v^2}, \quad v \geq 0, \quad (2.15)$$

and the joint PDF of r_ℓ and r_n with $1 \leq \ell < n$ is given by

$$f_{r_\ell, r_n}(u, v) = \frac{4(\pi\lambda)^n e^{-\pi\lambda v^2}}{(n-\ell-1)! (\ell-1)!} (v^2 - u^2)^{n-\ell-1} v u^{2\ell-1}, \quad u, v \geq 0. \quad (2.16)$$

□

Using Lemma 1, we can obtain closed-form accurate approximations for the outage probability and the average delivery rate in terms of the macro-diversity order L , the receive antenna array size n_r , the pathloss exponent η , and the PHY coding rate R .

Outage Probability Derivation

Due to the difficulty of obtaining an exact closed-form expression for the local-average SIR, we derive an approximate expression based on the approach introduced in [1, 7]. First, the Laplace transform of $1/\tilde{\rho}_{k,\ell}$ is derived. Then, this is numerically inverted via Euler series expansion. Finally, the CDF of $\tilde{\rho}_{k,\ell}$ can be obtained in the form of finite series yielding accurate results with only a few terms (see [7]).

Lemma 2. *The sought approximated form for the CDF of $\tilde{\rho}_{k,\ell}$ is*

$$F_{\tilde{\rho}_{k,\ell}}(\gamma) \approx 1 - \gamma \frac{e^{A/2}}{2^B} \sum_{b=0}^B \binom{B}{b} \sum_{g=0}^{G+b} \frac{(-1)^g}{D_g} \operatorname{Re} \left\{ \frac{\mathcal{L}_{1/\tilde{\rho}_{k,\ell}}(\tau)}{\tau} \right\}, \quad (2.17)$$

where

$$\tau = \frac{(A + i2\pi g)\gamma}{2}. \quad (2.18)$$

The values $D_0 = 2$ and $D_g = 1$ for $g > 0$ and $A = 9.21$, $B = 5$ and $G = 8$ provide a satisfactory accuracy [46]. $\square$

The Laplace transform of $1/\tilde{\rho}_{k,\ell}$, for $s \in \mathbb{C}$, is given by the following compact expressions, proved in Appendix A.1.

Proposition 3. *The Laplace transform of $1/\tilde{\rho}_{k,\ell}$ takes on the following form:*

Case 1: For $\ell < L$

$$\mathcal{L}_{1/\tilde{\rho}_{k,\ell}}(s) = \sum_{n=0}^{L-\ell-1} \frac{(-1)^n \Gamma(L)}{(L-\ell-1)! (\ell-1)! (n+\ell)} \binom{L-\ell-1}{n} {}_2F_1\left(L, \eta'; \eta' + 1; \frac{-2s}{\eta-2}\right), \quad (2.19)$$

where $\eta' = 2\frac{n+\ell}{\eta}$ and ${}_2F_1(a, b; c; z)$ is the Gaussian hypergeometric function.

Case 2: For $\ell = L$

$$\mathcal{L}_{1/\tilde{\rho}_{k,\ell}}(s) = \left(\frac{2s}{\eta-2} + 1 \right)^{-L}. \quad (2.20)$$

$\square$

Fig. 2.3 illustrates the CDF of the approximated local-average SIR given in (2.17) with different sub-stream indices and different values of L with a received antenna array size

Figure 2.3.: CDF of the approximated local-average SIR ($\tilde{\rho}_{k,\ell}$) with $n_r = 8$. Solid curves correspond to the analysis in (2.17) while the dashed curves are obtained via simulation.

$n_r = 8$, helper density $\lambda = 8 \text{ Relays/km}^2$, and $\eta = 3.75$. Monte Carlo simulation of the CDF is also reported for comparison, and shows that our analytical approximation is accurate. The expectation with respect to $\mathcal{X}_{2(n_r-L+1)}$ in (2.13) can be calculated in closed form as

$$\begin{aligned} C_{k,\ell}^{\text{qlb}}(\tilde{\rho}_{k,\ell}) &= \mathbb{E}[\log(1 + \tilde{\rho}_{k,\ell} \mathcal{X}_{n_r-L+1}) | \Phi] \\ &= \mathcal{I}_{(n_r-L+1)}(\tilde{\rho}_{k,\ell}) \log(e), \end{aligned} \quad (2.21)$$

where with a slight abuse of notation we use $C_{k,\ell}^{\text{qlb}}(\tilde{\rho}_{k,\ell})$ instead of $C_{k,\ell}^{\text{qlb}}(\Phi)$ since the dependency on the PPP points reduces to the single random variable $\tilde{\rho}_{k,\ell}$, and where we use the well-known general integral result (see [3])

$$\mathcal{I}_M(\mu) =: \mathbb{E}[\log_e(1 + \mu \mathcal{X}_{2M})] \quad (2.22a)$$

$$= \Pi_M(-1/\mu) E_i(1, 1/\mu) + \sum_{m=1}^{M-1} \frac{1}{m} \Pi_m(1/\mu) \Pi_{M-m}(-1/\mu), \quad (2.22b)$$

with $\Pi_n(x) =: e^{-x} \sum_{i=0}^{n-1} \frac{x^i}{i!}$ and with the exponential integral function defined as $E_i(n, x) =: \int_1^\infty t^{-n} e^{-xt} dt$. Due to the monotonicity of the log function, $C_{k,\ell}^{\text{qlb}}(\tilde{\rho}_{k,\ell})$ is strictly monotonically increasing in $\tilde{\rho}_{k,\ell}$. Then, using $C_{k,L}^{\text{qlb}}(\tilde{\rho}_{k,\ell})$ instead of $C_k^{(L)}(\Phi)$ in the outage probability expression (2.3), we arrive at the desired quasi-upper bound to the outage probability in the form

$$P_k^{\text{out}}(R) \lesssim \mathbb{P}\left(C_{k,L}^{\text{qlb}}(\tilde{\rho}_{k,L}) \leq R\right) \quad (2.23a)$$

$$= \mathbb{P}\left(\tilde{\rho}_{k,L} \leq \left(C_{k,L}^{\text{qlb}}\right)^{-1}(R)\right) \quad (2.23b)$$

$$= F_{\tilde{\rho}_{k,L}} \left(\left(C_{k,L}^{\text{qlb}} \right)^{-1} (R) \right), \quad (2.23c)$$

where the inverse function $\left(C_{k,L}^{\text{qlb}} \right)^{-1} (\cdot)$ is easily obtained numerically from (2.21).

Average Delivery Rate Derivation

In order to appreciate the tradeoff between the macro-diversity order L and the PHY coding rate R , and to quickly see which value of L minimizes the delivery latency, we can consider the average rate of the typical user when averaging is also with respect to the random locations of the helpers (i.e., with respect to Φ). We indicate by “overline” quantities averaged also with respect to the geometry. Then, we have

$$\overline{C}_{k,\ell} = \mathbb{E} \left[\log \left(1 + \frac{r_{k,\ell}^{-\eta} \mathcal{X}_{2(n_r-L+1)}}{\sum_{j=L+1}^{\infty} r_{k,j}^{-\eta}} \right) \right] \quad (2.24a)$$

$$= \mathbb{E} \left[\mathbb{E} \left[\log \left(1 + \frac{r_{k,\ell}^{-\eta} \mathcal{X}_{2(n_r-L+1)}}{\sum_{j=L+1}^{\infty} r_{k,j}^{-\eta}} \right) \middle| r_{k,L}, r_{k,\ell} \right] \right] \quad (2.24b)$$

$$\geq \mathbb{E} \left[\mathbb{E} \left[\log (1 + \tilde{\rho}_{k,\ell} \mathcal{X}_{2(n_r-L+1)}) \middle| r_{k,L}, r_{k,\ell} \right] \right] \quad (2.24c)$$

$$= \mathbb{E} \left[\log_2 (1 + \tilde{\rho}_{k,\ell} \mathcal{X}_{2(n_r-L+1)}) \right]. \quad (2.24d)$$

Remark 1. Comparing (2.24d) with (2.13) and using the law of iterated expectation, for which $\mathbb{E} [\log (1 + \tilde{\rho}_{k,\ell} \mathcal{X}_{2(n_r-L+1)})] = \mathbb{E} [\mathbb{E} [\log (1 + \tilde{\rho}_{k,\ell} \mathcal{X}_{2(n_r-L+1)}) \middle| \Phi]]$, we have that the expectation of our quasi-lower bound $C_{k,\ell}^{\text{qlb}}(\Phi)$ on the ergodic mutual information for a given geometry Φ yields a true lower bound $\overline{C}_{k,\ell}^{\text{lb}}$ on the average (w.r.t. the random geometry) ergodic mutual information. $\diamond$

At this point, it is convenient to define

$$\widetilde{\text{SIR}}_{k,\ell} = \tilde{\rho}_{k,\ell} \mathcal{X}_{2(n_r-L+1)}, \quad (2.25)$$

as the “SIR” quantity appearing in (2.24d) and evaluate the expectation by following the approach of [42]. We can write

$$\overline{C}_{k,\ell}^{\text{lb}} = \int_0^{\infty} \log_2(1 + \gamma) dF_{\widetilde{\text{SIR}}_{k,\ell}}(\gamma) \quad (2.26a)$$

$$= \int_0^{\infty} \left(1 - F_{\widetilde{\text{SIR}}_{k,\ell}}(2^\gamma - 1) \right) d\gamma. \quad (2.26b)$$

Notice that, for fixed $\tilde{\rho}_{k,\ell}$, $\widetilde{\text{SIR}}_{k,\ell}$ is chi-squared distributed (up to a scaling factor). Hence, its conditional CDF is given by

$$F_{\widetilde{\text{SIR}}_{k,\ell}|\tilde{\rho}_{k,\ell}}(\gamma) = 1 - \frac{\Gamma(n_r - L + 1, \gamma/\tilde{\rho}_{k,\ell})}{\Gamma(n_r - L + 1)}, \quad (2.27)$$

where $\Gamma(a, x) =: \int_x^\infty t^{a-1} e^{-t} dt$ is the upper incomplete gamma function. The unconditional CDF of $\widetilde{\text{SIR}}_{k,\ell}$ is derived by expressing $\tilde{\rho}_{k,\ell}$ in terms of $r_{k,\ell}$ and $r_{k,L}$ (cf. (2.14)) and using their joint PDF to average these variables out, by treating the two cases $\ell < L$ and $\ell = L$ separately (cf. Appendix A.2). The following result (proved in Appendix A.3) provides the sought lower bound of the average ergodic rate corresponding to the ℓ -th data stream:

Proposition 4. *A lower bound of the average ergodic rate is given by*

Case 1: For $\ell < L$

$$\begin{aligned} \bar{C}_{k,\ell}^{\text{lb}} = & \sum_{m=0}^{n_r-L} \sum_{n=0}^{L-\ell-1} \frac{2(-1)^n}{m!(L-\ell-1)!(\ell-1)!\eta} \binom{L-\ell-1}{n} \\ & \cdot G_{3,3}^{2,3} \left(\begin{matrix} -(m+1), -(m+L), -m-\eta' \\ -(m+1), -1, -(m+1+\eta') \end{matrix} \middle| \frac{2}{\eta-2} \right) \cdot \left(\frac{2}{\eta-2} \right)^{m+1} \log_2(e), \end{aligned} \quad (2.28)$$

where $G_{m,n}^{p,q} \left(\begin{matrix} a_1, \dots, a_n, a_{n+1}, \dots, a_p \\ b_1, \dots, b_m, b_{m+1}, \dots, b_q \end{matrix} \middle| z \right)$ is Meijer-G function.

Case 2: For $\ell = L$

$$\bar{C}_{k,L}^{\text{lb}} = \sum_{m=0}^{n_r-L} \frac{\log_2(e)}{m+L} {}_2F_1 \left(1, L; m+L+1; 1 - \frac{2}{\eta-2} \right). \quad (2.29)$$

□

The tightness of these lower bounds is illustrated in Fig. 2.4, comparing $\bar{C}_{k,L}^{\text{lb}}$ and $\bar{C}_{k,L}$ for the settings: $\lambda = 8 \text{ Relays/km}^2$ and $\eta = 3.75$ with $n_r = 8, L = 4$ and with $n_r = 16, L = 8$. Since eventually the delivery rate is defined by the worst-case data stream, we define the lower bound for minimum average ergodic rate as follows

$$\bar{C}_{k,\text{PZF}}^{\text{lb}} = \bar{C}_{k,L}^{\text{lb}}. \quad (2.30)$$

Remark 2. Operational significance of the average ergodic rate. *Averaging with respect to the random geometry of the helpers placement for a given typical user has no*

Figure 2.4.: Average ergodic rate versus stream index.

operational significance in terms of achievable rate. In fact this would require a sufficiently fast mixing, i.e., an ergodic behavior, of the geometry during the transmission of a single PHY codeword, which is generally not the case. We remark here that in classical stochastic geometry analysis it is customary to mix the time dynamics of the small-scale fading and of the random geometry. While the small-scale fading mixes on time intervals of the order of the inverse of the Doppler bandwidth, i.e., typically between 1 and 10 ms, the geometry (distances between a user and the helpers) evolves according to much slower dynamics, and can be considered constant on intervals between 1 and 10 s for users moving at vehicular speeds, and even much larger for nomadic users. Hence, the operational meaning of the average ergodic rate as an achievable rate for a specific typical user is questionable. This is precisely the reason why we focused on the outage probability where outages are defined with respect to the random geometry. Nevertheless, the average ergodic rate captures the tradeoff between L and R . On one hand, we would like to make L large in order to gain a speed-up factor L in the delivery latency (see (2.1)). On the other hand, a larger L yields a smaller value of $\bar{C}_{k,\text{PZF}}^{\text{lb}}$. Hence, a useful rule of thumb in system optimization is to choose the value of L that maximizes the product $L \times \bar{C}_{k,\text{PZF}}^{\text{lb}}$. $\diamond$

2.3.2. PZF with Successive Interference Cancellation

In this section we improve the PZF strategy by introducing successive interference cancellation (SIC). In PZF-SIC users decode their strongest helper signals in sequence. We let Π denote the set of permutations of $[L]$, and let $\pi = \{\pi(1), \pi(2), \dots, \pi(L)\} \in \Pi$ denote the decoding order of a generic user k . Then, user k decodes $\underline{\mathbf{x}}_{\pi(1)}$ first, by suppressing interference from the remaining $L - 1$ helpers via ZF beamforming. Then, it subtracts the decoded version of $\underline{\mathbf{x}}_{\pi(1)}$ from the received signal, and proceeds to the decoding of the next signal $\underline{\mathbf{x}}_{\pi(2)}$ by suppressing interference from the remaining $L - 2$ helpers via ZF beamforming. Notice that since we treat ergodic spectral efficiencies, each codeword must

span a large number of fading states (i.e., channel matrices). Therefore, the decoding order cannot depend on the realization of the channel matrices, but only on their statistics, i.e., ultimately on the distance dependent path strengths. Assuming successful decoding and interference cancellation for the first $\ell - 1$ SIC stages, the signal at the input of the ℓ -th decoding stage is given by

$$\mathbf{Y}_{k,\ell}^{\text{SIC}} = \sum_{j=\ell}^L \mathbf{h}_{k,\pi(j)} \sqrt{\beta r_{k,\pi(j)}^{-\eta}} \mathbf{x}_{\pi(j)} + \sum_{j=L+1}^{\infty} \mathbf{h}_{k,j} \sqrt{\beta r_{k,j}^{-\eta}} \mathbf{x}_j, \quad (2.31)$$

where $\ell \leq L$. Denoting by $\mathbf{H}_{k,\pi(\ell:L)}$ the channel matrix restricted to helpers with indices $\pi(\ell), \pi(\ell+1), \dots, \pi(L)$ and letting $\mathbf{H}_{k,\pi(\ell:L)}^\dagger$ be the corresponding pseudo-inverse, the ZF beamforming vector for the ℓ -th SIC stage is given by the first column of pseudo-inverse, denoted by $[\mathbf{H}_{k,\pi(\ell:L)}^\dagger]_{:,1}$, normalized to have unit norm. Letting $\mathbf{v}_{k,\ell}$ denote such vector, the decoder input after ZF beamforming is given by

$$\tilde{\mathbf{y}}_{k,\ell}^{\text{SIC}} = \mathbf{v}_{k,\ell}^H \mathbf{h}_{k,\pi(\ell)} \sqrt{\beta r_{k,\pi(\ell)}^{-\eta}} \mathbf{x}_{\pi(\ell)} + \sum_{j=L+1}^{\infty} \mathbf{v}_{k,\ell}^H \mathbf{h}_{k,j} \sqrt{\beta r_{k,j}^{-\eta}} \mathbf{x}_j.$$

Consequently, the ℓ -th decoder SIR is given by

$$\text{SIR}_{k,\ell}^{\text{SIC}} = \frac{r_{k,\pi(\ell)}^{-\eta} \left| [\mathbf{H}_{k,\pi(\ell:L)}^\dagger]_{:,1} \right|^{-2}}{\sum_{j=L+1}^{\infty} r_{k,j}^{-\eta} |\tilde{h}_{k,j}|^2}. \quad (2.32)$$

Since $\mathbf{v}_{k,\ell}$ is a unit vector that is independent of $\{\mathbf{h}_{k,j} : j > L\}$, as before it follows that $\tilde{h}_{k,j} \sim \mathcal{CN}(0, 1)$, $\forall j > L$. Also, similarly as before, we have that the useful signal coefficient $\left| [\mathbf{H}_{k,\pi(\ell:L)}^\dagger]_{:,1} \right|^{-2} = \mathcal{X}_{2(n_r-L+\ell)}$ is Chi-square distributed with $2(n_r-L+\ell)$ degrees of freedom and mean $n_r - L + \ell$. It follows that the ergodic rate achievable at the ℓ -th decoding stage is given by

$$C_{k,\ell}(\rho_{\pi(\ell)}) = \mathbb{E} \left[\log \left(1 + \frac{r_{k,\pi(\ell)}^{-\eta} \mathcal{X}_{2(n_r-L+\ell)}}{\sum_{j=L+1}^{\infty} r_{k,j}^{-\eta} |\tilde{h}_{k,j}|^2} \right) \middle| \Phi \right], \quad (2.33)$$

Operating as before, we obtain the corresponding quasi-lower bound on the ergodic rate at the ℓ -th decoding stage as

$$C_{k,\ell}^{\text{qlb}}(\tilde{\rho}_{k,\pi(\ell)}) = \mathbb{E} \left[\log \left(1 + \tilde{\rho}_{k,\pi(\ell)} \mathcal{X}_{2(n_r-L+\ell)} \right) \middle| \Phi \right], \quad (2.34)$$

where $\tilde{\rho}_{k,\ell}$ is defined in (2.14). Next, we consider the outage probability of the PZF-SIC decoder. Notice that (2.33) is the ergodic rate at the ℓ -th stage assuming a genie-aided SIC decoder that has already removed the codewords $\mathbf{x}_{\pi(1)}, \dots, \mathbf{x}_{\pi(\ell-1)}$. As a matter of

fact, the performance of the actual PZF-SIC decoder coincides with that of the genie-aided SIC as stated by the following result (see also [52]):

Proposition 5. *The overall probability of error of the actual PZF-SIC decoder coincides with that of the genie-aided PZF-SIC decoder.* $\square$

Proof. Define the outage set $\mathcal{A}$ as the set of all geometry configurations Φ for which the PZF-SIC fails w.h.p.. For any $\Phi \in \mathcal{A}$ there exists $1 \leq \ell^* \leq L$ such that

$$\begin{aligned} C_{k,\ell}(\rho_{k,\pi(\ell)}) &> R, \quad \text{for } \ell = 1, \dots, \ell^* - 1, \quad \text{and} \\ C_{k,\ell^*}(\rho_{k,\pi(\ell^*)}) &\leq R. \end{aligned} \quad (2.35)$$

In other words, ℓ^* is the index of the first stage (dependent on Φ) for which a decoding error occurs w.h.p.. Now, consider the set $\mathcal{B}$ of geometry configurations Φ such that $\min_{\ell \in [L]} C_{k,\ell}(\rho_{k,\pi(\ell)}) \leq R$. Since for any $\Phi \in \mathcal{A}$ it is always true that $\min_{\ell \in [L]} C_{k,\ell}(\rho_{k,\pi(\ell)}) \leq C_{k,\ell^*}(\rho_{k,\pi(\ell^*)}) \leq R$, then $\mathcal{A} \subseteq \mathcal{B}$. On the other hand, let $\hat{\ell}$ denote the index achieving the minimum of $\{C_{k,\ell}(\rho_{k,\pi(\ell)}) : \ell \in [L]\}$. For any $\Phi \in \mathcal{B}$ we have $C_{k,\hat{\ell}}(\rho_{k,\pi(\hat{\ell})}) \leq R$. Therefore, there must exist some $\ell^* \leq \hat{\ell}$ for which the condition (2.35) is verified (in fact, it has to be some $\ell^* \in [1 : \hat{\ell}]$ including $\hat{\ell}$ itself). Hence, we have $\mathcal{B} \subseteq \mathcal{A}$. Thus, we conclude that $\mathcal{A} = \mathcal{B}$, and the outage probability of the PZF-SIC decoder is given by $P_{\text{out},k}(R) = \mathbb{P}(\min_{\ell \in [L]} C_{k,\ell}(\rho_{k,\pi(\ell)}) \leq R)$. $\square$

Using the same argument made for PZF in the previous section, we replace $C_{k,\ell}(\rho_{k,\pi(\ell)})$ with its quasi-lower bound approximation (2.34) and obtain a quasi-upper bound to the outage probability of the PZF-SIC as

$$P_{\text{out},k}(R) \lesssim \mathbb{P}\left(\min_{\ell} C_{k,\ell}^{\text{qlb}}(\tilde{\rho}_{k,\pi(\ell)}) \leq R\right). \quad (2.36)$$

A problem that remains to be addressed is how to choose the optimal decoding order $\pi \in \Pi$ that minimizes the outage probability. It is immediate to verify from (2.34) that the functions $C_{k,\ell}^{\text{qlb}}(\rho)$ for $\rho \in \mathbb{R}_+$ are monotonically increasing and that, for any $\rho \in \mathbb{R}_+$, they satisfy the dominance condition

$$C_{k,1}^{\text{qlb}}(\rho) \leq C_{k,2}^{\text{qlb}}(\rho) \leq \dots \leq C_{k,L}^{\text{qlb}}(\rho), \quad (2.37)$$

due to the order of the chi-squared variable in (2.34) that increases with ℓ . Then, we have the following result, proved in Appendix A.4.

Theorem 1. *Let $f_1(x), \dots, f_L(x)$ be a collection of monotonically non-decreasing functions on $\mathbb{R}$ such that, for all $x \in \mathbb{R}$, $f_1(x) \leq f_2(x) \leq \dots \leq f_L(x)$. Then, for any L -tuple of*

Figure 2.5.: Outage probability versus delivery rate with $n_r = 8$.

values $x_1 \geq \dots \geq x_L$,

$$\max_{\pi \in \Pi} \min_{\ell \in [L]} f_\ell(x_{\pi(\ell)}) = \min_{\ell \in [L]} f_\ell(x_\ell), \quad (2.38)$$

i.e., the minimum of $f_\ell(x_{\pi(\ell)})$ is maximized by the identity $\pi(\ell) = \ell$ (although this may not be the unique solution). $\square$

Notice that for any given realization of the geometry Φ , the sequence $\tilde{\rho}_{k,1}, \tilde{\rho}_{k,2}, \dots, \tilde{\rho}_{k,L}$ is monotonically decreasing. Therefore, as a corollary of Theorem 1, the optimal PZF-SIC decoding order consists of decoding the helper signals in path strength order (strongest first, L -th strongest last, and treat all the others as noise).

In Fig. 2.5, the outage probability of the worst stream for cases with PZF and PZF-SIC are plotted. In PZF receiver, the last stream (L -th one) has the minimum ergodic rate and defines the outage probability of PZF (as already written in (2.23a)). However, for the PZF-SIC receiver the last stream is not necessarily the minimum for any realization of Φ . The curves (1) and (2) in Fig. 2.5 show the CDFs $\mathbb{P}\left(\min_{\ell \in [L]} C_{k,\ell}^{\text{qlb}}(\rho_{k,\ell}) \leq R\right)$ and $\mathbb{P}\left(C_{k,L}^{\text{qlb}}(\rho_{k,L}) \leq R\right)$ for PZF-SIC. We notice that these two CDFs are almost identical. Therefore, for the sake of analytical tractability, we shall further relax our outage probability approximation for the PZF-SIC receiver to

$$P_{\text{out},k}(R) \lesssim \mathbb{P}\left(C_{k,L}^{\text{qlb}}(\tilde{\rho}_{k,L}) \leq R\right), \quad (2.39)$$

which can be obtained analytically by adapting the formulas of Section 2.3.1. We conclude this section by providing a tight approximation of the average (over the geometry) ergodic rate of the PZF-SIC decoder. From what said before, it follows that

$$\overline{C}_{k,\text{PZF-SIC}}^{\text{qlb}} = \mathbb{E}\left[\min_{\ell \in [L]} C_{k,\ell}^{\text{qlb}}(\tilde{\rho}_{k,\ell})\right] \quad (2.40a)$$

$$\approx \mathbb{E}\left[C_{k,L}^{\text{qlb}}(\tilde{\rho}_{k,L})\right], \quad (2.40b)$$

Figure 2.6.: $L \times \bar{C}_{k,\text{PZF}}^{\text{lb}}$ and $L \times \bar{C}_{k,\text{PZF-SIC}}^{\text{lb}}$ versus $L \leq n_r$ for a typical user with $n_r = 8, 16$.

where the last line follows again by replacing the minimum with the L term. Using similar steps as done before for the PZF case with $\ell = L$, we obtain

$$\bar{C}_{k,\text{PZF-SIC}}^{\text{lb}} = \sum_{m=0}^{n_r} \frac{\log_2(e)}{m+L} {}_2F_1\left(1, L; m+L+1; 1 - \frac{2}{\eta-2}\right). \quad (2.41)$$

2.4. Numerical Results

In this section we provide some numerical results illustrating the behavior and the performance of the proposed content delivery wireless caching network. In order to generate the simulation results, the locations of helpers are distributed according to a homogeneous PPP restricted to a disk radius $R_{\text{area}} = 3$ km with density $\lambda = 8$ Relays/km². The number of helpers is a Poisson random variable with mean $\pi R_{\text{area}}^2 \lambda$ and the helper positions are generated independently with uniform probability over the disk. We considered realistic values of the pathloss exponent $\eta = 3.75$ and the number of antennas $n_r = 8, 16$ at the user receivers.

Fig. 2.6 compares, as a function of n_r , $L \times \bar{C}_{k,\text{PZF}}^{\text{lb}}$ (cf. (2.30)) and $L \times \bar{C}_{k,\text{PZF-SIC}}^{\text{lb}}$ (cf. (2.41)) versus L for PZF and PZF-SIC receiver, which serves for the system designer a quick way to choose the best macro-diversity order L in order to minimize the delivery latency. With PZF, the trade-off between PHY rate and macro-diversity order L is evident. In fact, the product $L \times \bar{C}_{k,\text{PZF}}^{\text{lb}}$ increases for small L , reaches a maximum at $L = 3$ for $n_r = 8$ and at $L = 6$ for $n_r = 16$, and then decreases, because the PHY rate at which the typical user can decode the L -th strongest helper decreases faster than increase in L . In contrast, with PZF-SIC, the product $L \times \bar{C}_{k,\text{PZF-SIC}}^{\text{lb}}$ monotonically increases with $L \in \{1, \dots, n_r\}$ showing that, at least for these system parameters, the best macro-diversity order is $L = n_r$.

Figure 2.7.: Outage probability versus $L \times R$ with $n_r = 8$.

Figure 2.8.: Outage probability versus $L \times R$ with $n_r = 16$.

Figs. 2.7 and 2.8 illustrate the outage probability versus $L \times R$ with PZF and PZF-SIC receiver, $n_r = 8$ and $n_r = 16$, respectively. For better exposition and simplicity of illustration, we only bring the plots for some macro-diversity orders whose outage probability are the lowest. The missing macro diversity orders in these two figures have higher outage probability than the illustrated plots, so they do not play a role to find the best trade-off between the latency and the macro diversity order. The delivery latency varies with $L \times R$ in an inverse manner and therefore moving to the right of these curves yields shorter delivery latency at higher outage probability (i.e., less and less users will be able to retrieve their requests, but those who can, receive it faster). In Fig. 2.7, by using PZF alone the macro-diversity order $L = 3, 4$, achieves better overall product $L \times R$ and therefore lower delivery latency. In PZF-SIC, by increasing L the curves move to right side, indicating that for given target outage probability the delivery latency decreases by increasing the macro-diversity order L , confirming the behavior already observed for the average ergodic rate in Fig. 2.6. Similarly for $n_r = 16$, with PZF receiver macro-diversity $L = 6, 7$ yield uniformly the best trade-off between latency and the outage probability while for PZF-SIC the best tradeoff is obtained by increasing L .

2.5. Summary and Conclusion

We considered a multipoint multicast system for the delivery of a common message to a large number of spatially distributed users with transmission from multiple spatially distributed infrastructure nodes, referred to here as helpers, without channel state information at the transmitter side. This scheme finds its main motivation in the application of the MAN coded caching approach to a spatially distributed extended network, according to the separation principle between caching and PHY. The resulting multipoint multicast system is somehow reminiscent of the current eMBMS for media broadcasting. The key ingredients of our scheme are coded caching as proposed for the single bottleneck network, able to turn the individual demands into a single coded multicast stream in an information-theoretic optimal way, and MDS-coded multipoint multicast. The MDS code allows each user to retrieve the whole multicast message by decoding just L out of all possible helper transmissions. In this way, each user can select its “best” L helpers in a completely decentralized user-centric way. In our case, since the pathloss depends on distance, the best L helpers are the L closets ones.

Overall, the proposed system results in full spatial scalability, since the per-user throughput (resp., per-request delivery latency) does not vanish (resp., does not diverges to infinity) as the system coverage area grows without bound with constant user density, as long as also the density of the helpers is also constant. We derived analytical expressions for the

outage probability with respect to the random network geometry and the average ergodic rate, where the averaging is also with respect to the network geometry. Our analysis shows that a rule of thumb to determine the optimal macro-diversity order L in the case of linear Partial Zero-Forcing (PZF) strategy at the users' receiver is to set L equal to half of the number of antennas n_r at the user receivers. In contrast, when PZF is augmented by Successive Interference Cancellation (SIC) in the order of the strongest helper (first) to the L -th strongest (last), letting $L = n_r$ provides the best performance.

3. Lossy Cache Aided Broadcast Channel

3.1. Background and Motivation

Recent years saw the emergence of wireless (cellular) standards designed for multicast streaming services (e.g. live TV), such as the evolved Multimedia Broadcast Multicast Service (eMBMS). It is possible to extend these paradigms by applying the coded caching scheme to design an on-demand video content delivery service in a lossy transmission environment. In such an environment, users experience different wireless channel qualities, which in turn should translate into different video streaming qualities. *Scalable Video Coding* (SVC) [55] refers to a set of techniques which enable a smooth tradeoff between video quality and source coding rate by producing layers of source-encoded bits. Layers are decoded in sequence at each user receiver, such that the number of successive decoded layer(s) determines the reconstructed source quality. The SVC scheme can be seen as a practical embodiment of the information-theoretic concept known as successive refinement source coding [12]. In this chapter, we focus on the special case of two layers. The encoder provides a fundamental layer at rate R_S^1 and a refinement layer at rate R_S^2 . A source is said to be *successively refinable* if the points (D_1, R_S^1) and $(D_2, R_S^1 + R_S^2)$ are points on the boundary of the distortion-rate region where D_1 and D_2 denote the distortions of layer 1 and 2, respectively. It is well-known that Gaussian sources with Mean Square-Error (MSE) distortion are successively refinable. It is also well-known that successive refinability with respect to the MSE distortion holds approximately for many other source distributions. In order to gain theoretical insights into the problem, we consider the Gaussian source case. For an i.i.d. source $\sim \mathcal{N}(0, \sigma^2)$, we have $D_1 = \sigma^2 2^{-2R_S^1}$ and $D_2 = \sigma^2 2^{-2(R_S^1 + R_S^2)}$.

Successive refinement has been applied to different coded caching scenarios. The authors in [57] presented a framework for layered caching in which heterogeneous cache sizes are considered for the end users. In [9, 69] a coded caching scheme with fixed heterogeneous distortion requirements is investigated. In [21], a cache-aided network for video delivery is considered. The delivery scheme was designed to minimize the average per-user distortion. During the placement phase, a user partially caches the layers according to the popularity distribution of the files. In [40] the authors considered equal distortion requirements for all users. They provided an inner and outer bound for a multi-layer coded caching scheme by

treating the cache memory data as side information. Finally, the authors in [22] provided an algorithm to jointly encode subfiles of different layers to achieve a lower rate than [69]. The works [9, 22, 69] considered partitioning the cache memory among the layers and proposed algorithms for cache assignment among layers. In [4], the authors compared the performance of time-division multiple access, superposition coding and dirty paper coding over broadcast channel to delivery scalable video files.

We proposed a multipoint multicast system for on-demand wireless video content delivery based on coded caching and lossy successive-refinement source coding. The proposed system is an extension of the previous chapter, where the coded caching message is MDS encoded and the MDS-encoded symbols are transmitted simultaneously from multiple wireless helpers. Each user can choose to receive data from up to L helpers. The goal is to deliver the video files at higher quality/rates to users with better channels. The source files are encoded into two layers, a fundamental layer and a refinement layer. Depending on the channel quality, each user may be able to decode only the fundamental layer, or both layers. In particular, using MDS codes of different rates for each layer, the successful decoding of a layer depends on the number of helpers that each user is able to decode. We use stochastic geometry to analyze the described system and consider both small and large scale fading. Our aim consists of minimizing the content delivery time subject to a target average per-user distortion requirement, where the optimization is with respect to the cache memory allocation between two layers. The proposed system achieves a distortion-delivery time tradeoff that is independent of the coverage area, in the limit of large area and given helper and users density. In this sense, we say that the system is spatially scalable. The helpers use two different channel access methods to transmit the coded multicast messages for different layers in the same frequency and time resource. Time Division Multiple Access (TDMA) and Superposition Coding (SC) were used.

3.2. System Model and Definition

We consider a wireless network with N_E helpers with a single antenna and K users equipped with an antenna array of size n_r and M units cache memory. All helpers are connected to the server through an error-free backhaul. The server has access to a content library with N files $\mathcal{F} = \{W_1, W_2, \dots, W_N\}$, each of which consists of F bits. Helpers are spatially distributed on the plane according to a two-dimensional homogeneous Poisson Point Process (PPP) of density λ . Each file $W_j, j \in [N]$ is source-encoded into $I = 2$ successive refinement layers at rates $R_S^i, 1 \leq i \leq I$ bits per source sample, such that $|W_n^{(i)}| = R_S^i F$ bits, where $W_j^{(i)}$ denotes the i -th layer of the j -th file. The users assign $M_i, i \in [I]$ units out of the total M memory units to cache segments (or “subfiles”) of layer i . Given a cache

memory partition, we apply a separate MAN coded caching scheme for each refinement layer. We let $t_i = M_i K / N, i \in [I]$, and assume that t_i is an integer for each i . The MAN scheme consists of two phases: a pre-fetching and delivery phase. In the pre-fetching phase, each layer of all files ($W_j^{(i)}$) is partitioned into subfiles $\{W_{j,T}^{(i)} : T \subseteq [K], |T| = t\}$ and user $k \in [K]$ caches a subset T of subfiles of layer i if and only if $k \in T$. In the delivery phase, for a given user demand vector $\mathbf{d} \in [N]^K$, for each layer i the server computes the codewords X_i by concatenating the blocks $X_S^{(i)}$ for all subsets $S \subseteq [K], |S| = t + 1$, where each such block is given by

$$X_S^{(i)} = \bigoplus_{k \in S} W_{d_k, S \setminus \{k\}}^{(i)}, \quad (3.1)$$

The overall transmission length for layer i is given by

$$\mathcal{L}(X_S^{(i)}) = \frac{FR_S^i}{\binom{K}{t_i}} \binom{K}{t_i + 1} = \frac{FR_S^i K(1 - \mu_i)}{1 + K\mu_i}, \quad (3.2)$$

where $\mu_i = M_i / N$ is the fractional cache memory assigned to layer i . In the proposed system, the codeword X^i is divided into L_i equally size blocks, for some integer $L_1 < L_2 \leq n_r$, to which $N_E - L_i$ parity blocks are appended by using MDS coding. The overall transmission length of each MDS-coded block for layer i is $\frac{\mathcal{L}(X_S^{(i)})}{L_i}$ bits. The resulting MDS-coded blocks of layers 1 and 2 are sent separately to the N_E helpers, such that each helper just broadcasts these two multicast messages. The MDS-coded blocks of layer 1 and 2 are transmitted in two ways including transmitting in sequence using time-division or superposition coding, on the wireless channel. The transmissions of all helpers are simultaneous, on the same frequency band, as in current eMBMS systems [33]. Each user k is able to reconstruct the entire codeword X_i if it can decode at least L_i messages from L_i distinct helpers. Depending on its location with respect to the helpers, a user may decode $\ell < L_1$ or $L_1 \leq \ell < L_2$ or $L_2 \leq \ell$ helpers. This corresponds to retrieving no layers, only the fundamental layer (layer 1), or both the fundamental and the successive refinement layers (layer 1 and layer 2). Each of these decoding outcomes yield a distortion level.

3.3. System Analysis

3.3.1. Time-Division Multiple Access (TDMA)

The first transmission scheme that we will explore is TDMA. In this scenario, the message for each layer is transmitted in a sequential manner in different time slots. A typical user indexed by k is considered at the origin location of a plane. The helpers are sorted with respect to their distance from user k . We assume a block fading channel with fading

3. Lossy Cache Aided Broadcast Channel

coherence block spanning n channel uses (symbols). The space-time signal $\mathbf{Y}_k \in \mathbb{C}^{n_r \times n}$ received by user k corresponding to a fading block is given by

$$\mathbf{Y}_k^i = \sum_{j=1}^{N_E} \sqrt{\beta r_{k,j}^{-\eta}} \mathbf{h}_{k,j} \mathbf{x}_j^i + \mathbf{N}_k, \quad (3.3)$$

where $\mathbf{h}_{k,j} \in \mathbb{C}^{n_r \times 1}$ is the channel vector containing the small-scale fading coefficients from helper j to the antenna array of user k , $\mathbf{x}_j \in \mathbb{C}^{1 \times n}$ is the block of the n symbols sent by helper j , $r_{k,j}$ is the distance between helper j and user k , with η and β being the pathloss exponent and intercept, respectively. The helpers transmit at a constant average power $P = \frac{1}{n} \mathbb{E}[\mathbf{x}_j \mathbf{x}_j^H]$. The noise samples in the matrix $\mathbf{N}_k$ are independent and identically distributed (i.i.d.) $\sim \mathcal{CN}(0, N_0)$ and $\mathbf{h}_{k,j}$ have components i.i.d. $\sim \mathcal{CN}(0, 1)$. Our system utilizes the *Partial Zero-Forcing* (PZF) receiver strategy, which consists of applying linear zero-forcing only with respect to the signals of the L_2 nearest helpers. We denote the channel matrix of the coefficients between the helpers and the user k 's antenna array by $\mathbf{H}_k = [\mathbf{h}_{k,1}, \dots, \mathbf{h}_{k,N_E}] \in \mathbb{C}^{n_r \times N_E}$, and denote by $\mathbf{H}_{k,\mathcal{B}}$ the submatrix formed by the columns with indices $j \in \mathcal{B} \subseteq [1 : N_E]$. Then, the PZF receiver matrix is the column-normalized version of the pseudo-inverse

$$\mathbf{H}_{k,1:L_2}^\dagger = \mathbf{H}_{k,1:L_2} (\mathbf{H}_{k,1:L_2}^H \mathbf{H}_{k,1:L_2})^{-1}, \quad (3.4)$$

of the channel submatrix corresponding to the closest L_2 helpers to user k . Our scenario takes place in an infinitely extended network with an asymptotically large number of helpers and a high-SNR interference limited performance, i.e. $N_E \rightarrow \infty$ and $N_0 \rightarrow 0$. The Signal-to-Interference Ratio (SIR) at the ℓ -th stream for user k is given by

$$\text{SIR}_{k,\ell} = \frac{r_{k,\ell}^{-\eta} \|\mathbf{h}_{k,\ell}^\dagger\|^{-2}}{\sum_{j=L_2+1}^{\infty} r_{k,j}^{-\eta} |\tilde{h}_{k,j}|^2}, \quad (3.5)$$

where $\mathbf{h}_{k,\ell}^\dagger$ denotes the ℓ -th column of $\mathbf{H}_{k,1:L_2}^\dagger$, $\tilde{h}_{k,j} \sim \mathcal{CN}(0, 1)$ and we have shown that $\|\mathbf{h}_{k,\ell}^\dagger\|^{-2} \sim \mathcal{X}_{2(n_r - L_2 + 1)}$ before. By considering the above SIR, the ergodic achievable rate is defined as following

$$C_{k,\ell}(\Phi) = \mathbb{E}[\log(1 + \text{SIR}_{k,\ell}) | \Phi], \quad (3.6)$$

where Φ is the ensemble of the locations of helpers. Using the same approach consisting of applying Jensen's inequality and replacing the terms in the SIR denominator by their ensemble average, we obtain a quasi-lower bound on the ergodic achievable rate of user k

as

$$C_{k,\ell}^{\text{qlb}}(\tilde{\rho}) = \mathbb{E} [\log (1 + \tilde{\rho}_{k,\ell} \mathcal{X}_{2(n_r-L_2+1)}) | \Phi], \quad (3.7)$$

where we define the approximated conditional local-average SIR as

$$\tilde{\rho}_{k,\ell} = \frac{r_{k,L_2}^{\eta-2}}{r_{k,\ell}^{\eta}} \frac{\eta-2}{2\pi\lambda} \quad 1 \leq \ell \leq L_2. \quad (3.8)$$

Notice that in the rate expression (3.7), the expectation is taken with respect to the small-scale fading, but it is conditional on the placement of the NEs and user k (system geometry). This corresponds to separating the time scale of the small-scale fading from the time scale of the geometry variation, due to mobility. The expectation with respect to $\mathcal{X}_{2(n_r-L_2+1)}$ in (3.7) can be calculated in closed form as

$$\begin{aligned} C_{k,\ell}^{\text{qlb}}(\tilde{\rho}_{k,\ell}) &= \mathbb{E} [\log (1 + \tilde{\rho}_{k,\ell} \mathcal{X}_{n_r-L_2+1}) | \Phi] \\ &= \mathcal{I}_{(n_r-L_2+1)}(\tilde{\rho}_{k,\ell}) \log(e), \end{aligned} \quad (3.9)$$

where $\mathcal{I}_M(\mu)$ is given by

$$\mathcal{I}_M(\mu) = \Pi_M(-1/\mu) E_i(1, 1/\mu) + \sum_{m=1}^{M-1} \frac{1}{m} \Pi_m(1/\mu) \Pi_{M-m}(-1/\mu), \quad (3.10)$$

with $\Pi_n(x) = e^{-x} \sum_{i=0}^{n-1} \frac{x^i}{i!}$ and with the exponential integral function defined as $E_i(n, x) = \int_1^\infty t^{-n} e^{-xt} dt$. The ℓ -th helper transmits the modulated blocks for layer i with PHY rate R_C^i . Consider a fraction of time $\alpha \in [0, 1]$ is assigned to layer 1, while the remaining fraction $1 - \alpha$ is assigned to layer 2. When using the time-sharing strategy, the achievable region should satisfy the following results

$$C(R_C^1, R_C^2) = \bigcup_{\alpha, 1-\alpha} (\{R_C^1, R_C^2\} : 0 \leq R_C^1 \leq \alpha C_{k,L_1}^{\text{qlb}}, 0 \leq R_C^2 \leq (1-\alpha) C_{k,L_2}^{\text{qlb}}). \quad (3.11)$$

By considering the MSE distortion function for a Gaussian source with source rate coding (R_S^i) as $D_i = \sigma^2 2^{-2R_S^i}$, $1 \leq i \leq I$ and assuming $\sigma^2 = 1$, we can write the average distortion for user k as

$$\begin{aligned} D_k &= \mathbb{P}(C_{k,L_1}^{\text{qlb}}(\tilde{\rho}_{k,L_1}) \leq \frac{R_C^1}{\alpha}) + \mathbb{P}(\frac{R_C^1}{\alpha} < C_{k,L_1}^{\text{qlb}}(\tilde{\rho}_{k,L_1}), C_{k,L_2}^{\text{qlb}}(\tilde{\rho}_{k,L_2}) \leq \frac{R_C^2}{1-\alpha}) 2^{-2R_S^1} \\ &\quad + \mathbb{P}(\frac{R_C^1}{\alpha} < C_{k,L_1}^{\text{qlb}}(\tilde{\rho}_{k,L_1}), \frac{R_C^2}{1-\alpha} < C_{k,L_2}^{\text{qlb}}(\tilde{\rho}_{k,L_2})) 2^{-2(R_S^1+R_S^2)}. \end{aligned} \quad (3.12)$$

Figure 3.1.: Level sets of distortion versus channel coding rates

The total delivery latency with $\alpha = 0.5$ is given by summation of delivery time of two layers

$$T = T_1 + T_2. \quad (3.13)$$

The delivery latency for layer i is given by

$$T_i = \frac{\mathcal{L}(X^i)}{wR_C^i L_i} = \frac{FR_S^i}{w} \frac{1}{R_C^i L_i} \frac{K(1 - \mu_i)}{1 + K\mu_i}, \quad (3.14)$$

where w is the bandwidth of the wireless channel and R_S^i and R_C^i are the source coding and channel coding rate for layer i . The level set for the average distortion function as defined in (3.12) is plotted in Fig. 3.1. It should be noted that the average distortion can be divided into two distinct regions. In the first region, where $0 \leq D_k \leq 2^{-2R_S^1}$ the level sets are bounded such that the channel coding rate for both layers is below the boundaries. In the second region with $2^{-2R_S^1} < D_k \leq 1$, the rate R_C^2 goes to the boundaries with the second layer having a very high probability of being incorrectly decoded. Expressions (3.12) and (3.14) establish an achievable tradeoff between average distortion and delivery time. To reduce distortion, we should choose lower R_C^1 and R_C^2 and to decrease delivery latency we need to increase R_C^1 and R_C^2 . Our goal is to minimize delivery latency with distortion requirement, while solving the cache allocation problem. The constraint on total cache size at each user is given as

$$\sum_{i=1}^I M_i F R_S^i = \mu N F \sum_{i=1}^I R_S^i. \quad (3.15)$$

where μ denotes the fraction of total source-encoded library bits cached at each user. Eliminating F from both sides, dividing by N , and dividing by $\sum_{i=1}^I R_S^i$, we obtain the cache allocation constraint as

$$\sum_{i=1}^I \mu_i \hat{R}_S^i = \mu, \quad (3.16)$$

where we define $\hat{R}_S^i := \frac{R_S^i}{\sum_{i=1}^I R_S^i}$. We assume that the source coding rates are given (e.g., standard and high definition of a given video format). Hence, our objective consists of minimizing the delivery latency subject to a target average distortion constraint D_0 . This yields the following problem:

$$\begin{aligned} & \underset{R_C^1, R_C^2, \mu_1, \mu_2}{\text{minimize}} && T \\ & \text{subject to} && D_k \leq D_0 \\ & && \sum_{i=1}^I \mu_i \hat{R}_S^i = \mu. \end{aligned} \quad (3.17)$$

3.3.2. Superposition Coding

In this section, the superposition coding scheme is introduced. In this scheme the helpers broadcast the superimposed signals of the layers instead of just broadcasting the signals of different layers in a sequential manner. Consider each helper splits the total power P into $P_1 = \alpha P$ and $P_2 = (1 - \alpha)P$ with $0 < \alpha < 1$. The transmitted signal is the sum of the signals of layer one and two with the power split.

$$\mathbf{x}_j^{\text{sc}} = P_1 \mathbf{x}_j^1 + P_2 \mathbf{x}_j^2, \quad (3.18)$$

where $\mathbf{x}_j^i$ is the signal of layer i . The signal received by user k can be written as follows

$$\mathbf{Y}_k^{\text{sc}} = \sum_{j=1}^{N_E} \sqrt{\beta r_{k,j}^{-\eta}} \mathbf{h}_{k,j} \mathbf{x}_j^{\text{sc}} + \mathbf{N}_k, \quad (3.19)$$

At the receiver side, $\mathbf{h}_{k,\ell}^\dagger / \|\mathbf{h}_{k,\ell}^\dagger\|$, $1 \leq \ell \leq L_2$ denotes the ℓ -th normalized column of the PZF matrix as defined in (3.4). By applying the normalized receiver filtering vector corresponding to the ℓ -th stream, the filtered output after PZF is written as

$$\tilde{\mathbf{y}}_{k,\ell}^{\text{sc}} = g_{k,\ell} \sqrt{\beta r_{k,\ell}^{-\eta}} \mathbf{x}_\ell^{\text{sc}} + \sum_{j=L_2+1}^{N_E} g_{k,\ell,j} \sqrt{\beta r_{k,\ell}^{-\eta}} \mathbf{x}_j^{\text{sc}} + \tilde{\mathbf{z}}_k, \quad (3.20)$$

where $g_{k,\ell,j} = \frac{(\mathbf{h}_{k,\ell}^\dagger)^\text{H}}{\|\mathbf{h}_{k,\ell}^\dagger\|} \mathbf{h}_{k,j}$ and $g_{k,\ell} = \frac{(\mathbf{h}_{k,\ell}^\dagger)^\text{H}}{\|\mathbf{h}_{k,\ell}^\dagger\|} \mathbf{h}_{k,\ell}$. In Chapter 2, we have shown that $g_{k,\ell,j} \sim \mathcal{CN}(0,1), \forall j \geq L_2 + 1$ and $|g_{k,\ell}|^2 \sim \mathcal{X}_{2(n_r - L_2 + 1)}$. User k first decodes the data for layer 1 by treating the signal for layer 2 as noise, and then extracts it from the received data. In the next step, the user uses *Successive Interference Cancellation* (SIC) to decode the data for layer 2. By using this scheme the following ergodic rates for layer 1 and 2 can be achieved

$$C_{k,1,\ell}^{sc-qlb}(\Phi) = \mathbb{E} \left[\log \left(1 + \frac{\alpha |g_{k,\ell}|^2 r_{k,\ell}^{-\eta}}{(1-\alpha) |g_{k,\ell}|^2 r_{k,\ell}^{-\eta} + \sum_{j=L_2+1}^{\infty} r_{k,j}^{-\eta} |g_{k,\ell,j}|^2} \right) \middle| \Phi \right], \quad (3.21)$$

$$C_{k,2,\ell}^{sc-qlb}(\Phi) = \mathbb{E} \left[\log \left(1 + \frac{(1-\alpha) |g_{k,\ell}|^2 r_{k,\ell}^{-\eta}}{\sum_{j=L_2+1}^{\infty} r_{k,j}^{-\eta} |g_{k,\ell,j}|^2} \right) \middle| \Phi \right], \quad (3.22)$$

where $0 < \ell \leq L_2$. They can be simplified to

$$C_{k,1,\ell}^{sc-qlb}(\Phi) = \mathbb{E} \left[\log \left(1 + \frac{\alpha |g_{k,\ell}|^2 \rho_{k,\ell}}{(1-\alpha) |g_{k,\ell}|^2 \rho_{k,\ell} + 1} \right) \middle| \Phi \right], \quad (3.23)$$

$$C_{k,2,\ell}^{sc-qlb}(\Phi) = \mathbb{E} [\log (1 + (1-\alpha) |g_{k,\ell}|^2 \rho_{k,\ell}) | \Phi]. \quad (3.24)$$

In order to decode layer 1, the user needs to decode at least L_1 streams. The achievable ergodic rate for layer 1 is defined as $L_1\text{-max}\{C_{k,1,\ell}^{sc-qlb}(\Phi) : j \in [N_E]\}$. In order to decode layer 2, the user needs to decode at least L_2 streams correctly. The achievable ergodic rate for layer 2 is given by $L_2\text{-max}\{C_{k,2,\ell}^{sc-qlb}(\Phi) | C_{k,1,\ell}^{sc-qlb}(\Phi) : j \in [N_E]\}$. By replacing $\rho_{k,\ell}$ with its average $\tilde{\rho}_{k,\ell}$ we obtain the average ergodic rate as follows

$$\mathbb{E} \left[\log \left(1 + \frac{\alpha |g_{k,\ell}|^2 \tilde{\rho}_{k,\ell}}{(1-\alpha) |g_{k,\ell}|^2 \tilde{\rho}_{k,\ell} + 1} \right) \middle| \Phi \right] \quad (3.25)$$

$$= \mathbb{E} \left[\log \left(\frac{|g_{k,\ell}|^2 \tilde{\rho}_{k,\ell} + 1}{(1-\alpha) |g_{k,\ell}|^2 \tilde{\rho}_{k,\ell} + 1} \right) \middle| \Phi \right] \quad (3.26)$$

$$= \mathbb{E} [\log (|g_{k,\ell}|^2 \tilde{\rho}_{k,\ell} + 1) - \log (1-\alpha) |g_{k,\ell}|^2 \tilde{\rho}_{k,\ell} + 1 | \Phi] \quad (3.27)$$

$$= \mathbb{E} [\log (|g_{k,\ell}|^2 \tilde{\rho}_{k,\ell} + 1) | \Phi] - \mathbb{E} [\log ((1-\alpha) |g_{k,\ell}|^2 \tilde{\rho}_{k,\ell} + 1) | \Phi] \quad (3.28)$$

$$= \mathcal{I}_{(n_r - L_2 + 1)}(\tilde{\rho}_{k,\ell}) \log(e) - \mathcal{I}_{(n_r - L_2 + 1)}((1-\alpha) \tilde{\rho}_{k,\ell}) \log(e), \quad (3.29)$$

where the last step is obtained by using (3.9). The achievable region for superposition coding is given by

$$C(R_C^1, R_C^2) = \bigcup_{\alpha, 1-\alpha} (\{R_C^1, R_C^2\} : 0 \leq R_C^1 \leq C_{k,1,L_1}^{\text{sc-qlb}}(\tilde{\rho}_{k,L_1}), 0 \leq R_C^2 \leq C_{k,2,L_2}^{\text{sc-qlb}}(\tilde{\rho}_{k,L_2})). \quad (3.30)$$

We consider here $\alpha = 1/2$, as a result the time necessary to deliver all requested files depends on the maximum transmission time for each layer. Hence the delivery latency is given by

$$T = \max(T_1, T_2), \quad (3.31)$$

where $T_i = \frac{\mathcal{L}(X_i)}{wR_C^i L_i} = \frac{FR_S^i}{w} \frac{1}{R_C^i L_i} \frac{K(1-\mu_i)}{1+K\mu_i}$. The average distortion for user k is given by

$$\begin{aligned} D_k = & \mathbb{P}(C_{k,1,L_1}^{\text{sc-qlb}}(\tilde{\rho}_{k,L_1}) \leq R_C^1) + \mathbb{P}(R_C^1 < C_{k,1,L_1}^{\text{sc-qlb}}(\tilde{\rho}_{k,L_1}), C_{k,2,L_2}^{\text{sc-qlb}}(\tilde{\rho}_{k,L_2}) \leq R_C^2) 2^{-2R_S^1} \\ & + \mathbb{P}(R_C^1 < C_{k,1,L_1}^{\text{sc-qlb}}(\tilde{\rho}_{k,L_1}), R_C^2 < C_{k,2,L_2}^{\text{sc-qlb}}(\tilde{\rho}_{k,L_2})) 2^{-2(R_S^1 + R_S^2)}. \end{aligned} \quad (3.32)$$

3.3.3. Multidimensional Decoding Error Probability

Given a homogeneous PPP Φ of density of λ , let r_n denote the n -th shortest distance of points of Φ from the origin. Then, the Probability Density Function (PDF) of r_n is given by [38]

$$f_{r_n}(v) = \frac{2(\pi\lambda)^n}{(n-1)!} v^{2n-1} e^{-\pi\lambda v^2}, \quad v \geq 0 \quad (3.33)$$

and the joint PDF of r_ℓ and r_n with $1 \leq \ell < n$ is given by

$$f_{r_\ell, r_n}(u, v) = \frac{4(\pi\lambda)^n}{(n-\ell-1)!(\ell-1)!} (v^2 - u^2)^{n-\ell-1} v u^{2\ell-1} e^{-\pi\lambda v^2}, \quad u, v \geq 0. \quad (3.34)$$

The conditional PDF of r_ℓ on r_k with $1 \leq \ell < k$ and $v \geq u \geq 0$ is given by

$$f_{r_\ell|r_k}(u | v) = \sum_{n=0}^{k-\ell-1} \alpha_{n,\ell,k} (-1)^n v^{-2(n+\ell)} u^{2(n+\ell)-1} (v > u \geq 0) \quad , \quad (3.35)$$

where $(v > u \geq 0) = 1$ if $v > u$ otherwise it is 0 and also we define

$$\alpha_{n,\ell,k} = \frac{2(k-1)!}{(k-\ell-1)!(\ell-1)!} \binom{k-\ell-1}{n}.$$

3. Lossy Cache Aided Broadcast Channel

By substituting $\ell = L_2$ in (3.8) and considering a given R_C^2 , the threshold on L_2 -th helper's distance $\hat{r}_{k,L_2} > r_{k,L_2}$ such that $R_C^2 < C_{k,L_2}^{\text{qlb}}$, is given by

$$\hat{r}_{L_2} := \sqrt{\frac{\eta - 2}{2\pi\lambda \left(C_{k,L_2}^{\text{qlb}}\right)^{-1} (R_C^2)}}, \quad (3.36)$$

where $\left(C_{k,L_2}^{\text{qlb}}\right)^{-1} (R_C^2)$ is the inverse of the function in (3.9). By substituting $\ell = L_1$ and $r_{k,L_2} = v$ in (3.8) and considering a given R_C^1 , the threshold on L_1 -th helper's distance $\hat{r}_{k,L_1} > r_{k,L_1}$ such that $R_C^1 < C_{k,L_1}^{\text{qlb}}$, is given by

$$\hat{r}_{k,L_1} := \left(\frac{\eta - 2}{2\pi\lambda} \frac{v^{\eta-2}}{\left(C_{k,L_1}^{\text{qlb}}\right)^{-1} (R_C^1)} \right)^{1/\eta}. \quad (3.37)$$

The successful decoding probability of layer one conditioned on $r_{k,L_2} = v$ is given by

$$\mathbb{P}(R_C^1 < C_{k,L_1}^{\text{qlb}} \mid r_{k,L_2} = v) = \int_0^{\min(v, \hat{r}_{k,L_1})} f_{r_{k,L_1}|r_{k,L_2}}(u \mid v) du. \quad (3.38)$$

By defining $a := \sqrt{\frac{\eta-2}{2\pi\lambda \left(C_{k,L_1}^{\text{qlb}}\right)^{-1} (R_C^1)}}$ such that $v \leq \hat{r}_{k,L_1}$, $v \leq a$ are equivalent. By considering the two cases $v \leq a$ or $v > a$, we calculate the integral as follows

$$\textbf{Case 1 : } \mathbb{P}(R_C^1 < C_{k,L_1}^{\text{qlb}} \mid r_{k,L_2} = v, v \leq a) = \int_0^v f_{r_{k,L_1}|r_{k,L_2}}(u \mid v) du = 1, \quad (3.39)$$

$$\begin{aligned} \textbf{Case 2 : } \mathbb{P}(R_C^1 < C_{k,L_1}^{\text{qlb}} \mid r_{k,L_2} = v, v > a) &= \int_0^{\hat{r}_{k,L_1}} f_{r_{k,L_1}|r_{k,L_2}}(u \mid v) du \\ &= \sum_{n=0}^{L_2-L_1-1} \alpha'_{n,L_1,L_2} (\gamma_1)^{\eta'} v^{-\eta'}, \end{aligned} \quad (3.40)$$

where $\eta' = \frac{2(n+L_1)}{\eta}$, $\gamma_1 = \frac{\eta-2}{2\left(C_{k,L_1}^{\text{qlb}}\right)^{-1} (R_C^1)}$ and

$$\alpha'_{n,L_1,L_2} = \frac{(L_2-1)!(-1)^n \binom{L_2-L_1-1}{n}}{(L_2-L_1-1)!(L_1-1)!(n+L_1)}.$$

By using these two conditional integrals, the successful decodig probability of the first layer

can be derived as follows

$$\begin{aligned}\mathbb{P}(R_C^1 < C_{k,L_1}^{\text{qlb}}) &= \int_0^a \mathbb{P}(R_C^1 < C_{k,L_1}^{\text{qlb}} \mid r_{k,L_2} = v, v < a) f_{r_{k,L_2}}(v) dv \\ &\quad + \int_a^\infty \mathbb{P}(R_C^1 < C_{k,L_1}^{\text{qlb}} \mid r_{k,L_2} = v, v > a) f_{r_{k,L_2}}(v) dv \\ &= \frac{1}{\Gamma(L_2)} \bar{\Gamma}(L_2, \gamma_1) + \sum_{n=0}^{L_2-L_1-1} \alpha'_{n,L_1,L_2}(\gamma_1)^{\eta'} \Gamma(L_2 - \eta', \gamma_1),\end{aligned}$$

where $\Gamma(s, x)$ and $\bar{\Gamma}(s, x)$ are upper and lower incomplete gamma functions, respectively. By conditioning the joint probability on r_{k,L_2} , the conditional joint probability is given by

$$\begin{aligned}\mathbb{P}(R_C^1 \leq C_{k,L_1}^{\text{qlb}}, R_C^2 > C_{k,L_2}^{\text{qlb}} \mid r_{k,L_2} = v) &= \mathbb{P}(R_C^2 > C_{k,L_2}^{\text{qlb}} \mid r_{L_2}) \mathbb{P}(R_C^1 \leq C_{k,L_1}^{\text{qlb}} \mid r_{k,L_2} = v) \\ &= \mathbb{1}(r_{L_2} > \hat{r}_{L_2}) \mathbb{P}(R_C^1 \leq C_{k,L_1}^{\text{qlb}} \mid r_{k,L_2} = v).\end{aligned}\quad (3.41)$$

By considering the two cases $a \leq \hat{r}_{k,L_2}$ or $a > \hat{r}_{k,L_2}$ the joint probability is calculated as follows. The expression $a \leq \hat{r}_{k,L_2}$ is equivalent to $(C_{k,L_1}^{\text{qlb}})^{-1}(R_C^1) \geq (C_{k,L_2}^{\text{qlb}})^{-1}(R_C^2)$. Notice that $C_{k,\ell}^{\text{qlb}}(\tilde{\rho}_{k,\ell})$ is strictly monotonically increasing in $\tilde{\rho}_{k,\ell}$, and this simplifies the expression $(C_{k,L_1}^{\text{qlb}})^{-1}(R_C^1) \geq (C_{k,L_2}^{\text{qlb}})^{-1}(R_C^2)$ to $R_C^1 \geq R_C^2$.

$$\textbf{Case 1: } \mathbb{P}(R_C^1 \leq C_{k,L_1}^{\text{qlb}}, R_C^2 > C_{k,L_2}^{\text{qlb}} \mid R_C^1 \geq R_C^2) = \sum_{n=0}^{L_2-L_1-1} \alpha'_{n,L_1,L_2}(\gamma_1)^{\eta'} \Gamma(L_2 - \eta', \gamma_2) \quad (3.42)$$

$$\begin{aligned}\textbf{Case 2: } \mathbb{P}(R_C^1 \leq C_{k,L_1}^{\text{qlb}}, R_C^2 > C_{k,L_2}^{\text{qlb}} \mid R_C^1 < R_C^2) \\ = \frac{1}{\Gamma(L_2)} \bar{\Gamma}(L_2, \gamma_1) - \frac{1}{\Gamma(L_2)} \bar{\Gamma}(L_2, \gamma_2) + \sum_{n=0}^{L_2-L_1-1} \alpha'_{n,L_1,L_2}(\gamma_1)^{\eta'} \Gamma(L_2 - \eta', \gamma_1),\end{aligned}\quad (3.43)$$

where $\gamma_2 = \frac{\eta-2}{2(C_{k,L_2}^{\text{qlb}})^{-1}(R_C^2)}$. Similarly, the last joint probability is given by two cases as follows

$$\begin{aligned}\textbf{Case 1: } \mathbb{P}(R_C^1 \leq C_{k,L_1}^{\text{qlb}}, R_C^2 \leq C_{k,L_2}^{\text{qlb}} \mid R_C^1 \geq R_C^2) \\ = \frac{1}{\Gamma(L_2)} \bar{\Gamma}(L_2, \gamma_1) - \sum_{n=0}^{L_2-L_1-1} \alpha'_{n,L_1,L_2}(\gamma_1)^{\eta'} \Gamma(L_2 - \eta', \gamma_2) \\ + \sum_{n=0}^{L_2-L_1-1} \alpha'_{n,L_1,L_2}(\gamma_1)^{\eta'} \Gamma(L_2 - \eta', \gamma_1)\end{aligned}\quad (3.44)$$

$$\text{Case 2: } \mathbb{P}(R_C^1 \leq C_{k,L_1}^{\text{qlb}}, R_C^2 \leq C_{k,L_2}^{\text{qlb}} \mid R_C^1 < R_C^2) = \frac{1}{\Gamma(L_2)} \bar{\Gamma}(L_2, \gamma_2). \quad (3.45)$$

3.4. Suboptimal Rate and Cache Allocation

In this section, we also provide a feasible but generally sub-optimal solution to the non-convex optimization problem defined in (3.17). This optimization has two constraints for cache allocation and minimum distortion requirement. Since the problem is non-convex and does not seem to have some especially appealing structure that can be exploited for its efficient solution, mainly due to the complicated dependency of the probabilities of layer decoding error on the channel coding rates, we propose an iterative method described in Algorithm 1. We denote by $T(R_C^1, R_C^2, \mu_1, \mu_2)$ the value of T in (3.12) for given $R_C^1, R_C^2, \mu_1, \mu_2$. Then, the algorithm applies alternate minimization by fixing μ_1, μ_2 and minimizing with respect to R_C^1, R_C^2 , and for the found values of R_C^1, R_C^2 minimizing with respect to μ_1, μ_2 .

We can handle the constrained minimization of $T(R_C^1, R_C^2, \mu_1, \mu_2)$ subject to the distortion constraint with respect to R_C^1, R_C^2 for fixed μ_1, μ_2 using the *Particle Swarm Optimization* (PSO) algorithm [49]. PSO performs a heuristic search in order to find a good feasible point. It is useful for minimizing a function with linear/nonlinear inequality constraints and it uses a penalty function technique to solve an unconstrained optimization instead of its constrained counterpart. Interestingly, the solution of the minimization with respect to μ_1, μ_2 for fixed R_C^1, R_C^2 can be found in closed form. Notice that the constraint $D_k \leq D_0$ involves only the variables R_C^1, R_C^2 , therefore, it does not play any role in the optimization of μ_1, μ_2 . The function $T(R_C^1, R_C^2, \mu_1, \mu_2)$ is convex in the vector $\boldsymbol{\mu} = [\mu_1, \mu_2]$. The minimization with respect to μ_1, μ_2 at the t -th step of our iterative algorithm is given by:

$$\begin{aligned} & \underset{\mu_1, \mu_2}{\text{minimize}} && T(R_C^{1,(t)}, R_C^{2,(t)}; \mu_1, \mu_2) \\ & \text{subject to} && \sum_{i=1}^2 \mu_i \hat{R}_S^i = \mu \end{aligned} \quad (3.46)$$

The partial Lagrangian function (not taking into account the non-negativity constraints) is given by

$$\mathcal{L}(\lambda, \boldsymbol{\mu}) = T(R_C^{1,(t)}, R_C^{2,(t)}; \mu_1, \mu_2) + \lambda \left(\sum_{i=1}^2 \mu_i \hat{R}_S^i - \mu \right). \quad (3.47)$$

We use cvx toolbox to solve above convex optimization.

Alternatively we could use only PSO with two constraints of distortion and cache allocation with four parameters $\mu_1, \mu_2, R_C^1, R_C^2$.

Algorithm 1 Searching strategy**Require:** μ, K, η, n and $L_i, R_S^i, i \in [2]$:

- 1: Set the initial value $\mu_{1,(1)} = \mu$ and $\mu_{2,(1)} = \mu$
- 2: **for** $t = 1 : n$ **do**
- 3: $[R_C^{1,(t)}, R_C^{2,(t)}] = \arg \min T(R_C^{1,(t)}, R_C^{2,(t)}, \mu_{1,(t)}, \mu_{2,(t)})$
- 4: Solve the Lagrangian problem and update the value $\mu_{1,(t+1)}, \mu_{2,(t+1)}$
- 5: **end for**

3.5. Results and Discussions

In this section we provide numerical examples to illustrate the sub-optimal solution for the delivery latency in (3.17). We considered realistic values of the pathloss exponent $\eta = 3.75$ and the number of antennas $n_r = 8$ at the user receivers and source coding rate $R_S^1 = 1$ and $R_S^2 = 2$. The macro diversity for the receiving layers are considered to be $L_1 = 2$ and $L_2 = 4$.

In Fig. 3.2, the cache allocation among layers is illustrated for target distortion $D_k \leq 0.2$. We compare the performance of the cache allocation according to the solution of the optimization in (3.17) with the scenario where the cache allocation is given by $\mu_1 = \mu_2 = \mu$. The metric for this comparison takes their delivery latency into account and is given by

$$\Delta T_n = \frac{T_{\text{unif}} - T_{\text{opt}}}{T_{\text{opt}}} \quad (3.48)$$

where T_{opt} and T_{unif} are the average delivery latencies for the former and latter scenario, respectively. The comparison is illustrated in Fig. 3.3 for various distortion requirements. The sub-optimal iterative method with heuristic searching decreases the delay between 2 – 20%. As can be seen in Fig. 3.3, the proposed optimization achieves significantly better performance for high target distortion values. As we discussed earlier superposition coding provides an opportunity to send both layers in same frequency and time slot. In Fig. 3.4, superposition coding reached a better delivery latency compared to TDMA for the same cache memory budget.

3.6. Conclusion

We studied an extension of the classical coded caching scheme with the goal of achieving spatial scalability and graceful degradation. Spatial scalability is obtained by sending the coded caching codewords simultaneously from multiple helpers, using MDS coding in order to enforce a desired level of macro-diversity. Graceful degradation is obtained by using successive refinement source coding and encoding the source files into a fundamental layer and a refinement layer. The scheme can be also interpreted as the concatenation of coded

Figure 3.2.: Cache allocation among layers with time-sharing scheme

Figure 3.3.: Improvement of delivery latency of optimized cache allocation over uniform cache allocation with time-sharing scheme

caching with a multiple-description code, where the users that can decode L_1 descriptions achieve a distortion level D_1 of the fundamental layer, and the users that can decode $L_2 > L_1$ descriptions achieve a distortion level $D_2 < D_1$ of the refinement layer. We studied the optimization of the delivery time subject to an average per-user distortion constraint. The optimization is with respect to the channel coding rates for the transmission of the two layers, and the memory allocation parameter of the user caches between the two layers. The optimization is non-convex, but it can be handled by alternating minimization. The proposed system could be applied to the lossy transmission of video-on-demand (unicast traffic) via multipoint multicasting, conceptually similar to a caching extension of eMBMS, to handle individual user demands and not only broadcast common content (such as Live TV). The approach can be extended to more than 2 layers, but the main bottleneck consists of the analysis of the probability of successful decoding of a given number ℓ of layers, since this involves the joint distribution of the first L distances of a PPP with respect to the origin. We compared the performance of applying superposition coding instead of using TDMA to transmit coded multicast messages of the fundamental and enhancement layers. Superposition coding provides a lower delivery latency compared to TDMA.

Figure 3.4.: Comparison of delivery latency of optimized cache allocation for time sharing and superposition coding with $K = 10$, $D = 0.2$, $L_1 = 2, L_2 = 4$

4. Multicast Routing Scheme in Practical Wireless Networks

4.1. Background and Motivation

Due to the growing consumption of on-demand multimedia content, a clever use of caching exploiting the low-cost storage capacity on user devices plays a key role in the design of efficient content distribution schemes. In this context, *caching* refers in general to the prefetching of popular files (or blocks thereof) at the edge nodes such that the traffic load can be reduced when users' demands are revealed. For example, [59] introduced *femtocaching* in wireless networks, where caching is performed at "helper" nodes modeling Access Points (APs) or Base Stations (BSs) in a spatially distributed wireless local area or cellular network. More recently, Fog Radio Access Networks (F-RAN) have been proposed, where helpers may possess local caches as well as baseband processing units. By letting helpers store popular files in their cache memories, [47] treats the joint design of the centralized (cloud) and decentralized (fog) processing to satisfy users' demands.

The above works, as well as many others that would be too long to mention here, are based on *uncoded caching*, where the demanded files are directly transmitted from the caches at the helpers and from the server through the network. A different line of works considers *coded caching* strategies, where the cache content at the users is exploited as side information such that coded *multicast messages* are simultaneously useful for many users. Through coding, individual user demands (unicast traffics) are converted into multicast messages which may be better suited to the broadcast property of the transmission medium.

In the MAN scheme, the prefetching phase is centrally coordinated. In practice, coordination may not be possible. For example, in a mobile network over an extended coverage area it would be impractical that all users receive from the same giant transmitter. In a typical wireless network scenario, the server communicates to the users via a layer of spatially distributed helper nodes (APs/BSs). Hence, due to mobility, the local cache configuration in each cell cannot be centrally pre-designed during the prefetching phase. Furthermore, users join and leave the network at arbitrary times and in an uncoordinated fashion. Therefore, *decentralized* prefetching schemes are needed in practice.

Another important aspect of practical systems is that user on-demand streaming sessions start and end at arbitrary times and are formed by sequences of HTTP requests, fetching sequentially chunks of the streamed video file [26] and [54]. The fundamental performance in this context is the *average delivery time* per chunk, which must be (slightly) smaller than the chunk playback time in order to keep the probability of empty playback buffer (buffer underrun) sufficiently small [6]. In order to handle the streaming sessions asynchronism in coded caching, each large video file can be divided into blocks, which are themselves identified with the “library files” of the coded caching scheme [37]. In order to avoid a long waiting time before starting a streaming session, the block playback duration should not exceed a few tens of seconds. For example, with a streaming rate of 2 Mbit/s, and 10s blocks, each effective file item in the library has size of 20 Mbits. This means that even though the actual video files may be very large, the effective length of the library files treated by the coded caching scheme is limited. This imposes a limitation of the *subpacketization order* of the coded caching scheme, i.e., the number of segments in which each library file is divided in order to be cached in the prefetching phase. In particular, in the MAN scheme the subpacketization order grows exponentially with the number of users K , which makes the scheme impractical for large networks.

Beyond user mobility and limited subpacketization order, there are several other practical issues that must be addressed in order to make the coded caching paradigm suitable for practical implementations (see for example the discussion in [5]). In particular, here we would like to mention: i) the problem of HTTP encryption, for which the user request can be decrypted only by the server, which belongs to the content owner (e.g., Netflix, Google, Apple) and not by intermediate helper nodes (APs and BSs belonging to some wireless network operator); ii) the fact that a content delivery scheme is typically run “above IP”, i.e., at the application and transport layer, and does not involve the underlying lower layers such as PHY and MAC, which follow some existing legacy standard (e.g., IEEE802.11, LTE, 5G NR) and are not under the control of the content distribution system; iii) the fact that in modern content distribution networks a single content server handles very large regions corresponding to tens of cells (e.g., an entire large metropolitan area) [2]. In particular, point (i) rules out the possibility of “fog” caching at the helper nodes (considered for example in [25,30,66]), since the helpers are not supposed to store content and are oblivious of the user requests; point (ii) rules out the possibility of joint PHY and caching design, as for example combining coded caching with MIMO zero-forcing precoding as in [32]; and point (iii) greatly de-emphasizes the relevance of various “multiserver” models [43,61].

Overall, these considerations motivate us to study network models resulting from the network-layer abstraction the underlying physical wireless network. Our model consists of one server, co-located with a library of N files, a layer of H helper nodes, connected to

Figure 4.1.: A pictorial representation of the networks considered in this work, formed by one server communicating to K users via H helpers, and routing coded caching packets via a multicast IP network.

the server via capacitated *fronthaul* links, and K users, connected to a limited number of helpers via a wireless *access network*, depending on their geographic location on the network area. The server communicates to the users via the helper nodes, and uses a multicast routing protocol (typically IP multicast) in order to leverage the multicast nature of the coded caching delivery phase. The helper nodes represent APs/BSs and are oblivious of the user demands and of the caching scheme, i.e., they can only forward to the users what they receive from the server. This captures the fact that helpers can only read the IP routing control of the packets, but cannot process, combine, or store such packets. Fig. 4.1 represents qualitatively the class of networks treated in this dissertation.

4.1.1. Contributions

This work extends the MAN scheme to the aforementioned two-hop network by considering the following two variants: i) A topological network formed by non-interfering links of limited capacity (referred to as “topological network” model in the following); ii) A network with broadcast constraints at the helpers and collision interference at the users (referred to as “broadcast/collision network” model in the following). *For both models, we propose schemes that solve at once all the problems mentioned before, i.e., subpacketization order, large network scalability, decentralized/asynchronous users’ activity, and transparency of the helper nodes which must only execute a standard multicast routing scheme oblivious of the content files and user requests, and therefore can support HTTP encryption.* Our main contributions are summarized as follows:

1) For the topological network model, we propose a novel scheme based on decentralized random cache replication prefetching and optimized routing of the MAN-type coded mul-

ticast messages. The routing optimization can be solved via a sequence of linear programs (LPs), with linear complexity in the network size. For comparison, we consider also a direct extension of the so-called *multiround delivery* scheme in [27, 48]. The proposed novel routing strategy generally outperforms the extended multiround scheme since the latter is a particular feasible point of the optimization problem yielding the former.

2) For the broadcast/collision model, we first propose a two-step baseline reuse scheme, where in the first step we assign to the same transmission resource (e.g., a time slot or a frequency subband) groups of mutually non-interfering helpers by graph coloring, and in the second step we assign the users to the helpers in an optimal way (which may be computationally hard) or using a greedy approach. Then, for the same broadcast/collision model, we propose a novel scheme that embraces interference and serves users as they become interference-free. This approach is nicknamed *avalanche scheme* since the users are freed of interference progressively as some helper finish serving its own list of interference-free users, and this property propagates through the network as an avalanche. The scheme has a practical appeal since it could be implemented via the CSMA protocol, where collisions are discarded at the receivers (the users) and helpers pause transmission when they have finished serving the users in their service list. The avalanche scheme not only avoids the graph coloring problem which is generally NP-hard, but also outperforms the reuse scheme since instead of following a fixed reuse partition of the transmission resource makes use of it in a more adaptive and opportunistic way. We show that for sparse graphs, which is the case for spatially distributed wireless networks, the complexity of the avalanche scheme is linear in the network size.

4.2. Topological Networks of Non-Interfering Links

In this section we consider our first network abstraction, formed by non-interfering links connecting the server to the helpers and the helpers to the users. The network is defined by layered graph as shown in Fig. 4.2. The underlying topology of the spatially distributed wireless network is reflected in the association between users and helpers. In particular, each helper is connected to a number of users through some mechanism of user-BS association (e.g., a helper is associated to all the users within a certain *signaling radius* a_{sig}). As motivated in Section 4.1, the specific association mechanism may be the result of some legacy PHY/MAC schemes operating “below IP” and not under the control of the caching/content delivery system. For the sake of our treatment, the details of the user-helper association mechanism are irrelevant since the access network topology is not part of the delivery optimization. The links in this model are “logical”, i.e., we assume that some reuse, resource allocation, and MAC protocol are able to maintain given transmission rates

(a) Layout geometry and user-helper association.

(b) Corresponding topological network graph.

Figure 4.2.: An example of the network topology considered in Section 4.2.1 with $H = 4$ and $K = 6$. In the graph the helpers and the users are enumerated in increasing order from left to right.

between associated pairs of helpers and users, such that the network layer can execute a routing algorithm on the resulting graph. The fact that users can receive simultaneously from multiple helpers reflects some form of *macro-diversity* and *carrier aggregation*, for which the users are able to receive on different channels at the same time.

4.2.1. System Model

We denote the library of N files as $\mathcal{F} = \{W_1, W_2, \dots, W_N\}$ where each file has size of F bits. The connectivity between the server and the helpers is referred to as the *fronthaul*, and consists of H error-free wired (i.e., non-interfering) links of capacity C_{front} bits per unit time connecting the server to the helpers. The connectivity between helpers and users is referred to as the *access network* and consists of a bipartite graph (see Fig. 4.2). We assume that sum of the capacities of the links outgoing from any given helper cannot be larger than the downlink sum capacity of the helper. For simplicity, we consider the symmetric case

where all helpers have the same downlink capacity denoted by C_{access} . This assumption can be trivially generalized to helpers with different downlink capacities.

In passing, we notice that the network model considered in this section is a generalization of the model in [41], where each user is connected to exactly r helpers (for some integer $r \in [H]$). In turn, this is a generalization of the so-called *combination network*, where $K = \binom{H}{r}$ and there is a user connected to each distinct combination of r out of H helpers, as considered in the context of coded caching in [25, 65]. The subset of users connected to helper $h \in [H]$ and the subset of helpers connected to user $k \in [K]$ are denoted by $\mathcal{U}_h$ and $\mathcal{H}_k$, respectively. The capacities of the links $h \rightarrow k$, denoted by $C_{h \rightarrow k}$, must satisfy the sum constraint

$$\sum_{k \in \mathcal{U}_h} C_{h \rightarrow k} \leq C_{\text{access}}. \quad (4.1)$$

Each user is equipped with a cache memory capable of storing up to MF bits, for some $M \in [N]$, while the helpers do not possess any cache memory and can only forward packets received from the server to their connected users. In the prefetching phase, user $k \in [K]$ stores some subfiles from the N library files. This phase is done without knowledge of the users' demands and of the network topology. We denote the content in the cache of user $k \in [K]$ by Z_k and let $\mathbf{Z} = \{Z_1, \dots, Z_K\}$ denote the collection of all caches in the system. During the delivery phase, each user $k \in [K]$ demands file W_{d_k} where $d_k \in [N]$. The demand vector $\mathbf{d} = \{d_1, \dots, d_K\}$ is revealed to all nodes as metacontent information embedded in the packets sent by the server to the users. Given $(\mathbf{d}, \mathbf{Z})$, the server sends message $X_{s \rightarrow h}$ of $R_h F$ bits to helper h , for all $h \in [H]$. Then, helper h transmits message $X_{h \rightarrow k}$ of $R_{h \rightarrow k} F$ bits to user k , for all $k \in \mathcal{U}_h$. User $k \in [K]$ must recover its desired file W_{d_k} from Z_k and the collection of received messages $\{X_{h \rightarrow k} : h \in \mathcal{H}_k\}$ from the helpers. A coded caching scheme is said to be *feasible* if, for any demand vector $\mathbf{d}$, all users recover their desired file with vanishing probability of error as $F \rightarrow \infty$.

As in most literature on coded caching (e.g., see [36, 71]), we focus on the worst-case delivery time over all possible demand vectors $\mathbf{d}$. We consider a pipelined transmission in which fronthaul links and local access links work in parallel. Messages are sufficiently long such that they can be broken into smaller packets and helpers can simultaneously receive such packets from their fronthaul links while transmitting previously received packets on the access links to the users. When the number of packets per message is large, the delivery time is the maximum between the delivery times in the first (fronthaul) and second (access) hops. The latency along a path from the server to user $k \in \mathcal{U}_h$ via helper h is given by $\max \left\{ \frac{R_h F}{C_{\text{front}}}, \frac{R_{h \rightarrow k} F}{C_{h \rightarrow k}} \right\}$. For each user k , the overall delivery time is the maximum of the latencies incurred by the data that have to reach user k , given by

$\max_{h \in \mathcal{H}_k} \max \left\{ \frac{R_h F}{C_{\text{front}}}, \frac{R_{h \rightarrow k} F}{C_{h \rightarrow k}} \right\}$. Finally, the worst-case user delivery time is given by

$$\max_{k \in [K]} \max_{h \in \mathcal{H}_k} \max \left\{ \frac{R_h F}{C_{\text{front}}}, \frac{R_{h \rightarrow k} F}{C_{h \rightarrow k}} \right\},$$

which is equivalently written as $\max\{T_{\text{front}}, T_{\text{access}}\}$, where we define

$$T_{\text{front}} = \max_{h \in [H]} \frac{R_h F}{C_{\text{front}}}$$

and

$$T_{\text{access}} = \max_{h \in [H], k \in \mathcal{U}_h} \frac{R_{h \rightarrow k} F}{C_{h \rightarrow k}}.$$

Eventually, the minimization over the cache design $\mathbf{Z}$ and the access link capacity allocation $\{C_{h \rightarrow}\}$ of the worst-case user delivery time is given by

$$T^* = \min_{\mathbf{Z}} \max_{\mathbf{d} \in [N]^K} \min_{\substack{\{C_{h \rightarrow k}\} \\ \sum_k C_{h \rightarrow k} \leq C_{\text{access}}}} \max\{T_{\text{front}}, T_{\text{access}}\}. \quad (4.2)$$

4.2.2. Coded Caching Scheme

For future reference, we briefly review here the MAN scheme for single shared-link network [36]. This network is a special case of the topological network model treated here with $H = 1$ helper connected to all K users, and with $C_{\text{access}} = K C_{\text{front}}$. Define the *library replication parameter* $t = KM/N$ as how many times the library can be contained in the collective cache memory of all users, and assume that $t \in [0 : K]$ (for non-integer t , a standard memory sharing approach can be used as done in several existing works, e.g., [36]). We define the collection of all user subsets of some integer size $r \in [0 : K]$ as $\Omega_r^K = \{\mathcal{U} \subseteq [K] : |\mathcal{U}| = r\}$. Each file W_i is partitioned into $\binom{K}{t}$ non-overlapping and equal-length subfiles $W_{i, \mathcal{T}}$, for all user subsets $\mathcal{T} \in \Omega_t^K$. Each user $k \in [K]$ caches the subfiles $W_{i, \mathcal{T}}$ for all $\mathcal{T} \ni k$ for all $i \in [N]$. In the delivery phase, for each subset $\mathcal{S} \in \Omega_{t+1}^K$, the server broadcasts the coded multicast message

$$V_{\mathcal{S}} = \bigoplus_{k \in \mathcal{S}} W_{d_k, \mathcal{S} \setminus \{k\}}. \quad (4.3)$$

Each user $k \in \mathcal{S}$ requires $W_{d_k, \mathcal{S} \setminus \{k\}}$ since by definition this subfile is needed (d_k is the index of the file wanted by user k) and not cached (since obviously $k \notin \mathcal{S} \setminus \{k\}$). Furthermore, all other subfiles $W_{d_j, \mathcal{S} \setminus \{j\}}$ for $j \in \mathcal{S}, j \neq k$ in the XOR (4.3) are in the cache of user k since $k \in \mathcal{S} \setminus \{j\}$. Therefore, each user $k \in \mathcal{S}$ can recover $W_{d_k, \mathcal{S} \setminus \{k\}}$ from $V_{\mathcal{S}}$ and eventually all demands are satisfied. For sufficiently large F , so that the subpacketization order $\binom{K}{t}$ is

possible, then the MAN scheme achieves deliver time

$$T^{\text{MAN}} = \frac{F}{C_{\text{front}}} \frac{\binom{K}{t+1}}{\binom{K}{t}} = \frac{F}{C_{\text{front}}} \frac{K-t}{1+t}. \quad (4.4)$$

4.2.3. Centralized Coded Caching and Routing Optimization

As a prelude to the proposed caching and delivery scheme of Section 4.2.5, we present here a direct application of the MAN scheme with routing-based delivery for a general topological network model. The purpose of this section is also to illustrate why such a scheme would be completely impractical, and therefore to motivate the following novel schemes. Define t and the caches configurations $\{Z_k\}$ as in the MAN scheme of Section 4.2.2. At the server side, the subfiles are individually precoded by using an erasure code over a sufficiently large finite field. Each subfile is represented as a sequence of finite field symbols over a binary-extension finite field $\mathbb{F}_{2^q}$ for some integer q . We denote by $\widehat{W}_{i,\mathcal{T}}$ the encoded version of $W_{i,\mathcal{T}}$, i.e., the resulting sequence of linear combinations over $\mathbb{F}_{2^q}$.¹ Letting $F' = F/(q\binom{K}{t})$ denote the length of the subfiles $W_{i,\mathcal{T}}$ in finite-field symbols, we define the normalized length of the codewords $\widehat{W}_{i,\mathcal{T}}$ as $y = |\widehat{W}_{i,\mathcal{T}}|/F' \geq 1$, same for all subfiles. This precoding is designed such that the original subfile $W_{i,\mathcal{T}}$ can be retrieved from any F' distinct symbols of $\widehat{W}_{i,\mathcal{T}}$.²

In the delivery phase, we create the coded multicast messages for each user group $\mathcal{S} \in \Omega_{t+1}^K$ by XOR-ing the precoded subfiles, i.e., we let $\widehat{X}_{\mathcal{S}} = \bigoplus_{k \in \mathcal{S}} \widehat{W}_{d_k, \mathcal{S} \setminus \{k\}}$. We let $\widehat{X}_{\mathcal{S}}^h$ denote the segment of $\widehat{X}_{\mathcal{S}}$ sent to helper h . After receiving $\widehat{X}_{\mathcal{S}}^h$, helper h forwards it to the users in $\mathcal{S} \cap \mathcal{U}_h$. We let $y_{\mathcal{S}}^h = \frac{|\widehat{X}_{\mathcal{S}}^h|}{F'}$, where $y_{\mathcal{S}}^h = 0$ if $\mathcal{S} \cap \mathcal{U}_h = \emptyset$, i.e., $\widehat{X}_{\mathcal{S}}^h$ is not forwarded at all to the helpers not connected to at least one user in $\mathcal{S}$. When a user $k \in \mathcal{S}$ receives $\widehat{X}_{\mathcal{S}}^h$ containing some symbols of its desired codeword $\widehat{W}_{d_k, \mathcal{S} \setminus \{k\}}$, it is able to locally generate the corresponding symbols of the interfering codewords $\widehat{W}_{d_j, \mathcal{S} \setminus \{j\}}$ for $j \in \mathcal{S}, j \neq k$ participating in the XOR from its cache content, and “cache out” the desired symbols. Thanks to the subfile precoding, if a user recovers F' distinct symbols of $\widehat{W}_{d_k, \mathcal{S} \setminus \{k\}}$, then it will be able to decode the whole desired subfile $W_{d_k, \mathcal{S} \setminus \{k\}}$. By making y large enough, it is always possible to make sure that the symbols cached out by user k from all its connected helpers $h \in \mathcal{H}_k$ are all distinct. It follows that the scheme is feasible if

$$\sum_{h \in \mathcal{H}_k} y_{\mathcal{S}}^h \geq 1, \quad \forall \mathcal{S} \in \Omega_{t+1}^K, \text{ and } \forall k \in \mathcal{S}. \quad (4.5)$$

¹In this section we use the “hat” notation $\widehat{A}$ to indicate blocks A of symbols over $\mathbb{F}_q$, whose length $|\widehat{A}|$ is given by the number of finite-field symbols.

²This can be implemented by intra-session random linear network coding [31, 41, 67] or algebraic MDS codes, as long as an MDS code with parameters (F', yF') over $\mathbb{F}_{2^q}$ exists.

From the above arguments it is clear that the scheme is feasible for sufficiently large field size 2^q and sufficiently large normalized length y since, for any $\mathbf{d}$, each user $k \in [K]$ can decode its desired file W_{d_k} if the server sends messages X_S^h to helpers $h \in [H]$ for all $\mathcal{S} \in \Omega_{t+1}^K$ such that (4.5) holds.

The length (in bits) of the message $\hat{X}_S^h$ is given by $qF'y_S^h = Fy_S^h/\binom{K}{t}$. The normalized link load from the server to each helper $h \in [H]$ is obtained by summing the length of all the multicast messages and dividing by F , yielding

$$R_h = \frac{1}{\binom{K}{t}} \sum_{\mathcal{S} \in \Omega_{t+1}^K} y_S^h. \quad (4.6)$$

Similarly, the normalized load for link $h \rightarrow k$ is obtained by summing over the messages forwarded by h to k and is given by

$$R_{h \rightarrow k} = \frac{1}{\binom{K}{t}} \sum_{\mathcal{S} \in \Omega_{t+1}^K : \mathcal{S} \ni k} y_S^h. \quad (4.7)$$

Hence, we have

$$T_{\text{front}} = \max_{h \in [H]} \frac{F}{C_{\text{front}} \binom{K}{t}} \sum_{\mathcal{S} \in \Omega_{t+1}^K} y_S^h, \quad (4.8)$$

$$T_{\text{access}} = \max_{h \in [H]} \max_{k \in \mathcal{U}_h} \frac{F}{C_{h \rightarrow k} \binom{K}{t}} \sum_{\mathcal{S} \in \Omega_{t+1}^K : \mathcal{S} \ni k} y_S^h, \quad (4.9)$$

and resulting routing and resource allocation problem is given by

$$\begin{aligned} & \underset{(y_S^h, C_{h \rightarrow k} \geq 0 : \mathcal{S} \in \Omega_{t+1}^K, h \in [H], k \in [K])}{\text{minimize}} && \max\{T_{\text{access}}, T_{\text{front}}\} \end{aligned} \quad (4.10a)$$

$$\text{subject to: } y_S^h = 0, \forall \mathcal{S} \cap \mathcal{U}_h = \emptyset, \quad (4.10b)$$

$$\sum_{h \in \mathcal{H}_k} y_S^h \geq 1, \forall \mathcal{S} \text{ and } \forall k \in \mathcal{S}, \quad (4.10c)$$

$$\sum_{k \in \mathcal{U}_h} C_{h \rightarrow k} \leq C_{\text{access}}, \forall h \in [H]. \quad (4.10d)$$

The optimization in (4.10) is not an LP because the objective function contains the ratio $\frac{y_S^h}{C_{h \rightarrow k}}$. However, it is possible to solve (4.10) through a sequence of LPs. First, we rescale the objective function in (4.10) by $C_{\text{front}} \binom{K}{t} / F$, which is just a fixed constant. Up to this

scaling, the problem is equivalent to

$$\begin{aligned} & \underset{(y_S^h, C_{h \rightarrow k} \geq 0 : S \in \Omega_{t+1}^K, h \in [H], k \in [K])}{\text{minimize}} \quad \alpha \end{aligned} \quad (4.11a)$$

$$\text{subject to: } \sum_{S \in \Omega_{t+1}^K} y_S^h \leq \alpha, \quad \forall h \in [H], \quad (4.11b)$$

$$\sum_{S \in \Omega_{t+1}^K : S \ni k} y_S^h \leq \frac{C_{h \rightarrow k}}{C_{\text{front}}} \alpha, \quad \forall h \in [H], \forall k \in [K], \quad (4.11c)$$

$$y_S^h = 0, \quad \text{if } S \cap \mathcal{U}_h = \emptyset, \quad (4.11d)$$

$$\sum_{h \in \mathcal{H}_k} y_S^h \geq 1, \quad \forall S \text{ and } \forall k \in S, \quad (4.11e)$$

$$\sum_{k \in \mathcal{U}_h} C_{h \rightarrow k} \leq C_{\text{access}}, \quad \forall h \in [H]. \quad (4.11f)$$

Written in the form (4.11), the problem can be solved by considering an interval $\alpha \in [0, \bar{\alpha}]$ large enough such that the feasibility problem associated with the constraints in (4.11) for fixed $\alpha = \bar{\alpha}$ is satisfied. Then, using the bisection method, we can determine the minimum α for which feasibility is satisfied.³

As previously anticipated, the subpacketization order of the MAN scheme becomes quickly very large since $|\Omega_t^K| \geq 2^{Kh_2(M/N)}$ (where $h_2(\cdot)$ is the binary entropy function). For constant fractional cache memory $M/N = \mu$ and a large number of users, this exponential growth in K makes the scheme impractical. For example, for a system with $K = 1000$ users and $\mu = 0.01$ (each user caches 1% of the library), the number of subpackets is larger than 2×10^{24} . Even computing the solution of problem (4.11) becomes intractable, because the number of variables $\{y_S^h\}$ and constraints is larger than the number of XOR messages $|\Omega_{t+1}^K|$. In the next section we address both these problems.

4.2.4. Divide and Conquer Greedy Optimization

The numbers of variables and constraints of the LP in (4.10) grow exponentially with the number of users. For very large value of K , the computational complexity of the direct solution of (4.10) becomes prohibitive. In order to reduce the computation complexity, we use greedy programming to break the problem into sub-problems, solve the sub-problems and combine their solutions to get a suboptimal solution to our problem. We explain how to apply the greedy programming to optimal delivery time optimization problem in (4.10). We randomly divide all $\binom{K}{t+1}$ MAN multicast messages into $G < \infty$ non-overlapping and

³In practice, the search stops when the gap between minimum feasible α and the maximum unfeasible α is small enough.

equal-length groups.⁴ We also let $g := \lceil \binom{K}{t+1} / G \rceil$, representing the maximum number of MAN multicast messages included in one group. In addition, the family of MAN multicast sets in the group i is denoted by $\mathcal{G}_i$. The optimization problem in (4.10) can be broken into multiple sub optimizations for each of the groups with a much lower number of variables than (4.10), i.e. $|\mathcal{G}_i| < |\Omega|$. We can apply minimization of the delivery load in each group individually and then iterate through the groups and feed the results from the previous optimization to the next sub-problem.

In the i -th step we solve an optimization for routing the coded multicast message in group $\mathcal{G}_i$ with an initial delivery time α_i^0 and then we use the optimal delivery time α_i until step i as a fixed initial delivery time into the next $(i + 1)$ -th step's optimization problem. Accordingly in (4.11), greedy algorithm can be applied as follows.

$$\begin{aligned}
 & \underset{(y_{\mathcal{S}}^h, C_{h \rightarrow k} : \mathcal{S} \in \Omega_i, h \in [H], k \in [K])}{\text{minimize}} && \alpha_i \\
 & \text{subject to} && \forall \mathcal{S} \in \mathcal{G}_i : \\
 & && \sum_{\mathcal{S}} y_{\mathcal{S}}^h \leq (\alpha_i - \alpha_i^0), \quad \forall h \in [H], \\
 & && \sum_{\mathcal{S}, k \in \mathcal{S}} y_{\mathcal{S}}^h \leq \frac{C_{h \rightarrow k}}{C_{\text{front}}} (\alpha_i - \alpha_i^0), \quad \forall h \in [H], k \in [K], \\
 & && 0 \leq y_{\mathcal{S}}^h \leq 1, \quad \text{if } h \in \mathcal{H}_{\mathcal{S}}, \\
 & && y_{\mathcal{S}}^h = 0, \quad \text{if } h \notin \mathcal{H}_{\mathcal{S}}, \\
 & && \sum_{h \in \mathcal{H}_k} y_{\mathcal{S}}^h \geq 1, \quad \forall k \in \mathcal{S}, \\
 & && \sum_{k \in \mathcal{U}_h} C_{h \rightarrow k, i} \leq C_{\text{access}}, \quad \forall h \in [H], \\
 & && C_{h \rightarrow k, i} \geq 0, \quad \forall h \in [H], k \in [K].
 \end{aligned} \tag{4.12}$$

Where $\alpha_i^0 = \alpha_{i-1}$, it is suboptimal delivery time up to step $i - 1$. For first step, we set $\alpha_1^0 = 0$. Notice that α_i is suboptimal delivery time for all packets from step 1 to i .

4.2.5. Decentralized Coded Caching with Cache Replication

In order to reduce the subpacketization order and allow for *decentralized* prefetching, such that users can join and leave the system at any time irrespectively of the other users, we consider the cache replication approach of [27] in the context of our “network layer” model and propose two delivery schemes. The first is a direct extension of the so-called

⁴If G does not divide $\binom{K}{t+1}$, each of the first $\binom{K}{t+1} - G \lfloor \binom{K}{t+1} / G \rfloor$ groups contains $\lceil \binom{K}{t+1} / G \rceil$ MAN multicast messages and each of the remaining groups contains $\lceil \binom{K}{t+1} / G \rceil - 1$ MAN multicast messages.

multiround delivery scheme of [48]. The second is the first important novel contribution of this chapter, and turns out to be generally more efficient. Following [27], we fix an integer $L < K$ and create a MAN subpacketization for the a system with L *virtual* users, with library replication parameter $t' = LM/N \in [0 : L]$. Hence, each file W_i is divided into $\binom{L}{t'}$ non-overlapping and equal-length subfiles $\{W_{i,\mathcal{T}} : \mathcal{T} \in \Omega_{t'}^L\}$. We generate L cache configurations, one for each virtual user, according to the MAN scheme for L users, such that the ℓ -th cache configuration is given by $\tilde{Z}_\ell = \{W_{i,\mathcal{T}} : \mathcal{T} \in \Omega_{t'}^L, \mathcal{T} \ni \ell, i \in [N]\}$. Notice that the subpacketization reduces from $\binom{K}{t}$ to $\binom{L}{t'}$. For example, in a system with $K = 1000$ users and $\mu = 0.01$ and $L = 10$ the subpacketization order reduces to ~ 300 instead of $\sim 2 \times 10^{24}$.

In the decentralized prefetching phase each user k , when joining the system and independently of the other users, picks at random an index $\ell \in [L]$ and loads the cache configuration $\tilde{Z}_\ell$, i.e., it lets $Z_k = \tilde{Z}_\ell$. The set of users with cache configuration ℓ is denoted by $\mathcal{P}_\ell$. By construction, all users $k \in \mathcal{P}_\ell$ have the same cache configuration $Z_k = \tilde{Z}_\ell$, and the user groups define the partition $\mathcal{P} = \{\mathcal{P}_1, \mathcal{P}_2, \dots, \mathcal{P}_L\}$. In the following, we describe two delivery schemes for the system with cache replication and decentralized prefetching.

Multiround Delivery with Routing Optimization

We start by recalling the so-called *multiround delivery* of [27, 48] to handle the case of cache replication for the MAN model (shared-link network). Consider the case where a single server is connected to K users partitioned into L caching groups $\mathcal{P}_1, \mathcal{P}_2, \dots, \mathcal{P}_L$ as said before, and define the sorting permutation $[\cdot]$ such that $|\mathcal{P}_{[1]}| \geq |\mathcal{P}_{[2]}| \dots \geq |\mathcal{P}_{[L]}|$. Define the *delivery array* $\mathbf{B}$ with L rows and $|\mathcal{P}_{[1]}|$ columns formed by placing in each row $\mathbf{B}_{\ell,:}$ the users in $\mathcal{P}_{[\ell]}$ for $\ell = 1, \dots, L$, respectively, where rows ℓ with $|\mathcal{P}_{[\ell]}| < |\mathcal{P}_{[1]}|$ are padded by zeros in order to have all rows of the same length. The ordered numbers $|\mathcal{P}_{[1]}| \geq |\mathcal{P}_{[2]}| \dots \geq |\mathcal{P}_{[L]}|$, i.e., the length of the non-zero leading segment of each row of $\mathbf{B}$, are referred to as the *occupancy numbers* of the delivery array. Then, each column $\mathbf{B}_{:,j}$, for $j = 1, \dots, |\mathcal{P}_{[1]}|$ corresponds to a set of users with distinct cache configurations. If $\mathbf{B}_{\ell,j} = 0$ it means that the user with the ℓ -th cache configuration is not present. For each column j , let $\mathcal{R}_j = \{\ell \in [L] : \mathbf{B}_{\ell,j} \neq 0\}$ denote the set of present cache configurations. The multiround delivery serves the users in each column of the array $\mathbf{B}$ (i.e., each delivery round) by forming the XORs corresponding to the MAN scheme with parameters N files, L users and library replication t' , only for the multicast subsets $\mathcal{S} \in \Omega_{t'+1}^L$ such that $\mathcal{S} \cap \mathcal{R}_j \neq \emptyset$ (otherwise the XOR messages would be useless in round j). Each XOR packet of such delivery has length $F/\binom{L}{t'}$ bits, and all the users in column j are served in $\binom{L}{t'+1} - \binom{L-|\mathcal{R}_j|}{t'+1}$ XOR transmissions. Grouping the columns by the number of zeros $b = 0, \dots, L-1$, $\mathbf{B}$ contains exactly $|\mathcal{P}_{[L-b]}| - |\mathcal{P}_{[L-b+1]}|$ columns with b zeros (where we

define $|\mathcal{P}_{[L+1]}| := 0$). The duration of the multiround delivery in XOR packets is

$$\sum_{b=0}^{L-1} |\mathcal{P}_{[L-b]}| - |\mathcal{P}_{[L-b+1]}| \left(\binom{L}{t'+1} - \binom{b}{t'+1} \right). \quad (4.13)$$

Dividing by $\binom{L}{t'}$ and rearranging terms, we arrive at the total delivery load

$$R_{\text{multiround}} = \sum_{r=1}^{L-t'} \frac{|\mathcal{P}_{[r]}| \binom{L-r}{t'}}{\binom{L}{t'}}. \quad (4.14)$$

The load in (4.14) was proven to be optimal for the shared-link network with assigned occupancy numbers [48].

In order to extend multiround delivery to the considered two-hop helper network, after partitioning the users into the caching groups $\mathcal{P}_1, \mathcal{P}_2, \dots, \mathcal{P}_L$, we can apply the routing optimization (4.11) for each delivery round (i.e., column of the resulting delivery array $\mathbf{B}$) independently, with the caveat that the set of XORs in round j is given by $\{\mathcal{S} \in \Omega_{t'+1}^L : \mathcal{S} \cap \mathcal{R}_j \neq \emptyset\}$. Eventually, the multiround scheme yields a total of $|\mathcal{P}_{[1]}|$ separate optimization problems, i.e., one for each round. Notice that $|\mathcal{P}_{[1]}| \leq K$ (in fact, for large K and random uniform assignment of the caching groups this is close to K/L up to small fluctuations by the law of large numbers) and $|\Omega_{t'+1}^L| = O(1)$ (constant with respect to K). Therefore, the complexity of this scheme is *linear* in the number of users K .

New Delivery Scheme based on Routing Optimization

Although multiround delivery is worst-case load optimal for the single shared-link network, in our model users with the same cache configuration are not equivalent due to the network topology. Hence, the load depends on the choice of the users in each round. Therefore, applying multiround delivery for our topological network model is generally suboptimal.

In this section we propose a novel delivery strategy that generally beats multiround delivery. The idea is to create coded multicast messages based on the network topology, such that they are simultaneously useful for users connected to same helper. In other words, there are no multicast messages simultaneously useful for users k, k' for which $\mathcal{H}_k \cap \mathcal{H}_{k'} = \emptyset$ (no common helpers in their connectivity set). For each user k in caching group ℓ_k , we need to transmit missing subfiles of the type $W_{d_k, \mathcal{S} \setminus \{\ell_k\}}$ where $\mathcal{S} \in \Omega_{t'+1}^L$ and $\mathcal{S} \ni \ell_k$. We define $W_{d_k, \mathcal{S} \setminus \{\ell\}}^h$ as the segment of $W_{d_k, \mathcal{S} \setminus \{\ell\}}$ sent to helper $h \in \mathcal{H}_k$ and define $y_{k, \mathcal{S} \setminus \{\ell\}}^h = \frac{|W_{d_k, \mathcal{S} \setminus \{\ell\}}^h|}{F/\binom{L}{t'}}$ as its normalized length. We define $\widetilde{W}_{\ell, \mathcal{S} \setminus \{\ell\}}^h = \cup_{k \in \mathcal{P}_\ell \cap \mathcal{U}_h} W_{d_k, \mathcal{S} \setminus \{\ell\}}^h$ as the concatenation of the subfiles segments required by the users connected to helper h with same cache configuration ℓ . Notice that if $\mathcal{P}_\ell \cap \mathcal{U}_h = \emptyset$ then $\widetilde{W}_{\ell, \mathcal{S} \setminus \{\ell\}}^h$ is empty and therefore has zero

length. The coded multicast message to helper h is obtained as follows

$$X_S^h = \bigoplus_{\ell \in \mathcal{S}} \widetilde{W}_{\ell, \mathcal{S} \setminus \{\ell\}}^h. \quad (4.15)$$

Since the sets $\mathcal{P}_\ell \cap \mathcal{U}_h$ may have different sizes, the concatenated segments $\widetilde{W}_{\ell, \mathcal{S} \setminus \{\ell\}}^h$ may have different lengths. Then, zero-padding is used in (4.15) such that X_S^h has length

$$|X_S^h| = \max_{\ell \in \mathcal{S}} |\widetilde{W}_{\ell, \mathcal{S} \setminus \{\ell\}}^h| = \max_{\ell \in \mathcal{S}} \sum_{k \in \mathcal{P}_\ell \cap \mathcal{U}_h} |W_{d_k, \mathcal{S} \setminus \{\ell\}}^h|. \quad (4.16)$$

For each $\mathcal{S} \in \Omega_{t'+1}^L$, helper h forwards to user $k \in \mathcal{U}_h$ and $\mathcal{S} \ni \ell_k$ just the useful portion of X_S^h , of length $|W_{d_k, \mathcal{S} \setminus \{\ell_k\}}^h|$. In any case, the bits of $W_{d_k, \mathcal{S} \setminus \{\ell_k\}}^h$ can be cached out from this portion since all other interfering bits come from subfiles present in cache $Z_k = \widetilde{Z}_{\ell_k}$.

Consistently with the definitions introduced before and using (4.16), we have

$$T_{\text{front}} = \max_{h \in [H]} \frac{F}{C_{\text{front}}(t')} \sum_{\mathcal{S} \in \Omega_{t'+1}^L} \max_{\ell \in \mathcal{S}} \sum_{k \in \mathcal{P}_\ell \cap \mathcal{U}_h} y_{k, \mathcal{S} \setminus \{\ell\}}^h \quad (4.17)$$

$$T_{\text{access}} = \max_{h \in [H]} \max_{k \in \mathcal{U}_h} \frac{F}{C_{h \rightarrow k}(t')} \sum_{\mathcal{S} \ni \ell_k} y_{k, \mathcal{S} \setminus \{\ell_k\}}^h \quad (4.18)$$

The resulting routing optimization problem is given by

$$\underset{(y_{k, \mathcal{S} \setminus \{\ell_k\}}^h, C_{h \rightarrow k} \geq 0): \mathcal{S} \in \Omega_{t'+1}^L, h \in [H], k \in [K])}{\text{minimize}} \quad \max\{T_{\text{front}}, T_{\text{access}}\} \quad (4.19a)$$

$$\text{subject to: } \sum_{h \in \mathcal{H}_k} y_{k, \mathcal{S} \setminus \{\ell_k\}}^h = 1, \quad \forall k \in [K], \forall \mathcal{S} \ni \ell_k \quad (4.19b)$$

$$\sum_{k \in \mathcal{U}_h} C_{h \rightarrow k} \leq C_{\text{access}}, \quad \forall h \in [H]. \quad (4.19c)$$

The problem reduces to a sequence of LPs in the same way seen for problem (4.11) (details are omitted for the sake of brevity). Different from the delivery scheme in Section 4.2.3, where we use random linear network coding to encode subfiles, here this is not needed since the scheme is able to deliver requested subfiles in sequence of segments of original subfiles, avoiding any overlap. The number of variables in problem (4.19) is at most $KH \left(\binom{L-1}{t'} + 1 \right)$ and the number of constraints at most $K \binom{L-1}{t'} + H$. Therefore, also this problem has linear complexity in K .

4.3. Networks with Broadcast Constraints and Collision Interference

While in Section 4.2 and 4.2.5 we assumed a model where transmission resources are already negotiated according to some PHY/MAC protocol, such that the network layer “sees” the access network as a set of logical orthogonal links, in this section we consider a model which is one step closer to an actual physical wireless network, capturing the broadcast nature of the wireless medium and interference in the form of *collisions*.

4.3.1. System Model

Consider again the 2-dimensional plane geometry qualitatively illustrated in Fig. 4.1 and assume spatially distributed helpers and users. We refer to the helpers that actually transmit as the “active helpers” in a given time slot. The set of active helpers can be scheduled over different time slots according to some transmission strategy which is part of the system optimization studied in this section. Since the radio channel is a broadcast medium, when a helper is active, its transmission is received at all users within a certain radius a_{interf} . Furthermore, we assume that users within a smaller radius $a_{\text{cell}} \leq a_{\text{interf}}$ can successfully decode the helper message unless they are not interfered by some other (active) helper. The decodability condition over the access network is formally expressed as follows: if user k is located at distance not larger than a_{cell} from active helper h , and there is no other active helper $h' \neq h$ within distance a_{interf} from user k , then user k can decode the message of helper h .⁵ An example of the network model considered in this section and the associated graph involving both interference conflicts and broadcast constraints is given in Fig. 4.3. Let $\Theta = \{\theta_h\} \subset \mathbb{R}^2$ and $\Phi = \{\phi_k\} \subset \mathbb{R}^2$ denote the set of helpers and users positions on the coverage area (a region in the 2-dimensional plane $\mathbb{R}^2$), respectively. In order for the system to be feasible, it is necessary that any user location ϕ_k is covered by at least one disk of radius a_{cell} centered around a helper position $\theta_h \in \Theta$, i.e., letting $\mathcal{B}(x, \rho)$ the disk centered at x of radius ρ , a necessary condition for feasibility is that

$$\phi_k \in \bigcup_{\theta_h \in \Theta_H} \mathcal{B}(\theta_h, a_{\text{cell}}), \quad \forall \phi_k \in \Phi. \quad (4.20)$$

Since here we are not concerned with issues such as coverage probability or outage probability (widely studied in stochastic geometry [20]), here we make the assumption that this condition is satisfied. This corresponds to the fact that, realistically, the network layer takes into consideration only the users that are actually associated to at least one

⁵This model has been widely used in the wireless networks literature and it is commonly referred as the *protocol model* (e.g., see [17]).

(a) Layout geometry with broadcast transmission from the helpers and collision interference at the users.

(b) Corresponding network graph with broadcast and interference constraints and A reuse scheme with $r = 3$ colors eliminating the interference conflicts.

Figure 4.3.: An example of the network topology considered in Section 4.2.1 with $H = 4$ and $K = 6$. In the graph the helpers and the users are enumerated in increasing order from left to right. The dashed edges in the graph represent interference conflicts.

helper and can thus receive data. As in the model of Section 4.2, we consider individual orthogonal fronthaul links of capacity C_{front} connecting the server to the helpers, and let the downlink multicast rate of transmission from the (active) helpers be equal to C_{access} . For simplicity, we use the same symbol C_{access} for the helpers downlink sum/multicast capacity. For the network model defined above, we consider a caching/delivery scheme where the prefetching is identical to the decentralized cache replication scheme of Section 4.2.5 with L caching groups, and use the same notation $t' = ML/N$ (integer value in $[L]$) and caching groups $\mathcal{P}_1, \dots, \mathcal{P}_L$ introduced in Section 4.2.5. The proposed delivery schemes for the centrally computed coded caching multicast messages is discussed in the following subsections.

4.3.2. Reuse with per Cell Multiround Delivery

A reuse scheme of order r consists of a coloring of the helpers with r colors, such that helpers with the same color are associated to the same subband or time slot, and helpers with different colors corresponds to orthogonal subbands or time slots. In particular, two helpers h, h' such that $\mathcal{B}(\theta_h, a_{\text{cell}}) \cap \mathcal{B}(\theta_{h'}, a_{\text{interf}}) = \emptyset$ can be associated to the same color and will never cause interference conflicts, since the users that can receive from h are not interfered by h' and vice versa. However, this is just a sufficient condition. More in general, for a given helper and user placements Θ and Φ there exist a minimum $r \in [H]$ for which there exists a reuse scheme of order r such that the network graph has no conflict edges. The delivery strategy proposed in this section consists of two sub-problems: 1) for given Θ, Φ find a reuse scheme of order r with r as small as possible avoiding all conflict edges; 2) for the given reuse scheme, associate users to helpers such as the system is feasible and the worst-case delivery time is minimized.

We define an undirected conflict graph $G = (V, E)$, with V and E denoting vertex and edge sets, respectively, where vertices $V = [H]$ correspond to helpers and E contains edges (i, j) , for all $i, j \in V$, such that there is a user at distance $\leq a_{\text{interf}}$ from both helpers i and j . The classical integer linear programming model for vertex coloring problem is defined as follows: define the binary 0 – 1 variables $y_c : c \in [H]$ and $x_{i,c} : (i, c) \in [H] \times [H]$, with $y_c = 1$ if color c is used in the reuse assignment and $x_{i,c} = 1$ if vertex i is assigned color c . Then, the minimization of the reuse order can be written as:

$$\text{minimize } \sum_{c=1}^H y_c \tag{4.21a}$$

$$\text{subject to: } \sum_{c=1}^H x_{i,c} = 1, \forall i \in V \tag{4.21b}$$

$$x_{i,c} + x_{j,c} \leq y_c, \quad \forall (i, j) \in E, \forall c \in [H] \quad (4.21c)$$

$$x_{i,c} \in \{0, 1\}, \quad \forall i \in V, \forall c \in [H] \quad (4.21d)$$

$$y_c \in \{0, 1\}, \quad \forall c \in [H]. \quad (4.21e)$$

It turns out that the minimum r (solution of (5.2)) is the chromatic number of the graph $G(V, E)$, and problem (5.2) is known to be NP-hard for general graphs G . Several important heuristic approaches have been proposed to solve the vertex graph coloring problem. One of the best known algorithms is DSATUR in [8]. That has been shown to provide the optimal solution for bipartite graphs with running time of $O(|V|^2)$. The pseudo-code of the algorithm can be found in [34, Fig. 2.8].

After solving graph coloring subproblem, then we address the user-helper association problem. Assume that a reuse scheme of order r has been found. In general, on the colored graph we need to find the optimal user-helper association that minimizes the worst-case delivery time. For a given association, the delivery at each helper achieved by the multiround delivery scheme in Section 4.2.5. Let $\mathcal{P}_\ell^h$ denote the set of users in caching group ℓ associated to helper h . The multiround delivery load of helper h , denoted by R_h , is given by expression (4.14) with occupancy numbers $|\mathcal{P}_{[1]}^h| \geq |\mathcal{P}_{[2]}^h| \geq \dots \geq |\mathcal{P}_{[L]}^h|$. The corresponding delivery time over the fronthaul link is simply given by $R_h F / C_{\text{front}}$ while the delivery time over the access (broadcast) downlink is given by $r R_h F / C_{\text{access}}$, where the factor r comes from the fact that with reuse of order r , the access channel is used only for a fraction $1/r$ of the total access transmission resource. It follows that the worst-case delivery time for the reuse scheme with given user-helper association is given by

$$T^{\text{reuse}} = \max \left\{ \frac{F}{C_{\text{front}}}, \frac{rF}{C_{\text{access}}} \right\} \times \max_{h \in [H]} \{R_h\}. \quad (4.22)$$

In order to minimize T^{reuse} , define the binary variables $x_{h,k}$ such that $x_{h,k} = 1$ if user k is associated to helper h and $x_{h,k} = 0$ otherwise. Denoting by E the set of solid colored edges in the colored graph, we have that $x_{h,k} = 0$ for all h, k for which there is no edge in E . The cardinality of the caching group $\mathcal{P}_\ell^h$ for a given association $\{x_{h,k}\}$ is given by

$$|\mathcal{P}_\ell^h| = \sum_{k: (h,k) \in E, k \in \mathcal{P}_\ell} x_{h,k}. \quad (4.23)$$

For given non-negative integers $A_1, \dots, A_L$, let the $[\cdot]$ subscript notation denote the sorting permutation such that $A_{[1]} \geq A_{[2]} \geq \dots \geq A_{[L]}$ and define the quantity

$$R_{\text{multi}}(A_1, \dots, A_L) = \sum_{\ell \in [L-t']} \frac{A_{[\ell]} \binom{L-\ell}{t'}}{\binom{L}{t'}}. \quad (4.24)$$

Hence, taking (4.23) into (4.14) and using the definition in (4.24) we arrive at the following optimal user-helper association problem

$$\underset{\{x_{h,k} \in \{0,1\}\}}{\text{minimize}} \quad \alpha \quad (4.25a)$$

$$\text{subject to: } R_{\text{multi}}(A_1^h, \dots, A_L^h) \leq \alpha, \quad \forall h \in [H], \quad (4.25b)$$

$$A_\ell^h \geq \sum_{k:(h,k) \in E, k \in \mathcal{P}_\ell} x_{h,k}, \quad \forall h \in [H], \quad \ell \in [L], \quad (4.25c)$$

$$\sum_{h:(h,k) \in E} x_{h,k} \leq 1, \quad (4.25d)$$

$$x_{h,k} \in \{0, 1\}, \quad (4.25e)$$

$$A_\ell^h \in \mathbb{R}_+. \quad (4.25f)$$

Since the function $R_{\text{multi}}(A_1^h, \dots, A_L^h)$ there is defined through a sorting permutation, the optimization problem (4.25) is non-linear. A way out of this problem can be found by noticing that the coefficients $\frac{\binom{L-\ell}{t'}}{\binom{L}{t'}}$ appearing in (4.24) are decreasing with ℓ , it follows that for a given set of occupancy numbers $A_1, \dots, A_L$, the permutation that sorts them in non-increasing order yields the maximum of the quantities

$$\sum_{\ell \in [L-t']} \frac{A_{\pi_\ell} \binom{L-\ell}{t'}}{\binom{L}{t'}} \quad (4.26)$$

over any permutation π . Hence, problem (24) can be linearized by replacing each constraint (4.25b) by the set of $L!$ constraints

$$\sum_{\ell \in [L-t']} \frac{A_{\pi_\ell}^h \binom{L-\ell}{t'}}{\binom{L}{t'}} \leq \alpha, \quad \forall \pi \in \Pi_L, \quad (4.27)$$

where Π_L denotes the set of all permutations of order L , where only one constraint (corresponding to the sorting permutation [.]) actually bites.

Greedy User Association Algorithm The drawback of the exact optimization user association method is that it generates $H \times L!$ constraints while in fact we need only H of such constraints since all the others are redundant. In order to reduce the complexity, we propose a greedy approach where the complexity order of our greedy algorithms is upper bounded by $L \log(L) \times K$. We define the set of helpers who can transmit message to user k as $\mathcal{H}_k = \{h : \phi_k \in \mathcal{B}(\theta_h, a_{\text{cell}})\}$. The proposed greedy user-helper association works as follows: i) Initialize the groups $\mathcal{P}_\ell^h$ by including the users that have unique assignment,

i.e., for which $|\mathcal{H}_k| = 1$; ii) For all users k for which $|\mathcal{H}_k| > 1$, associate them one by one, by selecting at each time the assignment that yields the minimum increase in the total objective function $\max_{h \in [H]} R_h$.

Example 2. Consider a network with $H = 4$ cells and $K = 6$ as shown in Fig. 4.3 and assume $L = 3$ cache configurations with $t' = 1$

$$\mathcal{P}_1 = \{1, 2, 5\}, \mathcal{P}_2 = \{3, 6\}, \mathcal{P}_3 = \{4\}.$$

A reuse scheme with $r = 3$ eliminating the interference conflicts is given in Fig. 4.3 (b). Helpers 1 and 4 are assigned to frequency band 1, while helpers 2 and 3 are assigned to frequency band 2 and 3, respectively. In the resulting colored graph, some users may be served by different helpers. Notice that the multiround delivery length in slots of duration $\frac{F}{C_{\text{access}}(t')}$ is given by (4.14). In the first step, user 1 is assigned to helper 1 and user 2 to helper 2 and user 5 helper 3. Since assigning user 3 to helper 2 or 3 will increase the number transmission slots equally, user 3 is randomly assigned to helper 2. By assigning user 4 to helper 3 the number of transmission slots of helper 3 will be increased to 3; on the other hand, assigning this user to helper 4 will increase the number of transmission slots of helper 4 to 2. Then the greedy algorithm assigns user 4 to helper 4. Finally user 6 can be assigned to either helper 2 or helper 4. By assigning the user to helper 2 the number of transmission slots of this helper will increase to 5 while assigning this user to helper 4 will increase the number transmission slot of helper 4 to 3. Therefore, the greedy algorithm assigns user 6 to helper 4. The resulting delivery time is

$$T^{\text{reuse}} = \frac{3F}{C_{\text{access}}} \times \frac{3}{3} = \frac{3F}{C_{\text{access}}}. \quad (4.28)$$

◇

4.3.3. Avalanche Scheduling Scheme

In this section we propose a routing and scheduling strategy that embraces collisions, and resolves them over multiple time slots, thus obtaining an overall better worst-case delivery time. The users are divided into two groups: non-interference and interference users. The non-interference users are those in the non-interference service area of the helpers given by the union over $h \in [H]$ of unique coverage regions $\mathcal{B}(\theta_h, a_{\text{cell}}) \setminus \cup_{h' \neq h} \mathcal{B}(\theta_{h'}, a_{\text{interf}})$. The second group contains users that are served by at least one helper and are receiving interference from neighboring helpers given by the union over $h \in [H]$ of coverage regions $\mathcal{B}(\theta_h, a_{\text{cell}}) \cap \cup_{h' \neq h} \mathcal{B}(\theta_{h'}, a_{\text{interf}})$. In reuse scheme all users within a cell are served with reuse factor $r > 1$, even non-interference users, while the helpers can serve these users

by all frequency resource without any collision. Our proposed avalanche scheme creates a platform where users can be served reuse factor 1. We let $\mathcal{P}_\ell^h$ denote the sets of non-interference users uniquely associated to helper h and belonging to caching group ℓ . At any point in time, the *delivery list* of helper h is the union $\mathcal{L}^h = \cup_{\ell \in [L]} \mathcal{P}_\ell^h$. The main difference between the scheme of this section, referred to as *avalanche* scheme, and the spatial reuse scheme in Section 4.3.2 is that in the avalanche scheme the sets $\mathcal{P}_\ell^h$ and therefore the delivery list of each helper is dynamically updated. The avalanche scheme starts by scheduling all the non-interference users simultaneously by running multiround delivery in parallel for all helpers. Since the multiround load depends on the occupancy numbers $\{|\mathcal{P}_{[\ell]}^h| : \ell \in [L]\}$ and these may differ over the helpers, at some point some helper h finishes its multiround delivery before the others. As soon as h finishes, it stops transmitting, so that some users that are interfered by h but can be served by some $h' \neq h$ become non-interference users and can be added to the delivery list of helper h' . Notice that some helper h may stop temporarily to transmit since its delivery list is empty, but may restart when some users in its service area $\mathcal{B}(\theta_h, a_{\text{cell}})$ that are interfered by some other helper become non-interference users when such helper stop its transmission. The process continues until all users are served. This algorithm is linear in number of edges in the bipartite graph represented in Fig. 4.3. For sparse graphs, as typically induced by the geometric coverage model considered here combined with some admission control protocol that limits the number of active users in each cell, the degree of each edge is upper bounded by some constant independent of H and K . Hence, the avalanche algorithm has linear complexity in the number of users K . Before giving the detailed description of the avalanche algorithm, we illustrate it through the following example.

Example 3. Consider again the network of Fig. 4.3 with $L = 3$ cache configurations and $t' = 1$ (same as in Example 2).

After decentralized caching, assume that the realization of the cache configurations is:

$$\mathcal{P}_1 = \{1, 2, 5\}, \mathcal{P}_2 = \{3, 6\}, \mathcal{P}_3 = \{4\}.$$

At the beginning, the only helper with non-empty delivery list is $h = 1$, with $\mathcal{P}_1^{(1)} = \{1\}$. All other sets are empty. Notice that the multiround delivery length in slots of duration $\frac{F}{C_{\text{access}}(L)} t'$ is given by [27, 48]

$$\Delta_h = \sum_{r \in [L-t']} |\mathcal{P}_{[r]}^h| \binom{L-r}{t'}, \quad (4.29)$$

where, we always assume (up to re-labeling of the caching groups) that at any point in time we have ordered occupancy numbers $|\mathcal{P}_{[1]}^h| \geq |\mathcal{P}_{[2]}^h| \geq \dots \geq |\mathcal{P}_{[L]}^h|$. Helper 1 finishes its delivery in $\binom{3-1}{1} = 2$ slots and stops transmission. In doing so, it frees from interference users 2 and 5. At this point the updated delivery lists contain $\mathcal{P}_{[1]}^{(2)} = \{2\}$ for helper 2, and $\mathcal{P}_{[1]}^{(3)} = \{5\}$ for helper 3. All other lists are empty. Helper 2 and 3 can serve users 2 and 5, respectively, in $\binom{3-1}{1} = 2$ time slots and stop transmission. At this point the delivery list of helper 4 contains $\mathcal{P}_{[2]}^{(4)} = \{6\}$ and $\mathcal{P}_{[3]}^{(4)} = \{4\}$. Users 4 and 6 belong to different caching groups and therefore can be served simultaneously by multicast coded messages. This requires $\binom{3-1}{1} + \binom{3-2}{1} = 3$ slots. Finally, user 3 can be served either by helper 2 or by helper 3, again in 2 times lots. Eventually, the total delivery time is given by

$$T^{\text{avalanche}} = \frac{F}{C_{\text{access}}} \times \frac{2 + 2 + 3 + 2}{\binom{3}{1}} = \frac{3F}{C_{\text{access}}}. \quad (4.30)$$

Notice that in this example the avalanche and the reuse scheme (see Example 2) achieve the same delivery time. $\diamond$

In order to give a general pseudo-code of the avalanche algorithm we need to introduce some notation. Consider the network bipartite graph G as in Fig. 4.3 (b). For a given subset of helpers $\mathcal{H}'$ and users $\mathcal{U}'$, let $G(\mathcal{H}', \mathcal{U}')$ denote the corresponding subgraph obtained by keeping only the edges $\{(h, k) : h \in \mathcal{H}', k \in \mathcal{U}'\}$. Let $\mathcal{E}_s(G)$ be the set of solid edges (i.e., carrying useful signal) and $\mathcal{E}_d(G)$ the set of dashed edges (i.e., carrying interference) in graph G . For a given assignment of the caching groups $\mathcal{P}_1, \dots, \mathcal{P}_L$, and a subset $\mathcal{A} \subset [H]$ of helpers, let re-define the symbol $\mathcal{P}_\ell^h$ to denote the set of users $k \in \mathcal{P}_\ell$ such that $\exists! (h, k) \in \mathcal{E}_s(G(\mathcal{A}, \mathcal{U}))$, where we use the unique existence symbol $\exists!$ to indicate that there is no other edge $(h', k) \in \mathcal{E}_s(G(\mathcal{A}, \mathcal{U})) \cup \mathcal{E}_d(G(\mathcal{A}, \mathcal{U}))$ in the graph. For what said before, defining the delivery list of helpers $h \in \mathcal{A}$ as $\mathcal{L}^h = \bigcup_{\ell=[L]} \mathcal{P}_\ell^h$, letting only the helpers in $\mathcal{A}$ to transmit (i.e., be *active*), it is clear that each helper in $h \in \mathcal{A}$ can serve by multiround delivery the users in $\mathcal{L}^h$ without interference from other helpers. Notice that in the avalanche delivery every XOR packet has size (in bits) $F/\binom{L}{t'}$ and since the helpers broadcast these packets on the access downlink, and must receive them from their fronthaul link, the transmission duration of a packet is given by $T_{\text{slot}} = \frac{F}{\binom{L}{t'} \min\{C_{\text{access}}, C_{\text{front}}\}}$. For a given active helper set $\mathcal{A}$ with delivery lists $\{\mathcal{L}^h\}$, we define the delivery epochs as the integer multiples of T_{slot} at which each column of the delivery array $\mathbf{B}^h$ induced by $\mathcal{L}^h$ is finished. Explicitly, these are given by

$$\Delta_{h, j_h} = \sum_{i=1}^{j_h} \left(\binom{L}{t' + 1} - \binom{L - |\mathcal{R}_{j_h}^h|}{t' + 1} \right), \quad (4.31)$$

for $j_h = |P_{[1]}^h|$ for each $h \in [H]$, representing the index of the last column in the delivery array of helper h and as defined before, $L - |\mathcal{R}_{j_h}^h|$ denotes the number of zeros in column j_h of $\mathbf{B}^h$. Notice that, given the cache group assignment $\mathcal{P}_1, \dots, \mathcal{P}_L$ and the residual graph $G(\mathcal{A}, \mathcal{U})$, the delivery lists $\mathcal{L}^h$ and arrays $\mathbf{B}^h$ therefore the sequence of delivery epochs $\{\Delta_{h,j_h}\}$ are uniquely determined. Then, the avalanche algorithm works as follows:

Initialization: Let $\mathcal{U}_{\text{unserved}} = [K]$, $D = 0$, and $\mathcal{A}$ be a maximal set of helpers with non-empty delivery lists in $G(\mathcal{A}, \mathcal{U}_{\text{unserved}})$ (e.g., this can be easily found in a greedy fashion).

1. **Find the set of helpers finishing the current served array column:** $\mathcal{F} = \{h \in \mathcal{A} : \Delta_{h,j_h} - D > 0 \text{ is minimal}\}$, and let $\Delta_{\min} = \min\{h \in \mathcal{A} : \Delta_{h,j_h} - D\}$ such minimal “next epoch” value.
2. **Increment time:** $D \leftarrow D + \Delta_{\min}$ (at this point, all helpers in $\mathcal{F}$ have finished delivery to the users in the j_h -th column of their delivery array, denoted collectively as $\partial\mathcal{U} = \{\mathbf{B}_{:,j_h}^h : h \in \mathcal{F}\}$).
3. **Update unserved users:** $\mathcal{U}_{\text{unserved}} \leftarrow \mathcal{U}_{\text{unserved}} \setminus \partial\mathcal{U}$.
4. If $\mathcal{U}_{\text{unserved}} = \emptyset$, exit.
5. **Identify stopping helpers:** for all $h \in \mathcal{A}$ such that $\mathcal{L}^h = \emptyset$, $\mathcal{A} \leftarrow \mathcal{A} \setminus \{h\}$.
6. **Update delivery arrays of active helpers:** for all $k \in \mathcal{U}_{\text{unserved}}$ such that $\exists! (h, k) \in \mathcal{E}_s(G(\mathcal{A}, \mathcal{U}_{\text{unserved}}))$, add k to $\mathcal{L}^h$ in the “next available column” of $\mathbf{B}^h$ and Update j_h for each $h \in \mathcal{A}$.
7. **Reactivate helpers:** for all $h \in [H] \setminus \mathcal{A}$ such that $\exists! (h, k) \in \mathcal{E}_s(G(\mathcal{A}, \mathcal{U}_{\text{unserved}}))$ for some k , add these users k in $\mathcal{L}^h$ and increase $\mathcal{A} \leftarrow \mathcal{A} \cup \{h\}$.
8. Go back to 1.

The “next available column” of $\mathbf{B}^h$ is the column j_h of still completely unserved users, and for which the ℓ -th group is empty (i.e., it has a zero). Notice that it may be necessary to adjoin a new column to the right of the current array $\mathbf{B}^h$, i.e., the delivery arrays in general keep growing to the right, until there are no more users to add. Notice also that at each update of the delivery arrays, all future epochs successive to the current time D must be updated accordingly, adding up future delivery intervals as in (4.31). As said before, these are deterministic functions of $\{\mathbf{B}^h\}$ and therefore such updates are trivial. Under the condition that all users are at least one helper at distance a_{cell} , the algorithm terminates with probability 1 and the resulting delivery time is $T_{\text{avalanche}} = D \times T_{\text{slot}}$.

Note. It is possible to implement LP program for collision model but it has very high complexity and it is not possible to run for network size given in the next section. The formulation of LP for collision model is given in Appendix. B.1

4.4. Results and Discussions

In this section we present some numerical results illustrating interesting features of the schemes proposed for the topological and the broadcast/collision network models defined in Section 4.2.1 and 4.3.1, respectively. For the topological network, given the helper placement Θ and user placement Φ in the plane, we associate user k in position ϕ_k to all helpers h such that $\phi_k \in \mathcal{B}(\theta_h, a_{\text{sig}})$, for some signaling radius a_{sig} . As said before, we are not concerned with coverage probability and only the users associated at least with one helper are considered, otherwise the delivery would be infeasible. For the broadcast/-collision model, we produce the signal/interference graph by defining the radius a_{cell} and a_{interf} as described in Section 4.3.1. For the same placements Θ and Φ the two models are related. In particular, driven by practical considerations, we let $a_{\text{cell}} \leq a_{\text{sig}} \leq a_{\text{interf}}$. In addition, we let C_{access} be equal in both cases, such that the sum rate of the (orthogonal) links outgoing from each helper in the topological model is equal to the broadcast downlink capacity of the helpers in the interference model.

We consider the following parameters throughout the simulations: in the topological model $a_{\text{sig}} = 220\text{m}$, while in the broadcast/collision model $a_{\text{cell}} = 200\text{m}$ and $a_{\text{interf}}/a_{\text{cell}} = 1.2$. The placements Θ and Φ are generated according to independent homogeneous *Poisson Point Processes* (PPP) with densities $\lambda_h = 7$ helpers per km^2 and $\lambda_u = 20 \times 7$ users per km^2 , within a circle of area $A = \pi R^2$ with radius $R = 1\text{km}$. This results in an average $H = 20$ helpers and $K = 400$ users in the whole area. By fixing an integer $L < K$ and generating L cache configurations as described in Section 4.2.5, each user chooses one of the L configurations randomly and independently. Hence, the PPPs of users with the same cache configurations are independent thinnings (with thinning factor $1/L$) of the user placement PPP. The total delivery time is obtained by averaging over several realizations of the network and users cache configurations. Without loss of generality, we let $F = 1$ bit and $C_{\text{front}} = 1$ bit/s. Therefore, our “normalized” results are easily translated in actual bit/s by choosing the ratio F/C_{front} .

Fig. 4.4 compares the performance of the multi-round delivery strategy (Section 4.2.5) and the newly proposed LP-optimized strategy (Section 4.2.5) for the topological model. We note that as the ratio $C_{\text{access}}/C_{\text{front}}$ increases, the worst-case delivery time of both schemes decreases but this improvement is limited (for example, going from $C_{\text{access}}/C_{\text{front}} = 1$ to $C_{\text{access}}/C_{\text{front}} = 2$ the improvement is significant, but the improvement from going

Figure 4.4.: Delivery time versus cache replication factor with $\mu = 0.2$ and $L = [5, 10, 15, 20]$.

$C_{\text{access}}/C_{\text{front}} = 2$ to $C_{\text{access}}/C_{\text{front}} = 5$ is essentially negligible. This indicates the fact that for $C_{\text{access}}/C_{\text{front}} = 1$ the system bottleneck is the access segment, but for $C_{\text{access}}/C_{\text{front}} \geq 2$ the system bottleneck is the fronthaul segment. Since the most interesting conclusions for the routing/scheduling algorithms are obtained when the system bottleneck is the access segment, in the next results we considered $C_{\text{access}}/C_{\text{front}} = 1$.⁶ Another interesting consideration is that while multiround delivery seems to be sensitive to the choice of L , the new LP optimized routing is very insensitive and reaches its minimum delivery time already for L as small as $L = 5$. Since the subpacketization order depends (exponentially) on L , this makes the new scheme very attractive since it can afford a very small value of L with almost no degradation in performance. Overall, we notice that the new LP-based scheme significantly outperforms the multiround delivery, although this was proved to be optimal in the case of a single helper (or, in our case, when each user can be served only by a single helper, such that the network graph becomes a tree).

For the broadcast/collision model, Fig. 4.5 compares the performance for different user-helper association schemes for the reuse scheme of Section 4.3.2. The helper coloring is obtained by both solving the optimization problem in (5.2) and with the DSatur algorithm. As a matter of fact, even though the coloring optimization is NP-hard, for the network topologies considered here the problem can be easily solved by standard integer programming solvers for up to $H = 1000$ helpers. Furthermore, due to the sparse nature of the underlying graph, DSatur essentially provides optimal results. Hence, optimal or quasi-optimal coloring is really not a significant problem in most practical scenarios. After coloring, we consider user association according to the following three methods: i) the relaxed LP user association in (4.25); ii) the greedy user association as described in Section

⁶Of course, this is a qualitative consideration and for different network parameters the transition between these two bottleneck regimes may appear at different ratio values.

Figure 4.5.: Delivery time versus cache replication factor with $\mu = 0.5$, $L = [2, 4, 6, 8]$ and $C_{\text{access}}/C_{\text{front}} = 1$

4.3.2; iii) a random user association, in which users are randomly assigned to one of the helpers at distance a_{cell} . The greedy scheme offers a significant improvement of the delivery time compared to the random association and has much lower computational complexity than solving the exact optimization in (5.2).

Fig. 4.6 shows a performance comparison between the reuse scheme and the avalanche scheme for the broadcast/collision model with different parameters. The avalanche scheme is competitive since it exploits the multicast nature of the coded caching messages together with the network geometry. In addition, the avalanche scheme is also very insensitive to the choice of L , such that we can choose L as low as 5 and yet achieve nearly the best performance. This has an important impact on the subpacketization order.

Fig. 4.6 also shows the comparison between the broadcast/collision model and the topological model for the same value of C_{access} , i.e., the sum of the capacities of the links outgoing from each helper in the topological model is equal to the helpers broadcast downlink rate of the broadcast/collision model. We notice that the broadcast/collision model with avalanche delivery outperforms the topological model with LP-optimized delivery. This may be explained by the fact that in the topological model each helper-user link is individual, such that the transmissions from helpers their served users is unicast. In contrast, the broadcast nature of the helpers transmissions in the broadcast/collision model is better batched to the multicast nature of the coded caching messages. Evidently, the gain obtained by leveraging the broadcast nature of the downlink transmissions is enough to counter the loss due to collision interference.

Figure 4.6.: Delivery time versus cache replication factor with $\mu = 0.2$, $L = [5, 10, 15, 20]$ and $C_{\text{access}}/C_{\text{front}} = 1$.

4.5. Conclusion

In this chapter we investigated two variants of a general “network-layer model” formed by one server, several helper stations (APs/BSs) and several users, namely, a topological non-interference network with bounded sum capacity of outgoing links and a network with broadcast transmission from the helpers and collision model for interference. For the first model, we proposed a novel routing optimization scheme that outperform the direct extension of the so-called multiround delivery at each helper. The complexity of the novel method is linear in the the number of users. For the second model, we proposed a baseline scheme based on time/frequency reuse and user-helper assignment, and a new scheme nicknamed “avalanche” that is very reminiscent of CSMA-based random access. Our novel schemes have worst-case delivery that is very insensitive to the number of distinct cache configurations L . This has important consequences for the subpacketization order, since a small value of L (yielding small subpacketization) can be chosen with minimal system performance degradation. Overall, our work essentially solves most of the problems outlined by previous literature as “key issues” for the application of coded caching in realistic scenarios. In particular, our schemes address i) asynchronous user streaming sessions (by breaking large files in small blocks and using a low subpacketization order with minimal performance degradation and a completely decentralized prefetching); ii) scalability to large cellular-type networks with many users and helpers; iii) the HTTP end-to-end encrypted requests, since the helpers are completely oblivious of the user requests and content files.

5. Conclusion and Future work

In this dissertation, we focus on the coded caching scheme introduced by Maddah-Ali and Niesen. This scheme was originally proposed for an idealized single bottleneck network, where a server is connected to K users through a shared error-free link of given capacity. This work addressed the practical aspects of coded caching in a class of two-hop spatially distributed wireless networks consisting of one server connected via fronthaul links to a layer of H helper nodes (access points/base stations), which in turn communicate via a wireless access network to K users, each equipped with its own cache. We investigated the coded caching design challenges in the physical, multiple access and network layers by leveraging the network topology. The main contribution is the improvement of efficiency of delivery of the MAN type multicast messages through helper nodes to the users. This dissertation also addressed one of the key drawbacks of the MAN scheme - namely the exponentially growing complexity.

Chapter 2 considered a SIMO system, where the users are equipped with n_r antennas. Building upon the coded multicast message for a group of users, the message is further encoded by (L, H) MDS code, which allows the MDS-coded blocks to be sent to multiple spatially distributed single-antenna helpers, transmitting at a fixed rate with no channel state information. Users applied the ZF receiver to decode the best L (micro diversity order) helper transmissions in a decentralized manner. In the path loss scenario the best L transmissions of helpers are also the nearest ones. By leveraging stochastic geometry we derived the analytical expression for the average ergodic rate and outage probability with respect to the network topology. The receiver performance is improved by applying SIC, where the optimal decoding order of SIC is according to the helper-user distance. The analysis showed that the micro diversity order L should be set as approximately equal to half of the number of antennas at the user's side.

Chapter 3 built upon 2 by extending to the video delivery scheme with two quality options. The video files are initially encoded by SVC into two layers of source-encoded bits, such that layer one provides a low quality version of the files, while layer two enhances it to a high quality version. Similar to the previous chapter, the users applied ZF to decode the helper transmissions. Each user is able to reconstruct the entire codeword message if it can decode at least L_1 messages from distinct helpers. Depending on its location with

respect to the helpers, a user may decode at least $L_2 > L_1$ messages; therefore, it could be able to decode the enhancement layer as well. This led to a scalable video delivery scheme, which takes advantage of superposition coding in order to impose the message of two layers with a much lower delivery time compared to the conventional scheme.

Finally in chapter 4, two variant network models are considered, which differ in the modeling of access links. Both models should be regarded as *abstractions* at the “network layer” for physical scenarios such as local area networks and cellular networks, which are spatially distributed over a certain coverage area. The key focus of this approach consists of routing MAN-type multicast messages through the network and formulating the optimal routing scheme as an optimization problem that can be solved exactly or for which we give powerful heuristic algorithms. The proposed scheme reduced the complexity of the coded caching scheme from being exponentially growing with the number of users to being linear.

5.1. Future Work

In conclusion, the results presented in this dissertation reveal numerous research directions. First, it would be interesting to go beyond the collision model presented in Chapter 4 and consider a more realistic model involving pathloss, shadowing and fading. One could consider the Line of Sight model (LoS) described in ITU-1411 [58]. If the helper antenna height is denoted by h_b , the user antenna height is denoted by h_m and the transmission wavelength is denoted by λ , then the transmission loss (in dB) at distance d is taken to be equal to

$$L = L_{bp} + 6 + \begin{cases} 20 \log_{10} \left(\frac{d}{R_{bp}} \right) & \text{if } d \leq R_{bp} \\ 40 \log_{10} \left(\frac{d}{R_{bp}} \right) & \text{if } d > R_{bp} \end{cases},$$

where $R_{bp} = \frac{4h_b h_m}{\lambda}$ denotes the breakpoint distance and $L_{bp} = \left| 20 \log_{10} \left(\frac{\lambda^2}{8\pi h_b h_m} \right) \right|$ denotes the basic transmission loss at the break point. One can think about generalizing the result of the Treating Interference as Noise (TIN) scheme to the multicast coded caching scheme in two-hop wireless networks. More specifically, the result in [13] shows that this scheme can achieve capacity within a constant gap. In a K -user interference channel, where the channel strength level from transmitter i to receiver j is equal to SNR_{ji} , $\forall i, j \in [K]$, if the following condition is satisfied

$$\text{SNR}_{ii} \geq \max_{j \neq i} \text{SNR}_{ji} \cdot \max_{i \neq k} \text{SNR}_{ik}, \quad (5.1)$$

then with power control, TIN is optimal. It is not possible to hold this condition for all users and helpers in our network model. The concept of *information-theoretic independent sets* (ITIS) introduced in [44], which indicates that the sets of links for simultaneous communication inside each of which, treating the interference from each other as noise is information-theoretically optimal. If the transmission set of users meets the TIN condition, then they will be scheduled together. A simple way to define ITIS is to use a greedy method to do an exhaustive search within all connections. The coded caching scheme groups L users together to create a multicast message. The interesting point is that this coded multicast message to the group of users can be scheduled within one ITIS set. The way to group users in the coded caching scheme which maximizes the cardinality of each ITIS is an interesting subproblem. The proposed greedy scheme can address these two concerns to find optimal ITIS sets. Hence, it would be worth figuring out the performance improvement that link scheduling with TIN condition [44] is able to guarantee in a coded caching two-hop setting. Third, it would be interesting to investigate the impact of more advanced power control with the results of these references in multicast scenario. For example, the geometric programming method introduced in [10] and have been implemented to D2D with TIN condition in [70]. There are several power allocation techniques to apply in the TIN problem. One of the well known approaches is the WMMSE algorithm [63] power control scheme.

Regardless of whether the TIN condition is applied or not, there are two problems that present themselves as possible directions for future work: 1) which transmissions should be scheduled together 2) the power control scheme.

Furthermore, an interesting future direction can be to address joint link scheduling and power control as a single optimisation problem. For example, recent results in [62] demonstrate that the original combinatorial problem of scheduling can be written in the form of fractional programming which can integrate the power control problem. In this method for each link i variable x_i is defined to be 1 if the link can be scheduled and 0 otherwise. The scheduling problem can be written as the weighted sum rate maximization with variables x_i . Unlike [44, 70] the scheduling optimization based on fractional programming does not require tuning of the design parameters. Consider a network with H helpers and K users, where $\mathcal{U}_i$ denotes the set of audience of multicast message from helper i . The scheduling problem can be formulated as the maximization of weighted sum-rate:

$$\text{maximize } \sum_{i \in [H]} w_i R_i(\mathbf{x}) \quad (5.2a)$$

$$\text{subject to } x_i \in \{0, 1\}, \forall i \in [H], \quad (5.2b)$$

$$R_i(\mathbf{x}) \leq \log(1 + z_i), \forall i \in [H], \quad (5.2c)$$

$$z_i \leq \frac{|h_{ki}|^2 p_i x_i}{\sum_{j \in [H], j \neq i} |h_{kj}|^2 p_j x_j + \sigma^2}, \forall k \in \mathcal{U}_i, \quad (5.2d)$$

where the weights w_i are chosen for priority or fairness, p_i is the transmission power of helper i , h_{ij} is the transmission loss from helper j to user i and σ^2 is noise power. By using the Lagrangian function, we could reformulate the original problem to

$$\underset{\mathbf{x}, \mathbf{z}}{\text{maximize}} \quad f_r(\mathbf{x}, \mathbf{z}) \quad (5.3a)$$

$$\text{subject to : } x_i \in \{0, 1\}, \forall i \quad (5.3b)$$

where the new objective function is

$$f_r(\mathbf{x}, \mathbf{z}) = \sum_{i \in [H]} w_i \log(1 + z_i) - \sum_{i \in [H]} w_i z_i + \sum_{i \in [H]} w_i (1 + z_i) \min_{k \in \mathcal{U}_i} \frac{|h_{ki}|^2 p_i x_i}{\sum_{j \in [H]} |h_{kj}|^2 p_j x_j + \sigma^2} \quad (5.4)$$

This optimization can be solved in an iterative fashion by using [62, preposition 1].

Many emerging technologies involve massive amounts of data collection, and collaborative intelligence that can process this data to make decision or predictions. The current trends focus on training a powerful learning algorithm, often a neural network, on a massive dataset and many specialized machine learning algorithms are being developed. The traditional scheduling method involves first estimating all the interfering channel strengths then optimizing the scheduling based on the model. This model-based method is however resource intensive and computationally hard. It is possible to schedule links efficiently based solely on the geographic locations of transmitters and receivers for networks in which the channels are largely functions of distance dependent path-losses. Deep Learning seems to be a well suited alternative to develop new network models that can be both accurate and simple to run. The authors in [53] (RouteNet), presented a novel network to understand the relationship between topology, delay and pathloss. Their scheme is able to generalize routing schemes over arbitrary topologies. Hence, an exciting line of research is to study practical and feasible coded caching schemes in a two-hop wireless network by using the results of graph learning like [53].

A. Stochastic Geometry

A.1. Proof of (2.19), (2.20)

The Laplace transform of $1/\tilde{\rho}_{k,\ell}$, for $s \in \mathbb{C}$, is given by

$$\mathcal{L}_{1/\tilde{\rho}_{k,\ell}}(s) = \mathbb{E} \left[e^{-s/\tilde{\rho}_{k,\ell}} \right] \quad (\text{A.1a})$$

$$= \int_0^\infty dv \int_0^v e^{-s \frac{u^\eta}{v^{\eta-2}} \frac{2\pi\lambda}{\eta-2}} f_{r_{k,\ell}, r_{k,L}}(u, v) du, \quad (\text{A.1b})$$

where $f_{r_{k,\ell}, r_{k,L}}(u, v)$ is given by (2.16) with the replacement $n \leftarrow L$. Evaluating the integral in (A.1b) separately for the two cases $\ell < L$ and $\ell = L$, we have

Case 1: For $\ell < L$

$$\mathcal{L}_{1/\tilde{\rho}_{k,\ell}}(s) = \int_0^\infty dv \int_0^v e^{-s \frac{u^\eta}{v^{\eta-2}} \frac{2\pi\lambda}{\eta-2}} f_{r_{k,\ell}, r_{k,L}}(u, v) du. \quad (\text{A.2})$$

The joint PDF of $f_{r_{k,\ell}, r_{k,L}}(u, v)$ is given by (2.16) with $n \leftarrow L$, $\ell \leftarrow \ell$. By replacing the expression for the joint PDF, we have

$$\begin{aligned} \mathcal{L}_{1/\tilde{\rho}_{k,\ell}}(s) = \int_0^\infty dv \int_0^v e^{-s \frac{u^\eta}{v^{\eta-2}} \frac{2\pi\lambda}{\eta-2}} & \frac{4(\pi\lambda)^L}{(L-\ell-1)!(\ell-1)!} \\ & \cdot (v^2 - u^2)^{L-\ell-1} v u^{2\ell-1} e^{-\pi\lambda v^2} du, \end{aligned} \quad (\text{A.3})$$

where after invoking the binomial expansion for $(v^2 - u^2)^{L-\ell-1}$, we obtain

$$\begin{aligned} \mathcal{L}_{1/\tilde{\rho}_{k,\ell}}(s) = \sum_{n=0}^{L-\ell-1} & \frac{4(\pi\lambda)^L}{(L-\ell-1)!(\ell-1)!} \binom{L-\ell-1}{n} (-1)^n \\ & \cdot \int_0^\infty v^{2(L-\ell-1-n)+1} e^{-\pi\lambda v^2} dv \\ & \cdot \int_0^v e^{-s \frac{2\pi\lambda}{\eta-2} \frac{u^\eta}{v^{\eta-2}}} u^{2\ell-1+2n} du. \end{aligned} \quad (\text{A.4})$$

First, we apply a change of variable $u^\eta \rightarrow x$ and then utilize [23, 3.351.1] to solve the inner integral. After simplification, we have

$$\begin{aligned} \mathcal{L}_{1/\tilde{\rho}_{k,\ell}}(s) &= \sum_{n=0}^{L-\ell-1} \frac{4(\pi\lambda)^L}{(L-\ell-1)!(\ell-1)!} \binom{L-\ell-1}{n} (-1)^n \\ &\quad \cdot \int_0^\infty v^{\nu+1} e^{-\pi\lambda v^2} \bar{\Gamma}\left(2\frac{n+\ell}{\eta}, s\alpha_1 v^2\right) dv, \end{aligned} \quad (\text{A.5})$$

where $\nu = 2((L-\ell-1-n) + (\eta-2)\frac{n+\ell}{\eta})$ and $\alpha_1 = \frac{2\pi\lambda}{\eta-2}$. Then, we invoke the change the variable $v^2 \rightarrow x$ once more and then utilize the identity [23, 6.455.2] to obtain following result

$$\begin{aligned} \mathcal{L}_{1/\tilde{\rho}_{k,\ell}}(s) &= \sum_{n=0}^{L-\ell-1} \frac{(-1)^n \Gamma(L)}{(L-\ell-1)!(\ell-1)!(n+\ell)} \binom{L-\ell-1}{n} \\ &\quad \cdot (1+\alpha_2 s)^{-L} {}_2F_1\left(1, L; \eta' + 1; \frac{\alpha_2 s}{1+\alpha_2 s}\right), \end{aligned} \quad (\text{A.6})$$

where $\alpha_2 = \frac{2}{\eta-2}$, $\eta' = 2\frac{n+\ell}{\eta}$. Finally, by using the formula [23, 9.131.1] the Laplace transform can be rewritten as in (2.19).

Case 2: For $\ell = L$

$$\mathcal{L}_{1/\tilde{\rho}_{k,L}}(s) = \int_0^\infty e^{-sv^2 \frac{2\pi\lambda}{\eta-2}} f_{r_{k,L}}(v) dv. \quad (\text{A.7})$$

The marginal PDF $f_{r_{k,L}}(v)$ is given by (2.15) with $n \leftarrow L$. After replacing the expression for the marginal PDF, we have

$$\mathcal{L}_{1/\tilde{\rho}_{k,L}}(s) = \int_0^\infty e^{-sv^2 \frac{2\pi\lambda}{\eta-2}} \frac{2(\pi\lambda)^L}{(L-1)!} v^{2L-1} e^{-\pi\lambda v^2} dv. \quad (\text{A.8})$$

To solve this integral first we apply the variable change $v^2 \rightarrow x$ and then use [23, 3.351.3], which gives (2.20).

A.2. Proof of (A.15) and (A.18)

Case 1: For $\ell < L$

$$\begin{aligned} F_{\widetilde{\text{SIR}}_{k,\ell}}(\gamma) &= \\ 1 - \int_0^\infty \int_0^v (1 - F_{\widetilde{\text{SIR}}_{k,\ell}}(\gamma|r_{k,\ell}, r_{k,L})) f_{r_{k,\ell}, r_{k,L}}(u, v) du dv. \end{aligned} \quad (\text{A.9})$$

By direct substitution of the expression (2.27) into (A.9), we have

$$F_{\widetilde{\text{SIR}}_{k,\ell}}(\gamma) = 1 - \int_0^\infty \int_0^v \frac{\Gamma(n_r - L + 1, \gamma \frac{2\pi\lambda}{\eta-2} \frac{u^\eta}{v^{\eta-2}})}{\Gamma(n_r - L + 1)} \cdot \frac{4(\pi\lambda)^L}{(L - \ell - 1)! (\ell - 1)!} (v^2 - u^2)^{L-\ell-1} v u^{2\ell-1} e^{-\pi\lambda v^2} du dv. \quad (\text{A.10})$$

Note that by using [23, 8.352.2] we can expand the incomplete gamma function and then we have

$$F_{\widetilde{\text{SIR}}_{k,\ell}}(\gamma) = 1 - \sum_{m=0}^{n_r-L} \frac{4(\pi\lambda)^L}{(L - \ell - 1)! (\ell - 1)! m!} \cdot \int_0^\infty \int_0^v \left(\gamma \frac{2\pi\lambda}{\eta-2} \frac{u^\eta}{v^{\eta-2}} \right)^m e^{-\gamma \frac{2\pi\lambda}{\eta-2} \frac{u^\eta}{v^{\eta-2}}} \cdot (v^2 - u^2)^{L-\ell-1} v u^{2\ell-1} e^{-\pi\lambda v^2} du dv. \quad (\text{A.11})$$

After expanding binomial, we have

$$F_{\widetilde{\text{SIR}}_{k,\ell}}(\gamma) = 1 - \sum_{n=0}^{L-\ell-1} \sum_{m=0}^{n_r-L} \frac{4(\pi\lambda)^L (-1)^n}{(L - \ell - 1)! (\ell - 1)! m!} \cdot \left(\gamma \frac{2\pi\lambda}{\eta-2} \right)^m \binom{L-\ell-1}{n} \int_0^\infty v^{-m(\eta-2)+2(L-\ell-1-n)+1} e^{-\pi\lambda v^2} \cdot \int_0^v e^{-\gamma \frac{2\pi\lambda}{\eta-2} \frac{u^\eta}{v^{\eta-2}}} u^{2n+2\ell-1+m\eta} du dv. \quad (\text{A.12})$$

To solve the inner integral first we change the variable $u^\eta \rightarrow x$ and then use [23, 3.351],

$$F_{\widetilde{\text{SIR}}_{k,\ell}}(\gamma) = 1 - \sum_{n=0}^{L-\ell-1} \sum_{m=0}^{n_r-L} \frac{4(\pi\lambda)^L (-1)^n}{(L - \ell - 1)! (\ell - 1)! m!} \cdot \binom{L-\ell-1}{n} \left(\gamma \frac{2\pi\lambda}{\eta-2} \right)^{-\eta'} \cdot \int_0^\infty v^{\nu+1} \bar{\Gamma}(\eta' + m, \gamma \alpha_1 v^2) e^{-\pi\lambda v^2} dv, \quad (\text{A.13})$$

where $\nu = (\eta - 2)\eta' + 2(L - \ell - 1 - n)$ and $\alpha_2 = \frac{2}{\eta-2}$, $\eta' = 2\frac{n+\ell}{\eta}$. In the next step to solve the remaining outer integral, first we change the variable $v^2 \rightarrow x$ and then use [23, 6.455.2] to obtain following result

$$F_{\widetilde{\text{SIR}}_{k,\ell}}(\gamma) = 1 - \sum_{n=0}^{L-\ell-1} \sum_{m=0}^{n_r-L} \frac{2(-1)^n \Gamma(m+L)}{(L - \ell - 1)! (\ell - 1)! m!}$$

$$\begin{aligned}
& \cdot \binom{L-\ell-1}{n} \frac{(\alpha_2 \gamma)^m}{\eta(\eta' + m)(\alpha_2 \gamma + 1)^{m+L}} \\
& \cdot {}_2F_1\left(1, L+m; \eta' + m + 1; \frac{\alpha_2 \gamma}{1 + \alpha_2 \gamma}\right), \tag{A.14}
\end{aligned}$$

where $\alpha_2 = \frac{2}{\eta-2}$. Finally, we use the formula [23, 9.131.1] to rewrite the preceding expression as (A.15).

$$\begin{aligned}
F_{\widetilde{\text{SIR}_{k,\ell}}}(\gamma) &= 1 - \sum_{m=0}^{n_r-L} \sum_{n=0}^{L-\ell-1} \frac{2(-1)^n}{m!(L-\ell-1)!(\ell-1)!} \\
& \cdot \frac{\Gamma(m+L)}{\eta(\eta' + m)} \binom{L-\ell-1}{n} \left(\frac{2\gamma}{\eta-2}\right)^m \\
& \cdot {}_2F_1\left(L+m, m+\eta'; m+\eta'+1; -\frac{2\gamma}{\eta-2}\right) \tag{A.15}
\end{aligned}$$

Case 2: For $\ell = L$

As previous case, the complement CDF of SIR can be written as follows

$$\begin{aligned}
F_{\widetilde{\text{SIR}_{k,L}}}(\gamma) &= 1 - \int_0^\infty \frac{\Gamma(n_r - L + 1, v^2 \gamma \frac{2\pi\lambda}{\eta-2})}{\Gamma(n_r - L + 1)} \frac{2(\pi\lambda)^L}{(L-1)!} \\
& \cdot v^{2L-1} e^{-\pi\lambda v^2} dv. \tag{A.16}
\end{aligned}$$

Note that by using [23, 8.352.2] we can expand the incomplete gamma function and then the preceding integral can be written as follows

$$\begin{aligned}
F_{\widetilde{\text{SIR}_{k,L}}}(\gamma) &= 1 - \sum_{m=0}^{n_r-L} \frac{2(\pi\lambda)^L}{(L-1)! m!} (\gamma\alpha_1)^m \\
& \cdot \int_0^\infty v^{2m+2L-1} e^{-(\pi\lambda + \alpha_1 \gamma)v^2} dv, \tag{A.17}
\end{aligned}$$

where $\alpha_1 = \frac{2\pi\lambda}{\eta-2}$. After solving the integral by using [23, 3.351.3] and simplify the result, the final expression can be written as (A.18).

$$F_{\widetilde{\text{SIR}_{k,\ell}}}(\gamma) = 1 - \sum_{m=0}^{n_r-L} \frac{(m+L-1)!}{m!(L-1)!} \frac{(\frac{2\gamma}{\eta-2})^m}{(\frac{2\gamma}{\eta-2} + 1)^{(m+L)}}. \tag{A.18}$$

A.3. Proof of (2.28) and (2.29)

The average rate can be computed by a integral which we provided in (2.26b).

Case 1: For $\ell < L$

$$\bar{C}_{k,\ell}^{\text{lb}} = \int_0^\infty 1 - F_{\widetilde{\text{SIR}}_{k,\ell}}(2^\gamma - 1) d\gamma \quad (\text{A.19})$$

By substituting the complement CDF of SIR from (A.15) into the preceding expression, we have

$$\begin{aligned} \bar{C}_{k,\ell}^{\text{lb}} &= \sum_{m=0}^{n_r-L} \sum_{n=0}^{L-\ell-1} \frac{2(-1)^n}{m!(L-\ell-1)!(\ell-1)!\eta(\eta'+m)} \frac{\Gamma(m+L)}{\eta(\eta'+m)} \\ &\quad \cdot \binom{L-\ell-1}{n} \int_0^\infty (\alpha_2(2^\gamma - 1))^m \\ &\quad \cdot {}_2F_1(L+m, m+\eta'; m+\eta'+1; -(2^\gamma - 1)\alpha_2) d\gamma. \end{aligned} \quad (\text{A.20})$$

By changing $2^\gamma - 1 \rightarrow x$ and using of [23, 9.34.7], the hypergeometric function can be expressed in terms of the Meijer-G function as follows

$$\begin{aligned} \bar{C}_{k,\ell}^{\text{lb}} &= \sum_{m=0}^{n_r-L} \sum_{n=0}^{L-\ell-1} \frac{2(-1)^n}{m!(L-\ell-1)!(\ell-1)!\eta} \binom{L-\ell-1}{n} \\ &\quad \cdot \log_2(e) \int_0^\infty (\alpha_2 x)^{m+1} (x+1)^{-1} \\ &\quad \cdot G_{2,2}^{1,2} \left(\begin{matrix} -(m+L), -m-\eta' \\ -1, -(m+1+\eta') \end{matrix} \middle| \alpha_2 x \right) dx \end{aligned}$$

and the preceding integral has the explicit solution in [23, 7.811.5] and is provided the final expression in (2.28).

Case 2: For $\ell = L$

$$\bar{C}_{k,L}^{\text{lb}} = \int_0^\infty F_{\widetilde{\text{SIR}}_{k,L}}^c(2^\gamma - 1) d\gamma \quad (\text{A.21})$$

By changing varibale to $2^\gamma \rightarrow e^\gamma$, then the integral is rewritten as

$$\bar{C}_{k,L}^{\text{lb}} = \sum_{m=0}^{n_r-L} \frac{(m+L-1)! \log_2 e}{m!(L-1)! y^L} \int_0^\infty \frac{e^{-\gamma L} (1 - e^{-\gamma})^m}{(1 + \frac{1-y}{y} e^{-\gamma})^{m+L}} d\gamma. \quad (\text{A.22})$$

The integral can be solved by using of [23, 3.312.3]. The final expression for the integral is

$$\begin{aligned} \bar{C}_{k,L}^{\text{lb}} &= \sum_{m=0}^{n_r-L} \frac{(m+L-1)!}{m!(L-1)!} \log_2(e) \frac{\Gamma(L)\Gamma(m+1)}{\Gamma(m+L+1)} \\ &\quad \cdot {}_2F_1\left(1, L; m+L+1; 1 - \frac{2}{\eta-2}\right). \end{aligned} \quad (\text{A.23})$$

After simplification, the final expression for average rate for the last sub-stream will be derived and be given by (2.29).

A.4. Proof of Theorem 1

Consider the $L \times L$ matrix $\mathbf{T}$ with (i, j) elements $T_{i,j} = f_i(x_j)$, $i \in [L]$, $j \in [L]$. The elements $T_{i,j}$ form a partially ordered set. By construction, two elements $T_{i,j}$ and $T_{i,j'}$ on the same row i are ordered such that $T_{i,j} \geq T_{i,j'}$ for $j \leq j'$, and two elements $T_{i,j}$ and $T_{i',j}$ on the same column j are ordered such that $T_{i,j} \geq T_{i',j}$ for $i \geq i'$.

Consider the Manhattan topology induced by the squared integer grid of the matrix indices (similar to the moves of the Rook on a chess board). Any two elements in the array are connected by a path formed by a horizontal move followed by a vertical move. A horizontal move to the left decreases the column index. A vertical move down increases the row index. Hence, the above inequalities imply that if two elements $T_{i,j}$ and $T_{i',j'}$ are connected by a path formed by a left horizontal move followed by a down vertical move (we write $(i, j) \vdash (\leftarrow, \downarrow) \dashv (i', j')$), we can conclude that $T_{i,j} \leq T_{i',j'}$. In contrast, any move containing a right horizontal move or an up vertical move does not lead to a necessary ordering of the elements, since these moves go against the monotonicity of the elements in the same row and in the same column given above.

Consider any permutation $\pi \in \Pi$, represented as $L \times L$ binary matrix $\mathbf{P}_\pi$ with a single 1 in each row and column, where $\mathbf{I}_{\text{id}}$ is the identity matrix corresponding to the identity permutation id . We denote by $\mathcal{S}_\pi$ the support of $\mathbf{P}_\pi$, i.e., the list of the positions of its “ones”, i.e., $\mathcal{S}_\pi = \{(i, j) : [\mathbf{P}_\pi]_{i,j} = 1\}$. The set of values $\{f_\ell(x_{\pi(\ell)}) : \ell \in [L]\}$ are obtained by retaining the elements of $\mathbf{T}$ corresponding to the “ones” of $\mathbf{P}_\pi$. In particular, $T_{\min, \pi} = \min\{T_{i,j} : (i, j) \in \mathcal{S}_\pi\}$ is the minimum corresponding to permutation π appearing in the right-hand side of (2.38). A transposition consists of exchanging two rows of $\mathbf{P}_\pi$. Assume $(i, j) \in \mathcal{S}_\pi$ and $(i', j') \in \mathcal{S}_\pi$, and consider the permutation π' obtained from π by transposition of rows i and i' . It follows that $\mathcal{S}_{\pi'}$ contains the same elements of $\mathcal{S}_\pi$ with the exception of $(i, j), (i', j')$ which are replaced by $(i, j'), (i', j)$. The following statement is immediate (details are omitted for the sake of space limitation): consider $\mathbf{P}_\pi$ and two positions (i, j) and (i', j') in its support $\mathcal{S}_\pi$ and consider $\mathbf{P}'_\pi$ obtained from $\mathbf{P}_\pi$ by transposition of rows i and i' . If $(i, j) \vdash (\leftarrow, \downarrow) \dashv (i', j')$, then $T_{\min, \pi'} \geq T_{\min, \pi}$. We call such transposition a *minimum non-decreasing transposition*. Notice that any permutation $\pi \neq \text{id}$ has at least a pair of positions (i, j) and (i', j') in $\mathcal{S}_\pi$ such that $(i, j) \vdash (\leftarrow, \downarrow) \dashv (i', j')$. Hence, if π achieves the max in (2.38), then π' obtained by minimum non-decreasing transposition that exchanges rows i and j also achieves the same max-min. It follows

Figure A.1.: Obtaining permutations of order $L = 3$ from the permutations of order $L = 2$ by adding a row and a column (shaded).

that the Theorem 1 is proved by showing that any π can be transformed into the identity permutation by a sequence of minimum non-decreasing transpositions.

The proof follows by induction. For $L = 2$, $\begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix}$ can be turned into $\begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}$ by transposing the rows, and obviously $(1, 2) \vdash (\leftarrow, \downarrow) \dashv (2, 1)$. Therefore, the statement holds for $L = 2$. Suppose that the statement is proved for $L - 1$. Notice that we can obtain the $L!$ matrices of the order- L permutations from the $(L - 1)!$ matrices of the order- $(L - 1)$ permutations by inserting an additional row in all possible positions and column in last position with a single “one” at their intersection, to all the order- $(L - 1)$ matrices. Fig. A.1 shows this augmentation process to go from $L = 2$ to $L = 3$. For all order- L matrices with the additional “one” in position (L, L) there is nothing to prove, since the $(L - 1) \times (L - 1)$ upper left submatrix is an order- $(L - 1)$ permutation matrix, that we can transform into the identity by a sequence of minimum non-decreasing transpositions by the induction assumption. For all order- L matrices with the additional “one” in position (i, L) for some $1 \leq i \leq L - 1$, we notice that the last row must contain a “one” in position (L, j) for $j < L$. Hence, $(i, L) \vdash (\leftarrow, \downarrow) \dashv (L, j)$, i.e., the transposition of rows L and i is minimum non-decreasing. After such transposition, we have a one in position (L, L) and the upper left $(L - 1) \times (L - 1)$ upper left submatrix is an order- $(L - 1)$ permutation matrix, that can be transformed into the identity by a sequence of minimum non-decreasing transpositions. This concludes the proof.

B. Linear Programming

B.1. Proposed Scheme by Independent Sets of Interference Graph

In the following section, we show how to apply the optimization proposed in (4.10) to the interference scenario. This section result can be obtained for very small network. Unfortunately it has complexity of exponential. In this delivery scheme, users are divided into two groups like avalanche scheme. The first group contains users without any interference and the second group contains users who are receiving interference from neighboring helpers. Helpers can serve non-interference users simultaneously. The detailed description is as follows.

The number of multicast messages (each of which consists of $\frac{F}{\binom{L}{t'}}$ bits) for the non-interference users connected to helper h is denoted by

$$L_h = \sum_{r \in [L-t']} |P_{r,h}| \binom{L-r}{t'}, \quad (\text{B.1})$$

where $P_{r,h}$ represents the non-interference users connected to helper h which are in group $\mathcal{P}_r$, $\ell \in [L]$ (recall that $\mathcal{P}_r$ is the number of users in the ℓ -th group that have the same cache content as defined in section 4.2.5). Assume without loss of generality that $L_1 \geq L_2 \cdots \geq L_H$. We define $D_j := L_{H-j-1} - L_{H-j}$ for $j \in [H-2]$ and D_j for $j \in \{0, H-1\}$ will be defined later. For example, $D_1 = L_{H-2} - L_{H-1}$, $D_{H-2} = L_1 - L_2$.

The delivery phase is divided into H steps, each of which is denoted by step j where $j \in [0 : H]$. We define D_j as the delivery time (the number of time slots to finish the transmission, where the unit of time slot is one multicast message) of step j . For example, if one step contains 3 time slots, where in the q^{th} slot each of helper transmits one multicast message (each of which consists of $\frac{F}{\binom{L}{t'}}$ bits), we say the delivery time of this step is 3. The delivery scheme for step j is as follows.

- $j = 0$. During step 0, each helper $h \in [H]$ serves its non-interference users (i.e., first group users). At the end of step 0, helpers H and $H-1$ finish the transmission for their non-interference users. Here, we have $D_0 = L_{H-1}$.

- $j \in [H - 2]$. At the beginning of step j , each helper in $[H - j : H]$ has finished its transmission for its non-interference users. During step j , each helper in $[H - j - 1]$ serves its unserved first group users. Meanwhile, helpers in $[H - j : H]$ coordinately serve the unserved second group users whose connected helpers are all in $[H - j : H]$. The transmission scheme for the second group users will be clarified later. Here, we have $D_j := L_{H-j-1} - L_{H-j}$, e.g., $D_1 = L_{H-2} - L_{H-1}$, $D_{H-2} = L_1 - L_2$.
- $j = H - 1$. At the beginning of step $H - 1$, all helpers have finished their transmissions for non-interference users. During step $H - 1$, all helpers coordinately serve all unserved second group users. The delivery time of step $H - 1$ is denoted by D_{H-1} , which will be explained later.

Hence, the total delivery time is $\sum_{j=0}^{H-1} D_j = L_1 + D_{H-1}$.

Now we describe our scheme to transmit packets from helpers in $[H - j : H]$ to the second group users in step $j \in [H - 1]$. The set of nodes (helpers) that are not causing interference at the users side form an independent set, i.e., they have no common user. We define the family of the independent sets for step j as

$$\mathcal{I}_j = \{\mathcal{R} \mid \mathcal{R} \subseteq [H - j : H], |\mathcal{H}_k \cap \mathcal{R}| \leq 1 \ \forall k \in \mathcal{U}_{[H-j:H]}\}, \quad (\text{B.2})$$

where $\mathcal{U}_{\mathcal{S}}$ represents the set of users whose connected helpers are all in $\mathcal{S} \subseteq [H]$ (we do not consider non-interference users in this set). In addition, for each $h \in [H]$, we define

$$\mathcal{I}_j^h = \{\mathcal{R} \in \mathcal{I}_j : h \in \mathcal{R}\}. \quad (\text{B.3})$$

We define the family of sets of interference users, which are to receive the coded multicast messages. For sake of simplicity, for each $h \in [H]$ we also define (whose meaning will be explained in the following paragraph)

$$\Omega'_{h,j} = \{\mathcal{S}_1 \in \Omega' : \mathcal{U}_h \cap \mathcal{S}_1 \neq \emptyset, (\mathcal{S}_1 \cap \mathcal{U}_h) \setminus \mathcal{U}_{[H-j:H]} = \emptyset\}. \quad (\text{B.4})$$

We start from step $j = 1$. The set of bits transmitted by helper $h \in \{H, H - 1\}$ in this step is denoted by $\mathcal{B}_j^h$, where for each $\mathcal{S} \in \Omega'_{h,j}$,¹ we generate $|\mathcal{X}_{\mathcal{S}}^h|$ random linear combinations of $X_{\mathcal{S}}^h$, and put them in $\mathcal{B}_j^h$. The transmission is divided into $|\mathcal{I}_j|$ rounds, where in each round we focus on one independent set $\mathcal{R} \in \mathcal{I}_j$, and let each helper $h \in \mathcal{R}$ broadcast $\bar{y}_{\mathcal{R},j}^h F$ random linear combinations in $\mathcal{B}_j^h$, which are then removed from $\mathcal{B}_j^h$.

¹ $\mathcal{U}_h \cap \mathcal{S}_1 \neq \emptyset$ guarantees that $X_{\mathcal{S}_1}^h$ is useful to some user(s) connected to helper h . Notice that in step j , helpers in $[H - j - 1]$ are broadcasting packets to their non-interference users. Hence, these $\bar{y}_{\mathcal{R},j,\mathcal{S}_1}^h$ random linear combinations of $X_{\mathcal{S}_1}^h$ transmitted by helper h can be received without interference only by its connected users who are not connected to any helper in $[H - j - 1]$. Thus we have the constraint $(\mathcal{S}_1 \cap \mathcal{U}_h) \setminus \mathcal{U}_{[H-j:H]} = \emptyset$.

In step $j \in [2 : H - 1]$, for each $h \in [H - j : H]$, the initial state of $\mathcal{B}_j^h$ is $\mathcal{B}_{j-1}^h$, obtained by the last step. In addition, for each $\mathcal{S} \in \left(\Omega'_{h,j} \setminus \cup_{q \in [j-1]} \Omega'_{h,q} \right)$, we generate $|X_{\mathcal{S}}^h|$ random linear combinations of $X_{\mathcal{S}}^h$ and put them in $\mathcal{B}_j^h$. The transmission is also divided into $|\mathcal{I}_j|$ rounds, where in each round we focus on one independent set $\mathcal{R} \in \mathcal{I}_j$, and let each helper $h \in \mathcal{R}$ broadcast $\bar{y}_{\mathcal{R},j}^h F$ random linear combinations in $\mathcal{B}_j^h$, which are then removed from $\mathcal{B}_j^h$.

Similarly, we repeat the above procedure until step $H - 1$. In the proposed linear programming as follows, we search the optimal values of $\bar{y}_{\mathcal{R},j}^h$ which represents the delivery time in step j for set $\mathcal{R} \in \mathcal{I}_j$. Notice that, in step 1, only helpers H and $H - 1$ broadcast packets to their second group users, while in step 2, helpers in $\{H, H - 1, H - 2\}$ broadcast packets to their second group users, etc. In other words, for any helper $h \in [H]$, it starts to serve its second group user from step $\max\{H - h, 1\}$.

$$\begin{aligned} & \underset{\substack{y_{\mathcal{S}}^h, \bar{y}_{\mathcal{R},j}^h : \mathcal{S} \in \Omega', \\ h \in [H], j \in [\max\{H-h, 1\} : H-1], \mathcal{R} \in \mathcal{I}_j^h}}{\text{minimize}} & & \frac{L_1 + \sum_{\mathcal{R} \in \mathcal{I}} \max_{h \in \mathcal{R}} \bar{y}_{\mathcal{R},H-1}^h}{\binom{L}{L'}} \end{aligned} \quad (\text{B.5a})$$

$$\text{subject to } 0 \leq y_{\mathcal{S}}^h \leq 1, \text{ if } h \in \mathcal{H}_{\mathcal{S}}, \forall \mathcal{S} \in \Omega', \quad (\text{B.5b})$$

$$y_{\mathcal{S}}^h = 0, \text{ if } h \notin \mathcal{H}_{\mathcal{S}}, \forall \mathcal{S} \in \Omega', \quad (\text{B.5c})$$

$$\sum_{\mathcal{S} : k \in \mathcal{S}, \mathcal{C}_{\mathcal{S}} = \mathcal{T}} \sum_{h \in \mathcal{H}_k} y_{\mathcal{S}}^h \geq 1, \forall \mathcal{T} \in \Psi, \forall k : c_k \in \mathcal{T}, \quad (\text{B.5d})$$

$$\sum_{\mathcal{R} \in \mathcal{I}_j} \max_{h \in \mathcal{R}} \bar{y}_{\mathcal{R},j}^h \leq D_j, \forall j \in [H - 2], \quad (\text{B.5e})$$

$$\sum_{j \in [\max\{H-h, 1\} : H-1]} \sum_{\mathcal{R} \in \mathcal{I}_j^h} \bar{y}_{\mathcal{R},j}^h = \sum_{\mathcal{S} \in \Omega' : \mathcal{U}_h \cap \mathcal{S} \neq \emptyset} y_{\mathcal{S}}^h, \forall h \in [H], \quad (\text{B.5f})$$

$$\sum_{j' \in [j]} \sum_{\mathcal{R} \in \mathcal{I}_{j'} : h \in \mathcal{R}} \bar{y}_{\mathcal{R},j'}^h \leq \sum_{\mathcal{S} \in \Omega'_{h,j}} y_{\mathcal{S}}^h, \forall j \in [H - 1], \forall h \in [H - j : H]. \quad (\text{B.5g})$$

In this optimization, the delivery time in step $H - 1$ is

$$D_{H-1} = \sum_{\mathcal{R} \in \mathcal{I}} \max_{h \in \mathcal{R}} \bar{y}_{\mathcal{R},H-1}^h, \quad (\text{B.6})$$

and thus the objective function is as (B.5a). The constraint in (B.5d) represents the decodibility condition for the users, i.e., each user k is able to recover $W_{d_k, \mathcal{T} \setminus \ell}$ where user k is with cache configuration ℓ . The constraint in (B.5e) follows that the number of transmitted broadcasted packets by each helper in each step cannot exceed the delivery time. The constraint in (B.5f) makes sure that the all requested multicast messages are sent,

such that the proposed scheme is decodable. Lastly, the constraint in (B.5g) guarantees that in step $j \in [H - 1]$, each helper $h \in [H - j : H]$ can only transmit the random linear combinations in $\mathcal{B}_j^h$ to its connected users who are not connected to any helper in $[H - j - 1]$, in order to avoid interference.

Publication List

- [BMG18] M. Bayat, R. K. Mungara and G. Caire, Coded Caching in a Cell-Free SIMO Network, In *22nd International ITG Workshop on Smart Antennas(WSA)* , Bochum, Germany, 2018, pp. 1-8.
- [BMG19] M. Bayat, R.K. Mungara and G. Caire, Achieving Spatial Scalability for Coded Caching via Coded Multipoint Multicasting, In *IEEE Transactions on Wireless Communications*, vol. 18, no. 1, pp. 227-240, Jan. 2019.
- [BYC18] M. Bayat, C. Yapar and G. Caire, Spatially Scalable Lossy Coded Caching, In *15th International Symposium on Wireless Communication Systems (ISWCS)* , Lisbon, 2018, pp. 1-6.
- [BWC19] M. Bayat, K. Wan and G. Caire, Routing-Based Delivery in Combination-Type Networks with Random Topology, In *IEEE 20th International Workshop on Signal Processing Advances in Wireless Communications (SPAWC)* , Cannes, France, 2019, pp. 1-5.
- [BWC20] M. Bayat, K. Wan and G. Caire, Coded Caching over Multicast Routing Networks, In *arXiv preprint arXiv:2008.08900* (2020).

Bibliography

- [1] Joseph Abate and Ward Whitt. Numerical inversion of Laplace transforms of probability distributions. *ORSA Journal on computing*, 7(1):36–43, 1995.
- [2] V. K. Adhikari, Yang Guo, Fang Hao, M. Varvello, V. Hilt, M. Steiner, and Z. Zhang. Unreeling netflix: Understanding and improving multi-CDN movie delivery. In *2012 Proceedings IEEE INFOCOM*, pages 1620–1628, 2012.
- [3] M-S Alouini and Andrea J Goldsmith. Capacity of rayleigh fading channels under different adaptive transmission and diversity-combining techniques. *IEEE Transactions on Vehicular Technology*, 48(4):1165–1181, 1999.
- [4] M. M. Amiri and D. Gündüz. On the capacity region of a cache-aided gaussian broadcast channel with multi-layer messages. In *2018 IEEE International Symposium on Information Theory (ISIT)*, pages 1909–1913, 2018.
- [5] E. Bastug, M. Bennis, and M. Debbah. Living on the edge: The role of proactive caching in 5G wireless networks. *IEEE Communications Magazine*, 52:82–89, Aug. 2014.
- [6] D. Bethanabhotla, G. Caire, and M. J. Neely. WiFlix: Adaptive video streaming in massive MU-MIMO wireless networks. *IEEE Transactions on Wireless Communications*, 15(6):4088–4103, 2016.
- [7] B. Błaszczyszyn and M. K. Karray. Spatial distribution of the SINR in Poisson cellular networks with sector antennas. *IEEE Trans. on Wireless Commun.*, 15(1):581–593, Jan 2016.
- [8] Daniel Brélaz. New methods to color the vertices of a graph. *Communications of the ACM*, 22(4):251–256, 1979.
- [9] D. Cao, D. Zhang, P. Chen, N. Liu, W. Kang, and D. Gündüz. Coded caching with heterogeneous cache sizes and link qualities: The two-user case. In *2018 IEEE International Symposium on Information Theory (ISIT)*, pages 1545–1549, 2018.

- [10] M. Chiang, C. W. Tan, D. P. Palomar, D. O’neill, and D. Julian. Power control by geometric programming. *IEEE Transactions on Wireless Communications*, 6(7):2640–2651, 2007.
- [11] Thomas M Cover and Joy A Thomas. *Elements of information theory*. John Wiley & Sons, 2012.
- [12] William HR Equitz and Thomas M Cover. Successive refinement of information. *IEEE Transactions on Information Theory*, 37(2):269–275, 1991.
- [13] C. Geng, N. Naderializadeh, A. S. Avestimehr, and S. A. Jafar. On the optimality of treating interference as noise. *IEEE Transactions on Information Theory*, 61(4):1753–1767, 2015.
- [14] G. George, R. K. Mungara, A. Lozano, and M. Haenggi. Ergodic spectral efficiency in MIMO cellular networks. *IEEE Trans. on Wireless Commun.*, 16(5):2835–2849, May 2017.
- [15] A. Ghorbel, K. Ngo, R. Combes, M. Kobayashi, and S. Yang. Opportunistic content delivery in fading broadcast channels. In *GLOBECOM 2017 - 2017 IEEE Global Communications Conference*, pages 1–6, Dec 2017.
- [16] N. Golrezaei, A. F. Molisch, A. G. Dimakis, and G. Caire. FemtoCaching and device-to-device collaboration: A new architecture for wireless video distribution. *IEEE Comm. Magazine*, 51(4):142–149, April 2013.
- [17] Piyush Gupta and Panganmala R Kumar. The capacity of wireless networks. *IEEE Trans. Inf. Theory*, 46(2):388–404, 2000.
- [18] Jad Hachem, Nikhil Karamchandani, and Suhas Diggavi. Content caching and delivery over heterogeneous wireless networks. In *Computer Communications (INFOCOM), 2015 IEEE Conference on*, pages 756–764. IEEE, 2015.
- [19] M. Haenggi. On distances in uniformly random networks. *IEEE Trans. on Inform. Theory*, 51(10):3584–3586, Oct 2005.
- [20] Martin Haenggi. *Stochastic geometry for wireless networks*. Cambridge University Press, 2012.
- [21] Parisa Hassanzadeh, Elza Erkip, Jaime Llorca, and A Tulino. Distortion-memory tradeoffs in cache-aided wireless video delivery. In *Communication, Control, and Computing (Allerton), 2015 53rd Annual Allerton Conference on*, pages 1150–1157. IEEE, 2015.

-
- [22] A. M. Ibrahim, A. A. Zewail, and A. Yener. On coded caching with heterogeneous distortion requirements. In *2018 Information Theory and Applications Workshop (ITA)*, pages 1–9, 2018.
 - [23] Alan Jeffrey and Daniel Zwillinger. *Table of integrals, series, and products*. Academic press, 2007.
 - [24] M. Ji, A. Tulino, J. Llorca, and G. Caire. Caching-aided coded multicasting with multiple random requests. In *2015 IEEE Information Theory Workshop (ITW)*, pages 1–5, 2015.
 - [25] Mingyue Ji, Antonia M Tulino, Jaime Llorca, and Giuseppe Caire. Caching in combination networks. In *Signals, Systems and Computers, 2015 49th Asilomar Conference on*, pages 1269–1273. IEEE, 2015.
 - [26] Junchen Jiang, Vyas Sekar, and Hui Zhang. Improving fairness, efficiency, and stability in http-based adaptive video streaming with festive. In *Proceedings of the 8th International Conference on Emerging Networking Experiments and Technologies*, pages 97–108, New York, NY, USA, 2012. Association for Computing Machinery.
 - [27] S. Jin, Y. Cui, H. Liu, and G. Caire. A new order-optimal decentralized coded caching scheme with good performance in the finite file size regime. *IEEE Trans. Commun.*, pages 1–1, 2019.
 - [28] Sian Jin, Ying Cui, Hui Liu, and Giuseppe Caire. Uncoded placement optimization for coded delivery. In *16th International Symposium on Modeling and Optimization in Mobile, Ad Hoc, and Wireless Networks (WiOpt)*, pages 1–8. IEEE, 2018.
 - [29] Kai Wan, D. Tuninetti, and P. Piantanida. On the optimality of uncoded cache placement. In *Proc. IEEE Inf. Theory Workshop (ITW)*, pages 161–165, Sep. 2016.
 - [30] Nikhil Karamchandani, Urs Niesen, Mohammad Ali Maddah-Ali, and Suhas Diggavi. Hierarchical coded caching. *IEEE Trans. Infor. Theory*, 62(6):3212–3229, Jun. 2016.
 - [31] Ralf Koetter and Muriel Medard. An algebraic approach to network coding. *IEEE/ACM Trans. Netw.*, 11(5):782–795, 2003.
 - [32] E. Lampiris and P. Elia. Adding transmitters dramatically boosts coded-caching gains for finite file sizes. *IEEE Journal on Selected Areas in Communications*, 36(6):1176–1188, 2018.

- [33] David Lecompte and Frédéric Gabin. Evolved multimedia broadcast/multicast service (embms) in LTE-advanced: overview and Rel-11 enhancements. *IEEE Communications Magazine*, 50(11), 2012.
- [34] Rhyd Lewis. *A guide to graph colouring*, volume 7. Springer, 2015.
- [35] Dong Liu, Binqiang Chen, Chenyang Yang, and Andreas F Molisch. Caching at the wireless edge: Design aspects, challenges, and future directions. *IEEE Comm. Magazine*, 54(9):22–28, 2016.
- [36] M. A. Maddah-Ali and U. Niesen. Fundamental limits of caching. *IEEE Trans. on Inform. Theory*, 60(5):2856–2867, May 2014.
- [37] M. A. Maddah-Ali and U. Niesen. Decentralized coded caching attains order-optimal memory-rate tradeoff. *IEEE/ACM Trans. on Netw.*, 23(4):1029–1040, Aug 2015.
- [38] F Javier Martin-Vega, F Javier Lopez-Martinez, Gerardo Gomez, and Mari Carmen Aguayo-Torres. Multi-user coverage probability of uplink cellular systems: A stochastic geometry approach. In *Global Communications Conference (GLOBECOM), 2014 IEEE*, pages 3989–3994. IEEE, 2014.
- [39] T. L. Marzetta, E. G. Larsson, H. Yang, and H. Q. Ngo. *Fundamentals of massive MIMO*. Cambridge Univ. Press, Cambridge, U. K., 2016.
- [40] T. Matsuta and T. Uyematsu. Caching-aided multicast for partial information. In *2016 IEEE International Symposium on Information Theory (ISIT)*, pages 600–604, July 2016.
- [41] N. Mital, D. Gündüz, and C. Ling. Coded caching in a multi-server system with random topology. In *Proc. IEEE Conf. Wireless Commun. Netw. (WCNC)*,, pages 1–6, April 2018.
- [42] R. K. Mungara, D. Morales-Jimenez, and A. Lozano. System-level performance of interference alignment. *IEEE Trans. on Wireless Commun.*, 14(2):1060–1070, Feb 2015.
- [43] N. Naderializadeh, M. A. Maddah-Ali, and A. S. Avestimehr. Fundamental limits of cache-aided interference management. *IEEE Trans. Inf. Theory*, 63(5):3092–3107, May 2017.
- [44] Navid Naderializadeh and Amir Salman Avestimehr. ITLinQ: A new approach for spectrum sharing in device-to-device communication systems. *IEEE journal on selected areas in communications*, 32(6):1139–1151, 2014.

-
- [45] K. Ngo, S. Yang, and M. Kobayashi. Scalable content delivery with coded caching in multi-antenna fading channels. *IEEE Trans. on Wireless Commun.*, 17(1):548–562, Jan 2018.
 - [46] Colm Art O’cinneide. Euler summation for fourier series and Laplace transform inversion. *Stochastic Models*, 13(2):315–337, 1997.
 - [47] S. Park, O. Simeone, and S. Shamai. Joint optimization of cloud and edge processing for fog radio access networks. In *Proc. IEEE Int. Symp. Inf. Theory (ISIT)*, pages 315–319, July 2016.
 - [48] E. Parrinello, A. ünsal, and P. Elia. Fundamental limits of coded caching with multiple antennas, shared caches and uncoded prefetching. *IEEE Transactions on Information Theory*, 66(4):2252–2268, 2020.
 - [49] Konstantinos E Parsopoulos, Michael N Vrahatis, et al. Particle swarm optimization method for constrained optimization problems. *Intelligent Technologies–Theory and Application: New Trends in Intelligent Technologies*, 76(1):214–220, 2002.
 - [50] Georgios Paschos, Ejder Bastug, Ingmar Land, Giuseppe Caire, and Mérouane Debah. Wireless caching: Technical misconceptions and business barriers. *IEEE Comm. Magazine*, 54(8):16–22, 2016.
 - [51] K. Poularakis and L. Tassiulas. On the complexity of optimal content placement in hierarchical caching networks. *IEEE Trans. on Commun.*, 64(5):2092–2103, May 2016.
 - [52] B. Rimoldi and R. Urbanke. A rate-splitting approach to the Gaussian multiple-access channel. *IEEE Trans. on Inform. Theory*, 42(2):364–375, March 1996.
 - [53] Krzysztof Rusek, José Suárez-Varela, Paul Almasan, Pere Barlet-Ros, and Albert Cabellos-Aparicio. Routenet: Leveraging graph neural networks for network modeling and optimization in SDN. *arXiv preprint arXiv:1910.01508*, 2019.
 - [54] Yago Sánchez de la Fuente, Thomas Schierl, Cornelius Hellge, Thomas Wiegand, Dohy Hong, Danny De Vleeschauwer, Werner Van Leekwijck, and Yannick Le Louédec. IDASH: Improved dynamic adaptive streaming over http using scalable video coding. In *Proceedings of the Second Annual ACM Conference on Multimedia Systems*, pages 257–264, New York, NY, USA, 2011. Association for Computing Machinery.
 - [55] Heiko Schwarz, Detlev Marpe, and Thomas Wiegand. Overview of the scalable video coding extension of the H. 264/AVC standard. *IEEE Transactions on circuits and systems for video technology*, 17(9):1103–1120, 2007.

- [56] A. Sengupta, R. Tandon, and O. Simeone. Fog-Aided wireless networks for content delivery: Fundamental latency tradeoffs. *IEEE Trans. on Inform. Theory*, 63(10):6650–6678, Oct 2017.
- [57] Avik Sengupta, Ravi Tandon, and T Charles Clanc. Layered caching for heterogeneous storage. In *Signals, Systems and Computers, 2016 50th Asilomar Conference on*, pages 719–723. IEEE, 2016.
- [58] P Series. Propagation data and prediction methods for the planning of short-range outdoor radiocommunication systems and radio local area networks in the frequency range 300 mhz to 100 ghz. *tech. rep., ITU, Tech. Rep. ITU-R*, 2015.
- [59] K. Shanmugam, N. Golrezaei, A. G. Dimakis, A. F. Molisch, and G. Caire. Femto-caching: Wireless content delivery through distributed caching helpers. *IEEE Trans. on Inf. Theory*, 59(12):8402–8413, Dec 2013.
- [60] S. P. Shariatpanahi, G. Caire, and B. Hossein Khalaj. Physical-layer schemes for wireless coded caching. *IEEE Transactions on Information Theory*, 65(5):2792–2807, 2019.
- [61] S. P. Shariatpanahi, S. A. Motahari, and B. H. Khalaj. Multi-server coded caching. *IEEE Trans. on Inform. Theory*, 62(12):7253–7271, Dec 2016.
- [62] Kaiming Shen and Wei Yu. FPLinQ: A cooperative spectrum sharing strategy for device-to-device communications. In *2017 IEEE International Symposium on Information Theory (ISIT)*, pages 2323–2327. IEEE, 2017.
- [63] Q. Shi, M. Razaviyayn, Z. Luo, and C. He. An iteratively weighted MMSE approach to distributed sum-utility maximization for a MIMO interfering broadcast channel. *IEEE Transactions on Signal Processing*, 59(9):4331–4340, 2011.
- [64] G. Vettigli, M. Ji, A. M. Tulino, J. Llorca, and P. Festa. An efficient coded multicasting scheme preserving the multiplicative caching gain. In *IEEE Conf. on Computer Commun. Workshops (INFOCOM WKSHPS)*, pages 251–256, April 2015.
- [65] K. Wan, M. Ji, P. Piantanida, and D. Tuninetti. Caching in combination networks: Novel multicast message generation and delivery by leveraging the network topology. In *Proc. IEEE Int. Conf. on Commun. (ICC)*, pages 1–6, May 2018.
- [66] K. Wan, D. Tuninetti, M. Ji, and G. Caire. A novel cache-aided fog-ran architecture. In *2019 IEEE International Symposium on Information Theory (ISIT)*, pages 2977–2981, 2019.

- [67] Kai Wan, Mingyue Ji, Pablo Piantanida, and Daniela Tuninetti. Novel outer bounds and inner bounds with uncoded cache placement for combination networks with end-user-caches. *arXiv preprint arXiv:1701.06884*, 2017.
- [68] Qifa Yan, Xiaohu Tang, Qingchun Chen, and Minquan Cheng. Placement delivery array design through strong edge coloring of bipartite graphs. *IEEE Commun. Letters*, 22(2):236–239, 2018.
- [69] Q. Yang and D. Gündüz. Coded caching and content delivery with heterogeneous distortion requirements. *IEEE Transactions on Information Theory*, 64(6):4347–4364, 2018.
- [70] Xinping Yi and Giuseppe Caire. ITLinQ+: An improved spectrum sharing mechanism for device-to-device communications. In *2015 49th Asilomar Conference on Signals, Systems and Computers*, pages 1310–1314. IEEE, 2015.
- [71] Qian Yu, Mohammad Ali Maddah-Ali, and A Salman Avestimehr. The exact rate-memory tradeoff for caching with uncoded prefetching. In *Proc. IEEE Int. Symp. Inf. Theory (ISIT)*, pages 1613–1617, Jun 2017.
- [72] A. A. Zewail and A. Yener. Coded caching for combination networks with cache-aided relays. In *Proc. IEEE Int. Symp. Inf. Theory (ISIT)*, pages 2433–2437, June 2017.